

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

137

$\frac{1}{4}$ Section Corner to Sections 34 and 35.
Found - 15" White Oak S. $85\frac{1}{2}^{\circ}$ E. 656.0 ft., cut open & found good scribing "TV"
34" White Oak N. $76\frac{1}{2}^{\circ}$ E. 345.8 ft., shows very plain scar. Didn't open.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W $\frac{1}{4}$ S34/S35
New BT's: 26" White Oak S. $16\frac{1}{2}^{\circ}$ E. 47.2 ft. Mkd: $\frac{1}{4}$ S35 CS BT.
16" White Oak N. $85\frac{1}{2}^{\circ}$ E. 83.3 ft. Mkd: $\frac{1}{4}$ S35 CS BT.
No trees readily available west of line.
Note - Corner is 37 ft. north of E. & W. Fence Line.

138

$\frac{1}{4}$ Section Corner to Sections 23 and 26.
Found - 24" White Oak S. $69\frac{1}{2}^{\circ}$ E. 277.9 ft., prev. opened, scribing visible
on partly rotted face "BT".
Did not find N. W. B. T.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W $\frac{1}{4}$ S23
S26
New BT's: 11" White Oak N. 44° E. 21.5 ft. Mkd: $\frac{1}{4}$ S23 CS BT.
6" White Oak S. 5° W. 19.5 ft. Mkd: $\frac{1}{4}$ S26 CS BT.
Note - Corner is approx. 70 ft. south of E. & W. Fence Line.

139

Int. "L" Corner D. L. C. No. 47.
Found - 11" W. Oak S. 20° W. 58.1 ft., has been opened prev., scribing
visible "RP" & what appears to be "10". See Ren. # 49.
12" White Oak N. 89° W. 26.4 ft., prev. opened, portions of scribe
marks visible on partly rotted face.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W Int. "L" DLC 47
New BT's: 9" W. Oak N. 88° W. 24.5 ft. Mkd: Int. "L" DLC 47 CS BT.
9" W. Oak S. 81° E. 22.2 ft. Mkd: Int. "L" DLC 47 CS BT.
Note - Corner is in Fence Corner, Fences E. - W. & S.
This is a renewal of Corner as set by Roberts in 1905.

FO. OK 7/90
1990-0066
COR. PO. OK
2/26/99
K. Raco - Co.
SURV. OFFICE
C.S. 6/24

140

Mst. Estrly. S.E. Corner D. L. C. No. 47.
Found - Bl. Oak Snag N. 59° E. 38.3 ft. Tree approx. 12" when marked.,
face rotted, scribe marks visible "RP". See Ren. #50.
No trace of Original Bearing Trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W E SE DLC 47
New BT's: 8" W. Oak N. 61° W. 3.1 ft. Mkd: E SE DLC 47 CS BT.
8" W. Oak S. 32° W. 37.7 ft. Mkd: E SE DLC 47 CS BT.
Note - $\frac{3}{4}$ " Iron Pipe bears N. 59° E. 5.2 feet.

176

141

Wit. Cor. to Mst. Strly. S.E. Cor. D. L. C. No. 47.
Found - 48" Bl. Oak, now dead, opened scar on W. side & fd. good scribing "C47"
appears to be Robert's scribing. Old scar on N. side but face
rotted away, Tree is corner.
Set - Wit. Cor. 10 ft. West. - Brass Cap Mkd: County Surveyor's Office, 1964
T26S R6W W.C. S. SW DLC 47, 10 ft. E. to Cor.
New BT's: 15" W. Oak N. 41° W. 42.6 ft. Mkd: W.C. SE DLC 47 CS BT.
15" W. Oak S. 44° E. 15.2 ft. Mkd: W.C. SE DLC 47 CS BT.
Note - Chiseled cross (3" x 3") on Rock Outcrop 4 ft. x 5 ft. x 30 in. above
ground bears N. 57° E. 8.0 ft. from W. C.
Fences North & West from D. L. C. Corner.

191

RE-RENEWED CORNER NO.

142

Section Corner to Sections 25 - 26 - 35 - 36.
Found - 24" Bl. Oak N. 28° W. 4.6 ft., opened & found good scribing "B".
Portion of Burned Oak Stump in Stump hole N. 5° E. 31.7 ft.
Part of old Laurel Snag S. 55° E. 59.4 ft., shows scar.
No trace of S. W. Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W S26 | S25
S35 | S36
Rescribed - 24" Bl. Oak N. 28° W. 4.6 ft. Mkd: T26S R6W S26 CS BT.
New BT's: 25" Bl. Oak S. 50° W. 49.5 ft. Mkd: T26S R6W S35 CS BT.
25" Bl. Oak S. 6° E. 37.9 ft. Mkd: T26S R6W S36 CS BT.
6" Wh. Oak N. 80° E. 47.9 ft. Mkd: S25 CS BT.

Milo E. Godfrey, Deputy Co. Surv.
Vernon Tracy - Wm. Stoffel - M. Stone.
July 1964
C. S. File No. 52/87