

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

New BT's: 20" White Oak N.67°W. 7.9 ft. Mkd: 1/4 S16 CS BT.
24" Bl. Oak S.82°E. 7.6 ft. Mkd: 1/4 S21 CS BT.
Note - Corner is in draw. Re-erect Rock mound around Brass Cap.

1/4 Section Corner to Sec. 30, T26-6W. & Sec. 25, T26-7W. 148
Found - 1/2" I. Pipe set by Eppstein in 1939. Ren. #82
34" D. Fir N.87°E. 17.3 ft., shows very good scars.
42" Old Bl. Oak N.77°W. 79.2 ft., shows good scra.
Old Oak Stump N.76°E. 60.7 ft., old face rotted away, but
old axe marks visible.
New BT: 7" Doug. Fir West 25.4 ft. Mkd: 1/4 S25 CS BT.
Note - Eppstein's N.E. Fir BT. & Orig. N.W. Oak are still in good condition.
Corner Pipe is in N. & S. fence Line, 15 ft. N. of fence Corner,
(Fences North, South & West).

S. E. Corner D. L. C. No. 38 - Int. L.D. L. C. #62. 149
Found - 30" W.Oak S.30°E. 39.6 ft., opened several years ago, scribing
visible on edge of old face "82", most of face rotted away.
Rock set by Cain, "X" on top. See Ren. #71.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R6W SE DLC 38 | DLC 62 Set alongsd. Rock.
New BT's: 13" W.Oak N.18°W. 28.0 ft. Mkd: SE DLC 38 CS BT.
5" W.Oak S.82°W. 50.9 ft. Mkd: DLC 62 CS BT.
Note - A fence corner, fences N. W. & E. SE., bears North 18 ft. from corner.

S. E. Corner D. L. C. No. 37. *End. O.K. MAY, 1981 SEE 188-1* 150
Found - Rock (4" x 6" Top) set by BBIrving, 1945, See Ren. No. 46.
40" Bl.Oak S.43°E. (not S.57°E.) 72.9 ft., very plain scars visible.
Cut Cross in Top of Rock & scribed one New Tree, as follows:
25" Pine N.41°E. 157.4 ft. Mkd: SE DLC 37 CS BT.
Note - Corner is in fence corner 14 ft. North of N. edge of concrete
frame for cattle guard.

S. E. Corner D. L. C. No. 62. 151
Found - Rock (4" x 4" top) with good "X" on top, top flush with
level of ground. See Ren. #72.
34" Black Oak, very plain scar visible, in good condition,
bearing N.14°E., 108 ft. from corner.
New BT: 8" Madrone S.33°W. 80.5 ft. Mkd: S. E. DLC 62 CS BT.

Sec. Cor. to Secs. 7 & 18, T26-6W. & Secs. 12 & 13, T26-7W. 152
Found - 20" D.Fir S.41°W. 52.0 ft., prev. opened, good scribing visible.
27" Black Oak N.78 1/2°E. 39.4 ft., shows fairly good scar.
25" Black Oak S.80°E. 59.0 ft., shows very plain scar. #198
32" Black Oak N.23 1/4°W. 210.0 ft., shows very good scar.
All trees, above, alive and in good condition. See Ren. #31.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T26S R7W S 12 | S 7 R6W
S 13 | S 18
New BT: To replace tree 210 ft. from corner.
6" D. Fir N.15°W. 17.0 ft. Mkd: S12 CS BT.
Note - Corner is along N.W. Side of old road or trail along foot of Hill.

1/4 Corner to Sections 27 and 34. 153
Due to Road Construction, we set Witness Corner 175.0 feet East
of 1/4 Corner recorded in Ren. #90, which is;-
5/8" Iron Rod for Corner & BT's:
12" W.Oak N.4°W. 12.7 ft., shows scribe.
8" Oak Snag S.46°W. 13.9 ft., shows scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T26S R6W W.C. 175 ft. W. to 1/4 S 27
S 34
New BT's: 6" Laurel S.61°E. 13.8 ft. Mkd: W.C. 1/4 S34 CS BT.
6" B.Oak N.40 1/2°E. 101.0 ft. Mkd: W.C. 1/4 S27 CS BT.
Witness Corner lies approx. 25.0 ft. East of small ravine.

Milo E. Godfrey, Deputy Co. Surv.
Vernon R. Tracy & Jack Barnett.
August 1964
C. S. File No. 52/87

Vernon R. Tracy
Terry Connell
July 8, 1965
C. S. File No. 52/87