

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 26 S. T. S. R. 6 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

164

John M. Powell  
Frank Jones & W. Penley  
Nov. 1969 C.S. 54/95

Section Corner to Sections 13 - 14 - 23 - 24.  
Found - No trace of 1961 Co. Surv. Brass Cap, See Ren. #88.  
20", now 21" W. Oak N.21°W. 55.3 ft., scribe visible.  
9", now 11" W. Oak S.62°W. (Rec.S65W) 36.6 ft., shows scar &  
parts of scribe.  
7", now 9" W. Oak N.28°E (RecN31E) 18.7 ft., shows scar.  
9", now 10" B. Oak, S.42°E. 44.5 ft., some scribing visible.  
Set - New Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 6 W  
Office S 14 S 13  
1969 S 23 S 24

All Bearing Trees O. K.

11/14/69

165

James W.  
Byron,  
Co. Surv.  
C.S. File  
No.  
54/97

1/4 Corner to Sec. 7, T26-6 and Sec. 12, T26-7W.  
Prorated 1/4 Corner. Found 1 1/2" Iron Pipe S.79°34'24"E. 34.31 ft.  
from 1/4 corner, unrecorded.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T. 26 S. R  
Office 7 S12 S 7 6  
1970 W 1/4 W  
New BT's: 12" D. Fir S.16°30'E. 43.8 ft. mkd: "1/4 S 7 CS BT".  
9" D. Fir N.83° W. 11.8 ft. mkd: "1/4 S12 CS BT".

1/15/70

166

Don E.  
Garrett  
For: WLS Assoc.  
Rolled Map  
RM 1 - 78

1/4 Corner to Sections 30 and 31.  
Found - 1/4 Corner set in intersection of N-S Fence and E-W Fence.  
Old Bearing Tree (28" Oak, down) fd. edges of reversed side  
of lower face bears S.55°E. 11.2 ft.  
Set - Brass Cap stamped " 1/4 Cor. 30 T.26S R.6W  
31 RS 544  
New BT's: 8" White Oak bears S.75 1/2°E. 52.5 ft. scribed "1/4 S31 BT."  
33" Bl. Oak bears N.47°W. 39.0 ft. scribed "1/4 S30 BT".

Feb. 1970

MARCH 71

167

1/4 Corner to Sections 11 and 14.  
No evidence of original found - Set by proportionate measurement.  
Set - Brass Cap, from which:  
24" B. Oak scribed "T26S R6W 1/4 S11 BT" bears N.40°W. 29.8 ft  
10" B. Oak scribed "T26S R6W 1/4 S14 BT" bears S.40°E. 31.7 ft

Section Corner to Sections 11 - 12 - 13 - 14.  
Set by double proportionate measurement.  
Set - Brass Cap 6" below surface of ground in open field, #197  
Just East of small draw.  
6" Ash scribed "T26S R6W S11 BT" bears N.23-1/2 W. 33.0 ft.  
24" B. Oak scribed "T26S R6W S13 BT" bears S.48-1/4°E. 876.1 ft.

169

1/4 Corner to Sections 2 and 11.  
No evidence of original, Set by proportionate measurement.  
Set Brass Cap, from which:  
12" W. Oak scribed "T26S R6W 1/4 S11" bears S.79°W. 59.5 ft.  
Fence Corner bears S. 1°E. 10.5 ft. (fences running East,  
West, and South.

170

S.W. Corner D.L.C. #47  
Found - Bolt with square head at corner. Ren. #27  
20" D. Fir, N.88 1/2°E., 42.2 ft. shows good scar. (This tree  
will probably be cut) Ren. #102  
14" Laurel, now stob, S.33°E., 23.0 ft. scribe visible "BT"  
New BT's - 22" W. Oak, S.37°E., 27.3 ft. scribed SW DLC 47 CS BT.  
18" Triple Laurel, N.39°E., 48.0 ft. scribed SW DLC 47 CS BT.  
Note: This cor. lies on top of high bank of river. Approx. 150.0 ft.  
south of house.

10/6/72

John Powell  
J. Heritage  
C.S. File 52/87

Victor M. McLind  
For: H. & D. Land Co. Inc.  
January, 1972 Map File M 42 - 56