

Douglas County Surveyor's Record of  
Government Corners Renewed

26 T. S. 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

Victor McLind  
For: L. Cornish  
May 1976  
M 60 - 16

1/4 Corner between Secs. 25 and 36.  
Brass cap not found. Ren. #51  
Reset cor. from BT's:  
A 10" W. Oak bears N.34 1/2°E., 63.4 ft.  
A 8" W. Oak bears S.80°E., 31.5 ft.  
Set - 5/8" x 30" I. Rod at corner.

175

May 1976

L. E. Monrean  
A. V. Cangie  
J. H. Cook  
Co. Surveyors Office  
June 17, 1976  
C.S. 59/18

East Southeast Corner DLC #47 Ren. #'s 50 and 140  
Found - 3/4" I. P. in east-west fence line. No bearing trees found.  
Note - The position of this monument fits for position of the  
East Southeast corner DLC #47 according to the County Surveyor's  
Office survey number C.S. 59/22, and M 61 - 16.

176

Set - As the brass cap set in 1964 is not at the DLC corner, I remove  
it and destroy scribing on bearing trees. I SET Brass cap at  
ESE corner DLC 47 stamped "County Surveyors Office" 1976

ESE  
DLC 47  
T 26 S  
R 6 W

Set - 3/4" Iron pipe beside brass cap.  
BT's - A 5" White Oak, bears N.69°W., 31.1 ft. Tree double blazed &  
scribed "ESE DLC 47 CS BT"  
A 7" White Oak, bears N.16°E., 15.3 ft. Tree double blazed &  
scribed "ESE DLC 47 CS BT"

Magnetic declination 20° East.

6/17/76

177

Sec. Cor. for Sec. 6; & Sec. 31 T25-6; & Sec. 36 T25-7; & Sec. 1 T26-7  
Found - Brass cap 6" above ground on a 1" I.P. and stamped OLS 536

Brass cap is on inside edge of  
a dike for a pond  
Ren. #173  
R T 25 S  
6 S 36 S 31 R  
W S 1 S 6 W  
T 26 S  
1974

We stamped correction on BC to read: "OLS 536"

R T 25 S R  
7 6 S 36 S 31 6  
W S 1 S 6 W  
T 26 S  
1974  
CS 1977

Found - A 42" Oak, now down, bears N.61°W., 46.0 ft. double blazed and  
scribed "S 35 BT".

Set - A metal fence post with survey marker sign 1.0 ft. north of BC.  
Set a 5/8" I.R. 30" long 3" above ground with an alum. cap stamped  
"B.O. 1" bears N.24°E., 74.0 ft. Set a metal fence post with  
survey marker sign 1.0 ft. west of I.R., point is on top of dike  
at west side of pond.  
Set a 5/8" I.R. 30" long 4" above ground with an alum. cap stamped  
"B.O. 2" bears S.4°W., 105.8 ft. Set a metal fence post with survey  
marker sign 1.0 ft. West of I.R. point is on edge of upper field,  
A 7" Pear tree bears N.67°W., 107.3 ft. double blazed and marked  
"T25S R67 S36 CS BT"

6/28/77

178

Section Corner for Sec. 36; and Sec. 31, T26-5; Sec. 1, T27-6; Sec. 6,  
T27-5.

Found - A 1" O.D. Iron pipe firmly set in a mound of stone. Ren. #62-A  
We find depressions in the ground and fragments of oak roots at  
the approx. record positions of the orig. NE, SE, and NW bearing  
trees. There is no identifiable evidence at these positions.  
A 10" now 13" Fork of a W. Oak, alive with well healed double  
blaze bears S.63°W., 27.8 ft. (Measured to center of root crown  
at ground level). Rec. S.55°W., 27.8 ft.) Ren. #62-A.  
A 6" now 10" W. Oak, alive with well healed double blaze bears  
S.14°E., 15.4 ft. (Rec. S.14°E., 15 ft.)  
A 6" now 9" W. Oak, alive with well healed double blaze bears N.70°E  
48.0 ft. (Rec. N.73°E., 48 ft.)

Gary L. Langlitz  
S.J. Flause  
F.C. Silagy  
Doug. Co. Surveyors  
Office  
April 24, 1978  
C.S. 59/46

R. B. Kimberling  
P. L. Earle  
Douglas Co. Surveyors Office  
June 28, 1977  
C.S. 59/34

3/77

JAN 78