

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

178

C O N T. ----10" now 17" W. Oak, alive with well healed double blaze bears N.48°W., 73.3 ft. (Rec. N.50°W., 74.1 ft.)

Set - At the location of the found 1" O.D. Iron pipe., we set a 1" x 30" I. Pipe with brass cap attached 28 inches in the ground, surrounded with rock and the found I.P. alongside.
We mark: Douglas Co. Surveyor

T 26 S
R 6 W S 36 S 31 R 5 W
S 1 S 6

Gary L. Langlitz
F.C. Silagy
S.J. Flause
Doug. Co. Surveyors
Office
April 24, 1978
C.S. 59/46

No new accessories

4/24/78

179

Section corner for Secs. 6 and 5; and Secs. 31,32 of T25-6

Found - A 9"x9"x17" Rock marked "CS" on north face. Ren. #79
A 5/8" I. Rod set next to rock. (Unrecorded)
A root hole bears S.20°W., 32 ft. (orig.)
A 4" Oak bears S.72°E., 11.1 ft. tree down and rotted.
A 10" B Oak now 14" bears N.7°E., 61.3 ft. with well healed double blaze.
A 10" Madrone now 14", was removed by cat work, has tag and shows good scar.
A 6" Madrone, now 10" trunk on triple trunk tree bears N.38°W., (rec. N.36°W.), 38.8 ft. to face, 39.8 ft. to center of base with well healed double blaze.
Set - A 1" x 36" I.P. with brass cap marked "Douglas County Surveyor" T25S S31 S32 S6 S5 T26S R6W 1979. Cap 5" above ground rod 9" above ground. Cap in position of stone. Placed stone next to cap and rod east side of cap.

New Accessories:

A 12" Madrone bears S.31°E., 50.4 ft. scribed "S5 T26S R6W CS BT" in double blaze.
A 11" Oak bears S.33°W., 158.5 ft. scribed "S6 T26S R6W CS BT" in double blaze.

3/15/79

Karen Reed
S. J. Flause
Doug. Co. Survey-
or Office
March 15, 1979
C.S. 60/24

Northwest Corner DLC #42 and a wit. cor. to NW cor. DLC #42

Found - A 1" x 36" I. Pipe with brass cap marked "County Surveyors Office" T26S R6W NW DLC 42 1964, leaning against SE BT. Ren. #124
I do not find 1954 brass cap (Ren. #61) or a 1 1/2" I.P. (Ren. #19)
A 24" B. Oak, now 26" bears S.24°W., 75.7 ft. with well healed double blaze. Ren. #61
A 20" B. Oak bears S.15°E., 30.5 ft. with well healed double blaze.
A N. S. fence bears west 39.0 ft. (Ren. #124 dist. 40.0 ft.)
Set - 5/8" x 30" I. Rod with alum. cap marked "Douglas County Surveyor" NW DLC 42 1979" at proper brgs & dist. from fd. BT's. Buried 6" below surface
A 1" x 36" I.P. with brass cap marked "County Surveyors Office" T26S R6W WC east 30 ft. NW DLC 42 1979, set west, 30.0 ft. from I. rod.

BT - 20" B. Oak bears S.54°E., 48.8 ft. from wit. cor. Ren. #124

Corner falls in gravel drive.

(sketch attached to field notes in C.S. file)

180

Karen Reed
P. L. Earle
Doug. Co. Survey-
ors Office
April 18, 1979
C.S. 60/24

4/18/79

SE 1/16 Corner for Section 16.

Found - A 1" I.P. with brass cap set 16" out of ground stamped: T26S R6W SE 1/16 + S16 1968 LS 536" as recorded by G. Baughman County Surveyors records M35 - 61
A 20" W. Oak now a 20" Diam. Oak stump, 24" high, bears S.28°W., 39.4 ft. (Rec. S.26°45'W., 39.4 ft.). Lower blaze remains partially healed, "BT" scribing visible.
A 16" now 22" Madrone bears N.87°E., 40.0 ft. (Rec. S.86°W. 40.0 ft.) with a partially healed double blaze, scribing SE 1/16 BT visible. The blaze on this madrone faces the present location of the brass cap. The cap was found firmly set in ground. For these reasons along with the agreement of the other bearing and distances, we determine this bearing to the madrone was recorded in reverse.

New BT - A 6" W. Oak bears S.27°E., 27.2 ft. scribed "SE 1/16 S16 CS BT" on a double blaze.

Note: Corner lies 50 ft. north of dirt road course S-W.

P. Earle
F. Silagy
Doug. Co. Survey-
ors Office
Oct. 16, 1979
C.S. 60/34

10/16/79