

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 26      T. S.      R 6      R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORR, 21881

195

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
May 4, 1990  
C.S. 64/9

Center 1/4 Corner for Section 3  
Found - A 6 3/4" dia. Auto axle flange with a 3 1/2" dia. raised center hub. (Rec. 6" flange) found flush with ground. From M16-25 Northwest corner of concrete barn foundation bears S.82 1/2°E., 84.5 ft. (Rec. S,80°E., 84.5 ft.) Per M16-25 Fence corner noted in Ren. #123 is knocked over.  
New Accessories:  
5" dia. Ash double blazed and scribed "C 1/4 S3 CS BT" bears S.65 1/2°W., 47.0 ft.  
6" dia. Ash double blazed and scribed "C 1/4 S3 CS BT" bears N.63°E., 97.4 ft.  
2 ft. square concrete footing for electric generating windmill, center bears N.50 1/2°W., 168.6 ft.  
Corner lies near the intersection of a south and west running fence lines.  
- - - - - 5/4/90

196

1/4 Corner for Sections 20 and 21  
Found - 3/4" I.D. iron pipe found 1" below ground. (M 1 - 69) Ren #6  
27" now 35" dia. W. oak with a fully healed single blaze bears N.70°W., 289.2 ft. Ren. No. 128  
(No other BTs found)  
Set - The found 3/4" iron pipe is referenced, I.P. measures 25" long when removed.  
A 2 3/8" dia. brass cap on a 1 1/4" O.D. x 31" long I.P. is set at referenced position. BC/IP protrudes 4" above ground with found 3/4" I.P. set 2" below ground along north side of BC/IP. Cap is stamped "Douglas County Surveyors T26S 1/4 S20 | S21 R6W 1990 Office"  
New BTs - 3" dia. W. oak double blazed and scribed "X BT" bears S.55 1/4°W., 73.2 ft.  
4" dia. W. Oak double blazed and scribed "X BT" bears N.88 1/4°E., 53.9 ft.  
6" dia. Madrone bark scribed "1/4 S21 CS BT" bears S.46°E., 17.6 ft.  
- - - - - 4/9/90

197

Section Corner for Sections 11, 12, 13 and 14.  
Found - A 2 1/2" dia. brass cap on an iron pipe flush with ground. Cap is unmarked. Ren. No. 168  
6" now 13" Ash with a fully healed lower and partially healed upper blaze scribe mark visible "6" bears N.23 1/2°W., 33.0 ft. (agrees with record) Ren. No. 168  
24" now 29" B. oak, no blazes visible bears S.48 1/4°E., 876.1 ft. (agrees with record) Ren. No. 168  
New BTs - 21" dia. apple, bark scribed "T26S R6W S13 CS BT" bears S.1 3/4°E., 138.2 ft.  
11" dia. Ash double blazed and scribed "T26S R6W S11 CS BT" bears N.1 3/4°W., 97.0 ft.  
- - - - - 5/8/90

198

Section Corner for Secs. 7 and 18; and Secs. 12 and 13 of T.26-7  
Found - 1964 DCSO 2 1/2" BC on a 1 1/2" O.D. I.P. protruding 4" above ground. BC/IP leans 9.4 ft. north of plumb. Ren. No. 152  
14" now 31" dia. B. oak with a fully healed blaze bears N.78 1/2°E., 39.4 ft. (agrees with rec.) Orig. BT.  
(No other original BTs found)  
8" now 23" dia. 1 1/2 ft. tall D. fir stump with a fully healed lower blaze, bears S.41°W., 52.6 ft. (Rec. S.41°W., 52.0 ft. Ren. #31)  
14" now 25" dia. B. oak with a fully healed double blaze bears S.80 1/2°E., 59.0 ft. (agrees w/rec.) Ren. No. 31  
24" now 35" dia. 2 1/2 ft. tall Oak stump with a fully healed lower blaze bears N.23 1/4°W., 210.0 ft. Ren. No. 31  
6" now 7" dia. 1 1/2 ft. tall D. fir stump with a fully healed lower blaze bears N.13 1/4°W., 17.0 ft. (Rec. N.15°W., 17.0 ft.) Ren. #152  
New BTs - 8" dia. D. fir double blazed and scribed "T26S R7W S12 CS BT" bears N.75 1/4°W., 15.9 ft.  
11" dia. D. fir double blazed and scribed "T26S R7W S13 CS BT" bears S.12 1/2°W., 91.0 ft.  
Corner lies at the intersection of a north and west running fence lines.  
- - - - - 4/10/90

Douglas County Surveyors Office  
Randall Smith - Stephen Flause  
April - May 1990  
C.S. 64/9