

Douglas County Surveyor's Record of
Government Corners Renewed

26

T. S.

7

R. W. W. M.

ROSE CHAPMAN CO., EUGENE, ORE. 91002

- ✓ 1/4 COR. BETWEEN 14 and 15
Reset from one stump with "B.T." on it. Drove an Iron Pipe in the ground and marked the following trees:
Fir 30" dia. bears N.70°W., 24.5 ft.
W. Fir 18" dia. bears S.46°E., 21.9 ft. *SEARCHED FOR, NOT FOUND MAR. 1966 Terry L.P.*
- ✓ SECTION CORNER BETWEEN 9, 10, 15 and 16
Reset from one original B.T. and two stumps. I drove an Iron Pipe and marked the following trees.
Fir 18" dia. bears S.88°W., 24.0 ft.
Fir 30" dia. bears S.20°E., 27.9 ft.
Fir 30" dia. bears N.71°E., 9.8 ft.
Fir 20" dia. bears North 21.7 ft. *54*
- ✓ WITNESS CORNER TO SE CORNER J. H. GILLAM D.L.C. 46
Original corner washed out by River. This corner is one chain short of original. I marked the following new B.T.s - MAR. 1966 - SEARCHED FOR, NOT FOUND. VRT. L.P.
Black Oak 16" dia. bears N.59 1/2°W., 39 lks. *13*
- ✓ N.W. CORNER D.L.C. 46
Marked the following trees
Laurel 8 ins. dia. bears S.45°E., 102 lks.
Laurel 10 ins. dia. bears S.42 1/2°W., 84 lks. *MAR. 1966 - SEARCHED FOR, NOT FOUND VRT C.S. 573 221 14*
- ✓ N.E. CORNER D.L.C. 46
Marked the following B.T.
Black Oak 30" dia. bears S.35°W., 200 lks. *4 15*
- ✓ CORNER SECTIONS TO 22, 23, 27, and 26.
Set from Old B.T. in section 23. Other trees gone.
Set 1 1/2" x 18" Pipe. Marked the following new B.T.s
Fir 20" dia. bears S.25°E., 38.0 ft.
Fir 24" dia. bears N.62 1/2°E., 20.5 ft.
White Oak 14" dia. bears N.80°W., 107 ft. *67 16*
No tree available in section 27
- ✓ 1/4 CORNER BETWEEN 5 and 4
Set 4" x 4" x 30" Fir Stake from old B.T. and marked new B.T.s as follows
Fir 24" dia. bears N.66°E., 24 ft. *NOT FOUND V.R.T. 12/3/68 97 17*
Fir 24" dia. bears S.49°E., 22.3 ft.
- ✓ THE 1/4 COR. BETWEEN SECTIONS 34 and 35
Reset this corner from one old B.T. Scribe marks plain.
Set a 2" x 30" Iron Pipe 20 feet East on side of road for Witness Corner from which
A 10" White Oak bears N.43 1/2°E., 42.0 ft. *SEE PEN #45 (1908) 71 18*
A 12" White Oak bears S.55 1/2°E., 61.5 ft.
- ✓ MOST NORTHERLY N.E. COR. D.L.C. 43 (STUCKER)
Found original Sandstone Rock, to which this corner is tied, N.504.2' and rock at N.W. corner of this D.L.C. at fence corner from which this corner is set. Mr. Long and Mr. Thompson witness that location for this corner should be in the center of the county road (as extended North) to the South. Set 4" Round Oak Post 1" Steel Bar in the center for corner from which fence cor. bears W.26'. *70 19*
- ✓ 1/4 CORNER EAST SIDE OF SECTION 25.
Set 1" x 36" Iron Pipe 8" above ground for corner from stump of B.T. in Sec. 30. Original B.T. good in Section 25. Cut B.T. out on stump and marked new B.T.
Fir 18" dia. bears N.87°E., 17.3 ft. *56 20*
Old B.T. in section 25 good.

11
G. G. Stewart D.C.S.
Wit. C. Crocker
Blumburg, Will Long,
Carpenter
December 1, 1922
C.S. 1013, P. 131
M-2-B

12
W. F. Briggs
Feb. 30, 1892

13
C. S. VOL. 1, PAGE 208-209
F.B.A. PAGE 18
G.S. FILE 18/54

14
J. H. Wolford
Surveyor
Wit. B.A. Lane
P.D. Wolford
Jas. F. Jeffries
Sept. 13, 1934

15
F.C. Frear
Wit. E. Richardson
B.A. Lane
Carl Becker
May 18, 1935
L.E. Thompson
June 1934
NO REF. FOUND
NO REF. FOUND

16
F.C. Frear
Wit. B.A. Lane
Will Long
Carl Becker
Jno. Paulson
L.E. Thompson
May 18, 1935
L.E. Thompson
June 1934
NO REF. FOUND
NO REF. FOUND

17
Arthur Boyer
Wit. B.A. Lane
Will Long
H.L. Eppstein
Fred T. Reece
Husband of Mrs. Anne Emery Thompson
1939
NO REF. FOUND

18
H.L. Eppstein
Wit. B.A. Lane
Fred T. Reece
APRIL 12 1939
NO REF. FOUND

19
H.L. Eppstein
Wit. B.A. Lane
Fred T. Reece
APRIL 12 1939
NO REF. FOUND

20
NO REF. FOUND