

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 26 S. T. S. R. 7 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21991

61

$\frac{1}{4}$  Corner to Sections 11 and 14.  
Found -  $\frac{1}{2}$ " I. P. & BT's. as recorded in Ren. # 8.  
Orig. 12", now 28" B.Oak N. 61° W. 119.5 ft., prev. opened  
& rebark scribed in 1922 by Stewart, "CS  $\frac{1}{4}$ ".  
No trace of Other Orig. BT.  
14", now 26", D. Fir S. 43° W. 99.1 ft., shows good scar.  
(We do not open)  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T26S  $\frac{1}{4}$   $\frac{S 11}{S 14}$  R7W  
(Deposit old corner pipe alongside.)  
New BT's: 8" D. Fir N. 85° E. 19.7 ft. Mkd:  $\frac{1}{4}$  S11 CS BT.  
12" D. Fir S. 42° W. 7.0 ft. Mkd:  $\frac{1}{4}$  S14 CS BT.  
Note - Corner lies at fence corner on steep N. slope, fences N.-W.-E.

FDOK PER PIESKE  
M106-25 5/83

62

$\frac{1}{4}$  Corner to Sections 10 and 15.  
Found -  $\frac{1}{2}$ " I. Pipe & Stump of BT. as recorded in Ren. #10.  
30", now 48" Fir S. 50° W. 28.0 ft., bark scribed, now stump.  
No trace Orig. BT's. or other BT.  
Set - Brass Cap in mound of Stone 24" high & Mkd: County Surveyor's Office, 1966 T26S  $\frac{1}{4}$   $\frac{S 10}{S 15}$  R7W  
New BT's: 7" W. Fir N. 73° E. 86.6 ft. Mkd:  $\frac{1}{4}$  S10 CS BT.  
No trees close in Section 15.  
Note - Corner lies 15.0 ft. E. of SW - NE fence on steep, rocky N. slope.

63

Sec. Corner to Sections 14 - 15 - 22 - 23.  
Found -  $\frac{3}{4}$ " I. Pipe with elbow on Top as recorded Ren. # 2.  
30", now 41", Fir N. 18° W. 27.0 ft., Stump, no scribe found.  
36", now 48" Fir Stump S. 63 $\frac{1}{2}$ ° W. 46.1 ft., bark scribe.  
30", now 42" Fir Stump S. 42 $\frac{1}{2}$ ° E. 22.7 ft., bark faced off,  
badly flaked, no scribe.  
12", now 24" Fir East 41.9 ft. (recorded as 31.9 ft.) Open  
& find "BT" scribe.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T26S  $\frac{S 15}{S 22}$  |  $\frac{S 14}{S 23}$  R7W  
New BT's: 5" W. Fir N. 64° E. 12.2 ft. Mkd: S14 CS BT.  
14" B. Oak N. 31° W. 23.9 ft. Mkd: T26S R7W S15 CS BT.  
6" W. Fir S. 20° W. 23.1 ft. Mkd: S22 CS BT.  
5" D. Fir S. 23° E. 24.7 ft. Mkd: S23 CS BT.  
Note - W. - E. Fence bears 8.0 ft. South.

64

$\frac{1}{4}$  Corner to Sections 16 and 15.  
Found - Orig. 30", now 48", Fir N. 10° W. 26.4 ft. Prev. opened &  
"BT" scribe on face. Open higher & find axe notch just  
above "BT". Also very faint " $\frac{1}{4}$ " bark scribe.  
Orig. 10", now 24" Fir N. 85° E. 8.6 ft., prev. opened,  
no scribing found.  
No trace of Stewart's BT's. as recorded in Ren. # 5.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T26S  $\frac{1}{4}$  S 16/S 15 R7W  
New BT's: 8" Laurel N. 17° W. 63.4 ft. Mkd:  $\frac{1}{4}$  S16 CS BT.  
31" D. Fir N. 58° E. 49.2 ft. Mkd:  $\frac{1}{4}$  S15 CS BT.  
Note - This corner lies on very steep East slope.

65

$\frac{1}{4}$  Corner to Sections 15 and 22.  
Found -  $\frac{3}{4}$ " I. Pipe with elbow on top, as recorded in Ren. # 4.  
10", now 12", W. Fir N. 54° E. 27.5 ft., rotted Stump 6" high, no scribe.  
18", now 26" W. Fir S. 4 $\frac{1}{2}$ ° W. 23.7 ft., now stump. Open & find scribe.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T26S  $\frac{1}{4}$   $\frac{S 15}{S 22}$  R7W  
(Deposit I.P. alongside)  
New BT's: 10" W. Fir N. 26° W. 8.4 ft. Mkd:  $\frac{1}{4}$  S15 CS BT.  
21" D. Fir S. 22° W. 37.5 ft. Mkd:  $\frac{1}{4}$  S22 CS BT.  
Note - E. - W. Fence bears South 3.0 ft.

Vernon "Ray" Tracy  
Mike Stone & Jack Heritage  
March 1966  
C. S. File No. 54/23