

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 26 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

77

$\frac{1}{4}$  Corner to Sections 8 and 17.  
Found - Orig. 24", now 38", N. 80° W. 13.9 ft. (alive), shows faint bark scribe "S" on upper face & fragmentary scribe on lower face. Hole, approximately where S. W. Orig. BT. would have been.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T26S  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{8}{17}$  R7W  
New BT's: 13" D. Fir N. 57° E. 3.9 ft. Mkd:  $\frac{1}{4}$  S 8 CS BT.  
16" D. Fir S. 7° W. 17.2 ft. Mkd:  $\frac{1}{4}$  S17 CS BT.  
Rebark scribe alongside Orig. Scribe, as follows:  
38" Cedar N. 80° W. 13.9 ft. Mkd:  $\frac{1}{4}$  S 8 CS BT.  
Note - Corner lies on South edge of bench.

Section Corner to Sections 16 - 17 - 20 - 21.  
Found - 1959 Cadastral Brass Cap appropriately marked.  
11" Fir S. 16 $\frac{1}{2}$ ° E. 79.5 ft., Now Snag 25.0 ft. high, shows "T26S R7W S21 BT" scribe on unhealed blaze.  
14" Fir S. 71 $\frac{3}{4}$ ° W. 87.8 ft., Alive, shows scribe on unhealed blaze.  
10" Fir N. 13 $\frac{1}{4}$ ° W. 60.1 ft., now turned out, laying face down. Original BT's. also turned out.  
New BT's: 16" W. Fir N. 5° W. 110.2 ft. Mkd: T26S R7W S20 CS BT.  
16" W. Fir S. 51° E. 71.4 ft. Mkd: T26S R7W S21 CS BT.  
No trees convenient to N. E.  
Note - Corner lies approx. 500 ft. North of old logging road.

$\frac{1}{4}$  Corner to Sections 17 and 20.  
Found - Orig. 60", now 72" Fir S. 20° W. 11.2 ft. (Orig. Fld. nts. call for 6" Fir Find very old bark scribe "S" & faced area now burned at base of tree where BT. would have been. Open & find ring count reveals approx. 6" of growth.  
No trace of Laurel to N. W.  
Set - Brass Cap Mkd: County Surveyor's Office, 1966 T26S  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{17}{20}$  R7W  
New BT's: 15" D. Fir S. 67° W. 27.1 ft. Mkd:  $\frac{1}{4}$  S20 CS BT.  
8" W. Fir N. 33° W. 29.0 ft. Mkd:  $\frac{1}{4}$  S17 CS BT.  
Note - Corner lies 20 ft. North of old logging road, cut off to South of line

Sec. Cor. to Secs. 4 & 5, T26-7 and Secs. 32 & 33, T25-7.  
Found - Orig. 30", now 50" Fir N. 80° E. 18.5 ft., shows old bark scribe "S R7W" & fragmentary scribe. Alive.  
Orig. 30", now 43" Fir N. 50° W. 39.6 ft., shows "S" bark scribed & fragmentary letters. Alive.  
Other BT's. down.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T25S R7W  $\frac{S}{S}$   $\frac{32}{5}$  |  $\frac{S}{S}$   $\frac{33}{4}$   
New BT's: 10" Maple N. 50° W. 10.0 ft. Mkd: T25S R7W S32 CS BT.  
8" D. Fir S. 63° W. 18.2 ft. Mkd: T26S R7W S5 CS BT.  
19" D. Fir S. 22° E. 24.6 ft. Mkd: T26S R7W S4 CS BT.  
Note - Corner lies 4.0 ft. east of small, dry creek, course S curving to S.E.

$\frac{1}{4}$  Corner to Sec. 33, T25-7W. & Sec. 4, T26-7W.  
Found - Orig. 24", now 33" Laurel S. 60° W. 18.5 ft., prev. opened, upper face rotted away. Open lower & find "B" scribed, reverse. Ring count impossible being too close together.  
Orig. 12", now 30" Fir N. 80° W. 19.8 ft., shows very old scar & renovation scar.  
Set - Brass Cap 2.0 ft. N. W. of fence corner, course E. & S. Mkd: County Surveyor's Office 1966 T25S R7W  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{33}{4}$   
New BT's: 14" D. Fir S. 9 $\frac{1}{2}$ ° W. 27.0 ft. Mkd:  $\frac{1}{4}$  S 4 CS BT.  
6" W. Fir N. 47° W. 33.9 ft. Mkd:  $\frac{1}{4}$  S33 CS BT.  
Note - Corner lies approx. 100 ft. W. of small draw, course S. E.

Vernon "Ray" Tracy  
Mike Stone & Jack Heritage  
May and June 1966  
C. S. File No. 54/23

Vernon "Ray" Tracy  
Joe Brady & Jack Heritage  
June 14, 1966  
C. S. File No. 54/10