

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

106

1/4 Corner for Sec. 2 and Sec. 35 of T25-7

Found - Orig. 18" B. Oak, now 40" measured below fork, half dead, bears S.89 3/4°W., 532.0 ft. Found opened blaze and scribing "BT".
Orig. 12" B. Oak, now 37" dead trunk (tree is triple trunked at ground) bears N.89 3/4°W., 522.7 ft. Found opened blaze and scribing "B" in cut out section. Ren. #102
A 4 ft. mound of stone at corner location.
A 4 ft. x 4 ft. outcropping in sandstone ledge marked "X B0" bears N.35°W., 56.2 ft.
Set - A 1" I.P. 36" long set 33" in ground in mound of stone 4 ft. base to cap marked: T25S R7W 1/4 S35 S2 T26S 1977.
Set - A metal fence post 2.0 ft. North of brass cap with sign attached.
New B.O.- A 2' x 3' outcropping in sandstone ledge marked "B0" on horiz. surface with 3" "X" on surface facing corner bears S.13 1/2°E., 63.7 ft.
Set a metal fence post 18" West of "X" with witness post sign attached.
Note: Equipment used, Ranger lazer beam distance meter and Gurley transit for bearing.

R. B. Kimberling, Doug. Co. Surveyors
Office
P. Earle
May 19, 1977
C.S. 59/34

5/19/77

107

Sec. Cor. for Sec. 1; Sec. 6 T26-6; Sec. 31 T25=6; Sec. 36-T25-7

Found - Brass cap 6" above ground on a 1" I.P. and stamped OLS 536

Brass cap is on inside edge
of a dike for a pond. Ren.
#98

	T	25	S
R	S	36	S 31
6	S	1	S 6
W	T	26	S
		1974	

R
5
W

We stamped correction on BC to read:

"OLS 536"
T 25 S
R S 36 | S 31 R
7 6 S 1 | S 6 6
W T 26 S W
1974
CS 1977

R. B. Kimberling
P. L. Earle
Douglas Co. Surveyors Office
June 28, 1977
C.S. 59/34

Found - A 42" Oak, now down, bears N.61°W., 46.0 ft. double blazed and scribed "S 35 BT"
Set - A metal fence post with survey marker sign 1.0 ft. north of B.C.
Set a 5/8" I.R. 30" long 3" above ground with an alum. cap stamped "B.O. 1" bears N.24°E., 74.0 ft. Set a metal fence post with survey marker sign 1.0 ft. west of I.R., point is on top of dike at west side of pond.
Set a 5/8" I.R. 30" long 4" above ground with an alum. cap stamped "B.O. 2" bears S.4°W., 105.8 ft. Set a metal fence post with survey marker sign 1.0 ft. west of I.R. point is on edge of upper field.
A 7" Pear tree bears N.67°W., 107.3 ft. double blazed and marked "T25S R67 S36 CS BT".

6/28/77

108

S.W. Corner Pierce DLC #49
Set - 12" x 12" x 15" deep, oonc. block.
1" Pipe 35 feet east of corner
2" pipe 40 ft. south of corner.

A. Boyer For:
A.E. Thompson R
Nov. 1937
C.S. 30/39

11/37

109

S.E. Corner Pierce DLC #49
Set - Concrete Block 12" x 12" x 15"

11/37

110

Sec. cor. common to Sec's 7, 8, 18, & 17.

Found - Orig. cor. monument and B.Cap set by Byron (Ren.#28) not found.

BT's - Orig. 20" Fir, now 42" stump, bears N.85°E., 15.2-ft. This tree cut low...no scribing remains.
Orig. 18" Fir, now 32", bears N.82 1/2 °W., 38.1-ft. (orig. Rec. N.85°W., 40.3-ft.). Bark scribed: T R W remains.
Stump hole at record bearing & dist. to SE orig. BT remains
Note - Face measurement to orig. diameter used for distances to the original bearing trees.

Larry E. Monrean
Deputy Doug. County
Surveyors Office
T.R. Plouff, witness
Sept. 29, 1981
C.S. 61 / 27