

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26

T. S.

R 7

R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

FO. OK 7/91  
J. ARZMAN 1991-46

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Jan. 5, 1990  
C.S. 64/5

Witness Corner for 1/4 Corner Section 36; and Sec. 31 of T.26-6 118  
Found - 1967 2 1/2" dia. brass cap on a 1 1/4" O.D. iron pipe that protrudes  
4" above ground. Ren. #82  
5/8" iron rod set at a position for 1/4 corner in Ren. #82, is  
under AC in road. A strong metal reading was taken at a  
point 30 ft. west of W.C.  
16" now 19" dia. W. oak with fully healed double blaze bears  
S.16°W., 16.3 ft. (agrees well with rec) Ren. #82  
5/8" iron rod property pin bears West, 1.19 ft. (agrees well  
with record) See M 35 - 17  
5/8" iron rod property pin bears N. 1 1/2°W., 59.87 ft. (Rec.  
N.1°08'09"W., 60.01 ft.) See M 35 - 17

New Accessories:

- 5/8" iron rod with yellow plastic cap marked L.S. 1075" bears  
S.50 3/4°W., 78.90 ft.
- 5/8" iron rod with alum. cap (CRRW 10+00.00 PT. on South side  
of Cleveland Lp Dr.) bears N.19 1/2°E., 197.40 ft.
- 5/8" Iron rod with alum. cap (CRRW 10+46.76 PC on South side of  
Cleveland Lp Dr.) bears N.32 3/4°E., 202.36 ft.

Corner lies 1 1/2 ft. North of the intersection of a North-South and East  
running fence line.

\_ 1/5/90 \_

FO. 11-91  
G. BAUGHMAN  
M 114-24

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
April 10, 1990  
C.S. 64/9

Section Corner for Secs. 12 and 13; and Secs. 7 and 18 of T.26-6 119  
Found - 1964 DCSO 2 1/2" BC on a 1 1/2" O.D. I.P. protruding 4" above ground  
BC/IP leans 0.4 ft. north of plumb. Ren. #57  
14" now 31" dia. B. oak with a fully healed blaze bears N.78 1/2°E.,  
39.4 ft. (agrees with record) Original BT.  
(No other original BTs found)  
8" now 23" dia. 1 1/2 ft. tall D. fir stump with a fully healed lower  
blaze, bears S.41°W., 52.6 ft. (Rec. S.41°W., 52.0 ft. Ren. #47)  
14" now 25" dia. B. oak with a fully healed double blaze bears  
S.80 1/2°E., 59.0 ft. (agrees w/rec) Ren. No. 47  
24" now 35" dia. 2 1/2 ft. tall Oal stump with a fully healed lower  
blaze bears N.23 1/4°W., 210.0 ft. Ren. No. 47  
6" now 7" dia. 1 1/2 ft. tall D. fir stump with a fully healed lower  
blaze bears N.13 1/4°W., 17.0 ft. (Rec. N.15°W., 17.0 ft. Ren. #57)  
New BTs - 8" dia. D. fir double blazed and scribed "T26S R7W S12 CS BT"  
bears N.75 1/2°W., 15.9 ft.  
11" dia. D. fir double blazed and scribed "T26S R7W S13 CS BT"  
bears S.12 1/2°W., 91.0 ft.

Corner lies at the intersection of a north and west running fence lines.

\_ 4/10/90 \_

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Terrie Franssen  
Jan. 17, 1991  
C.S. 64/13

Section Corner for Secs. 3 and 4; and Secs. 33 and 34 of T.25-7 120  
Found - 2 1/2" dia. 1966 County brass cap on a 1 1/2" O.D. I.P., protruding  
14" above ground. Ren. No. 75  
1 1/8" O.D. axle shaft protrudes 3" above ground. Ren. No. 27  
Axle shaft is south 0.4 ft. from brass cap.  
15" now 24" dia. 5 ft. high D. fir stump with a fully healed  
double blaze, bears S.25°W., 8.6 ft. (Rec. S.30 1/2°W.,  
8.6 ft. in BLM resurvey) Ren. No. 27  
14" now 20" dia. D. fir with a fully healed single blaze, bears  
S.71 1/2°E., 96.0 ft. (Rec. S.66°E., 96.0 ft.) 1975 BLM  
(BTs from Ren. No. 75 are gone.)  
New BTs- A multi trunked elder berry double blazed and scribed "X BT"  
on 12" dia. near trunk, bears N.41 1/2°E., 83.9 ft.  
5" dia. B. oak double blazed and scribed "X BT" bears  
S.78°W., 17.4 ft.  
7" dia. pistol butt maple double blazed and scribed "T25S R7W  
S33 CS BT" bears N.59°W., 104.5 ft. to center of trunk at  
upper blaze.

\_ 1/17/91 \_