

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21881

Section Corner of Sections 28, 29, 32, and 33, det. from O.B.T's: 11
12" D.Fir Snag bears N.50°E. 4 lks. with partial scribe marks.
10" D.Fir bears S.52°E. 65 lks., down and decayed.
14" D.Fir bears S.57°W. 8 lks., down and decayed.
10" D. Fir Snag bears N.49°W. 33 lks. with axe mks., other mks.
destroyed by fire.

Set an Iron Pipe 3' long 2" in diam., 28" in the ground mkd. RS404
from which new bearing trees:

6" D.Fir bears N.64°E. 10 lks. mkd. T26SR8W S28 RS404 BT.
18" D.Fir bears S.10°E. 21 lks. mkd. T26S R8W S33 RS404 BT.
10" D.Fir bears S.77½°W. 9 lks. mkd. T26S R8W S32 RS404 BT.
12" D.Fir bears N.33°W. 19 lks. mkd. T26S R8W S29 RS404 BT.

¼ Section Corner Sections 28 and 29. 12

Set at proportionate distance. Find no evidence of the Orig. Corner.
Set an Iron Pipe 3' long, 1½" diam., 28" in the ground Mkd.

RS404, from which:
22" D. Fir bears N.37°E. 46 lks. mkd. ¼ S28 RS404 BT.
26" D.Fir bears S.24°W. 37 lks. mkd. ¼ S29 RS404 BT.

Section Corner of Sections 20, 21, 28 and 29. 13

This corner falls on bedrock in the bed of a stream.

Set an iron pipe 3' long, 2" in diam, on bedrock with a mound
of stone to the top, mkd. RS404, from which the only original
evidence of this corner is an X mkd. on the rock bears N.60°E.,
40 lks. dist. A prominent rock bears S.18°W., 26 lks. dist.,
but I am unable to find the X.

New BT's: 12" W.Fir bears N.67½°E. 59 lks, mkd. T26S R8W S21 RS404 BT.
8" Cedar bears S.82½°E. 48 lks. mkd. T26S R8W S28 RS404 BT.
8" Hemlk bears S.42½°W. 42 lks. mkd. T26S R8W S29 RS404 BT.
18" Alder bears S.18½°W. 56 lks. mkd. T26S R8W S20 RS404 BT.

¼ Section Corner to Sections 21 and 28. 14

Point for ¼ corner at proportionate dist. No evidence of the
Original Corner.

Set an Iron Pipe 3' long 1½" in diam. 28" in the gr.Mkd. RS404
from which:

16" D.Fir bears N.21°E. 21 lks. mkd. ¼ S21 RS404 BT.
18" D.Fir bears S.75°E. 14 lks. mkd. ¼ S28 RS404 BT.

Section Corner of Sections 21, 22, 27 and 28. 15

Monumented with an Iron Pipe 2" in diam, 10" above the ground,
mkd. RS404 from which:

8" Chinq. bears N.8½°E. 31 lks. mkd. T26S R8W S22 RS404 BT.
16" D.Fir bears S.55½°E. 56 lks. mkd. T26SR8W S27 RS404 BT.
22" D.Fir bears S.15°W. 70 lks. mkd. T26S R8W S28 RS404 BT.
9" ChinQ. bears N.61½°W. 32 lks. mkd. T26S R8W S21 RS404 BT.

¼ Section Corner of Sections 32 and 33, det. from Orig. BT's: 16

50" D.Fir bears East 33 lks. mkd. ¼ with other mkd. healed.
50" D.Fir sawed stump, bears S.85°W., 46 lks. mkd. BT.

Set an Iron Pipe 3 ft. long, 1½" diam., 28" in the ground, mkd.
RS404 from which:

20" Hemlock bears S.28°W. 25 lks. mkd. ¼ S32 RS404 BT.

¼ Section Corner to Sections 23 and 26. 17

Point for ¼ sec. cor. at prop. dist. Find no evidence of
the original corner.

Set an iron pipe 3 ft. long 1½" in diam., 28" in the gr.
mkd. RS 404, from which:

24" Cedar bears N.59°E. 58 lks. mkd., ¼ S26 RS404 BT.
28" D.Fir bears S. 7°W., 85 lks. mkd.; ¼ S26 RS404 BT.

MARVIN C. RAMSEY
For J. H. Baxter & Co.
July 1960
C.S. File No. 51/105
51/41

Marvin C. Ramsey
For J.H. Baxter & Co.
July 1960
C.S. File 51/116

RE-RENEWED, SEE CORNER NO. #71