

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

1/4 Corner common to Sections 21 and 22.

Found no evidence of 8" Fir BT.

Set - 1 1/2" Iron pipe with brass cap. Referenced with
"W" nails and plates.

New BT's: 24" Fir, S.25°E., 47.3 ft.
32" Fir, N.04°W., 54.5 ft.

May, 1972

50 Triangle Engineer
ing co.
May, 1972
C.S. 55/251
M 44 - 79

North 1/4 Corner to Section 2. (T27-8)

Set - 2" Pipe with Brass Cap, from which:

10" Hemlock bears N.18°E. 3.0 ft. (Weyco Tag & "W" nail)

7" Hemlock bears N.77 1/2°W. 13.7 ft. (Weyco Tag & "W" nail)

8" Hemlock bears S.68 1/2°W. 2.0 ft. (" " " ")

March, 1973

51 Templin, Craig L.
For:
Weyerhaeuser
C.S. File
55/285

1/4 Corner, Sections 34 and 35.

Found - 52" Orig. D. Fir. Opened face & found scribe "1". Face burned &
axe marks vis. Rescribed "1/4 S34 BT", bears N.55°W., 158.4 ft.
(Record 36")

Set - Brass cap mkd. T26S R8W, 1/4 S34, S35 1973.

New BT's - 12" D. Fir, scribed "1/4 S35 BT", bears N.44°E., 15.0 ft.

10" D. Fir, Scribed "1/4 S34 BT", bears S.53°W., 5.9 ft.

52
Fd 3/90 CS 63/104

Shaner Engineering
for Hub Lumber Co.
M 49 - 33
August 16, 1973

Section corner, sections 27, 26, 34 and 35.

Set - Brass cap mkd. T26S, R8W, WM S27, S26, S34, S35, 1973

New BT's - 12" D. Fir, scribed "T26S, R8W S27 BT", bears N.84°W, 27.4ft.

10" D. Fir, scribed "T26S, R8W, S26 BT" bears N.43°E., 32.1 ft.

10" D. Fir, scribed "T26S, R8W, S34 BT" bears S.61°W., 40.9 ft.

10" D. Fir, scribed "T26S, R8W, S35 BT" bears S.67 1/2°E., 10.8 ft.

53
Fd 7/96
c.s. 63/127

Sec. Cor. for Secs. 25-26-35-36.

Found - 3/4" x 15" I.P.

60" D. Fir, orig. BT, bark scribes vis., bears S.15°E.,
241.2 ft. (Rec. 30" fir, 211.2 ft.)

30" D. Fir, orig. BT, face vis., bears S.2°W., 183.4 ft.
(Rec. 12" Fir, 178.2 ft.)

32" D. Fir, orig. BT, scribing vis., bears N.41°E., 101.8
ft. (Rec. 10" D. fir, 57.4 ft.)

Set - Brass cap alongside I.P. mkd. T26S, R8W, WM S26, S25,
S35, S36 1973.

New BT's - 16" D. Fir, scribed "T26S, R8W S35 BT", bears S.38°W,
30.0 ft.

18" D. Fir, scribed "T26S, R8W S36 BT", bears S.53°E.,
38.4 ft.

14" D. Fir, scribed "T26S, R8W S26 BT", bears N.32°W.,
87.9 ft.

54
Shaner Engineering
for Hub Lumber and Weyerhaeuser Co.
December 21, 1973
M 49 - 49

1/4 Cor. for Secs. 25 and 36.

Found - 38" D. Fir, org. BT, scribes vis. bears S.83°E., 508.2 ft.

40" D. Fir, orig. BT, scribes vis. bears N.58°E., 320.4 ft.
(Rec. 264.0 ft.)

Set - Brass cap mkd. T26S, R8W 1/4 S25, S36 1973.

New BT's - 20" D. Fir, scribed "S25 1/4 BT", bears N.37°W., 15.5 ft.

12" D. Fir, scribed "S36 1/4 BT" bears S.86°E., 11.0 ft.

55

1/4 Cor. for Sec. 36 and Sec. 31, T26-7.

Found - 1963 County Surveyors brass cap. Ren. No. 25

32" D. Fir snag, org. BT, face rotted out, bears N.28°E.,
17.2 ft.

28" D. Fir, scribing vis., bears N.32°E., 32.6 ft.

New BT - 6" D. Fir, scribed "1/4 S36 BT", bears S.86°W., 19.7 ft.

Found 1/2" Aluminum pipe driven in beside brass cap.

56