

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 T. S. R. 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Shaner Engineering
for Hub Lumber and Weyerhaeuser Company
December 21, 1973
M 49 - 49

Sec. 1 Cor., Sec. 36, T26-8; Sec. 31, T26-7; Sec. 1, T27-8;
Sec. 6, T27-7.

Found - 40" D.Fir stump, orig. BT, face badly burned, scribes
"BT" vis., bears S.32°W., 54.8 ft.
36" D.Fir stump, prob. orig. BT, badly burned and
rotted, bears N.35°W., 59.0 ft. (Rec. N.40°W., 61.4 ft.)
36" Cedar stump, prob. orig. BT. I re-scribed "T26S, R7W
S31 BT", bears N.20°E., 78.0 ft. (rec. 67.3 ft.)
Set - Brass cap mkd. T26S, R8W S36; T26S, R7W S31; T27S, R8W
S1; T27S, R7W, S6.
New BT's-6" D.Fir, scribed "T26S, R8W, S36 BT" bears N.64°W., 55.4"
8" hemlock, scribed "T27S, R7W. S6 BT" bears S.62°E.,
24.7 ft.
8" D.Fir, scribed "T27S, R8W, S1 BT" bears S.34°W.,
114.4 ft.

57

1/4 Cor. for Sec. 36 and Sec. 1, T27-8.

No original evidence found.

Set - Brass cap mkd. T26S, R8W, S36; T27S, R8W, S1, 1/4 1973
BT's 6" D.Fir, scribed "S1 1/4S BT", bears S.88°W., 3.1 ft.
5" D.Fir, scribed "S36 1/4 BT", bears N.56°E., 8.0 ft.

58

Sec. Cor., Sec. 36 and Sec. 35 and Secs. 2 and 1, T27-8.

Found - 3/4" I.R. (Weyerhaeuser survey, C.S. 55/285)
36" fir stump, prob. orig. BT, rotten and burnt, bears
S.30°W., 7.3 ft.
Probable Orig. fir BT, now mound of rotten wood, bears
N.20°W., 31.0 ft.

Set BT's-Brass cap alongside I.R. mkd. T26S, R8W, S35, S36
T27S, R8W, S2, S1 1973.

New BT's- 14" D.Fir, scribed "T26S, R8W, S36 BT", bears N.11°E.,
16.5 ft.
24" D.Fir, scribed "T27S, R8W, S2 BT" bears S.41°W.,
19.6 ft.
12" D.Fir, scribed "T26S, R8W, S35 BT", bears N.65°W
33.3 ft.
16" D.Fir, scribed "T27S, R8W, S1 BT", bears S.88°E.,
29.0 ft.

59

Sec. Cor. for Secs. 25, 36, and 30 and 31 of T26-7

Found - 1959 BLM Cadastral brass cap-
18" D.Fir snag BT, scribing vis. bears N.14°E., 26.4 ft.
10" D.Fir BT, face vis. bears S.16°E., 141.9 ft.
12" D.Fir, face vis., bears S.11°W., 130.0 ft.
26" D.Fir, windfall, scribing vis., bears N.83°W., 13.2 ft.
22" D. Fir, scribing partially vis., bears N.43°W.,
31.7 ft.
23" D.Fir, snag, windfall, bears N.19°E., 31.7 ft.
New BT - 12" Hamlock, scribed "T26S, R8W S25 BT", bears N.45°W.,
105.4 ft.

60

Center Cor. sec. 36.

Set - Brass cap mkd. T26S, R8W S36 C1/4 1973
BT's - 10" D.Fir, scribed "S36 C1/4 BT", bears S.7°E., 19.6 ft.
10" D.Fir, scribed "S36 C1/4 BT", bears S.63°W., 34.3 ft.

61

Center 1/4 Corner for Section 34.

Set - Brass cap mkd. T26S R8W WM C 1/4 S34 1974 from which:
10" Douglas fir, I scribed "C $\frac{1}{4}$ BT", bears N.50 E., 28.6 ft.
16" Douglas fir, I Scribed "C $\frac{1}{4}$ BT", bears S.45 E., 4.8 ft.

62

Bruce Shaner for
Hub Lumber Company
RM 2 - 63
June 24, 1974

fd. 3/90
C.S. 63/127

6/24/74