

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

76

Fd. 3/90 C.S. 62/104

Center 1/4 Corner Sec. 35

Set - 5/8" x 30" I.R. 26" in the ground
BT's - 16" Douglas Fir bears N.46 1/2°E., 27.6 marked C1/4S35BT
24" Douglas Fir bears S.26°W., 25.3 feet marked C1/4S35BT

Note - Corner lies on gentle N.E. slope, 30 feet N.E. of draw and 250 feet North of dirt road.

Burton W. Holt
For: Sun Studs Inc.
Nov. 1979
M 79 - 12

1/4 Corner for SEc. 1 only. (west)

Found - 1971 BLM brass cap ly8ng out of prlce downhill from corner location.

32" now 32" fir per 1971 resurvey, alive with good scar.
13" cedar per 1971 resurvey has apparently slid downhill and into the creek.

Set - Using record bearing and dist. from found BT (N.44°W., 79.9 ft.) I RESET found brass cap in its proper location. Because cor. falls on very steep slope and on solid rock, I drill approx. 4" deep hole in rock and cement in a 5/8" x 30" I. Rod; I then put the found I.R. and cement bottom of pipe to the rock; I then place a mound of stones around the monument. I add the marks "Reset 1983" to brass cap.

New BTs - 12" fir scribed "1/4 S1 CS BT" in double blaze bears S.40°E., 126.8 ft.

7" fir scribed "1/4 S2 CS BT" in double blaze bears S.67°W., 27.0 ft.

4/18/83

78

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
R. Smith; J. Powell
April 18, 1983
C.S. 62/7

Section corner for Secs. 11, 12, 13 and 14.

Found - 1968 Dougl. Co. brass cap on 1 1/2" I.P. Ren. #37
27" split chinquapin bears S.54°W., 39.60 ft. (Rec. S.60°W., 37.0 ft.) scribed T26S R8W S14 CS BT (original)
15" rotten hemlock snag, 30 ft. tall, bears N.48°E., 18.5 ft. (Rec. N.52°E., 17.8 ft.) No scribing visible. (Original)
48" fir stump bears S.60°E., 37.9 ft. (Rec. 37.0 ft.) No scribing visible (original)
21" hemlock bears S.59°E., 32.3 ft. (Rec. S.58°E., 32.8 ft.)
18" hemlock snag, 30 ft. tall bears N.13°E., 27.7 ft. (Rec. 27.0 ft.) Scribe marks visible on open blaze. (1968)

New BTs - 15" chinquapin bears S.2°30'E., 38.2 ft. scribed T26S R8W S14 BT.
8" hemlock bears N.3°30'E., 30.5 ft. scribed T26S R8W S12 BT.
No BT's available in NW and SW quadrant.

Scribe marks visible on open blaze.

Ronald Geisler LS 1988
For: Champion International
Sept./Dec. 1983
M 90 - 49

79

Center 1/4, Section 12.

Set - 2 1/2" alum. cap set on a 1" x 36" iron pipe. Standard markings and PLS 1988.

BTs - 10" fir bears N.85°E., 22.7 ft.
8" fir bears S.32°30'E., 38.4 ft.

Both BTs scribed: C 1/4 S12 BT.

80

1/4 Corner for Secs. 12 and 13

Found - 1968 Doug. Co. Brass cap on 1 1/2" iron pipe. Ren. #32
36" fir bears N.4°W., 6.8 ft.

Scribe marks visible on chopped face. (1968)
42" fir, down and uprooted, Scribe marks visible on chopped face. Root hole bears S.68°W., 7.3 ft. (Rec. N.68°E.) (1968).

New BT - 6" fir bears S.79°W., 39.6 ft. scribed 1/4 S13 BT.

Sec BLM Resurvey V-54 Pg 21039