

Douglas County Surveyor's Record of
Government Corners Renewed

26 T. S. 9 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

6

Section Corner for Secs. 9, 10, 16 and 15.

Found - A B.L.M. monument from which:

- 16" Douglas Fir, bears S.40°W., 57 lks.
- 10" Hemlock bears S.47°E., 31 lks.
- 10" Maple, bears N.13°E., 38. lks.
- 12" D. Fir, bears N.28°W., 45 lks.

There is also a 2" aluminum pipe set by Menasha Corp. It is improperly located according to B.L.M. sources and G.L.O. notes

7

1/4 Corner for Secs. 10 and 15.

No evidence of the orig. corner or its accessories was found. The cor. was re-established by the single proportion method.

Set - a 1" iron pipe from which:

- 12" Madrone, bears N.81°W., 32.0 ft. scribed 1/4 S 10 RP
- 24" D. Fir, bears S.82°E., 29.1 ft. scribed 1/4 Cor S 15 RP.

8

Section Corner for Secs. 10, 11, 15, and 14.

Found - B.L.M. monument from which:

- 20" Cedar bears S.30°W., 25 lks. - orig. scribe visible
- 10" Myrtle bears N.65° 1/2°E., 65 lks.
- 36" Myrtle, bears S.03°W., 27 lks.

9

1/4 Corner for Secs. 10 and 11.

No evidence of the orig. corner or its accessories was found. The corner was reestablished by the single proportion method.

Set - A 1" iron pipe from which:

- 24" D. Fir, bears S.43°W., 36.1 ft. scribed 1/4 Cor S 10 RP
- 14" Madrone, bears S.60°E., 12.0 ft. scribed 1/4 Cor S 11 RP

10

Section Corner for Secs. 2, 3, 10 and 11.

Found 1" Iron pipe set by Weyerhaeuser Company engineers. Orig. bearing trees for pipe were destroyed by road construction. Corner was re-referenced as follows:

- 8" Hemlock, bears N.37°W., 6.1 ft.
- 24" Madrone, bears N.76°E., 5.5 ft.
- 18" D. Fir, stump, bears S.13°E., 25.0 ft.
- 8" D. Fir, bears S.60°W., 23.4 ft.

RE-RENEWED, SEE CORNER NO. 28

11

1/4 Corner for Secs. 3 and 10.

Position of this corner is occupied by a small hemlock stub. Orig. bearing trees were destroyed by road construction. Re-referenced by Weyerhaeuser Co. engineers

- 22" Hemlock bears N.01°W., 17.9 ft.
- 28" D. Fir, bears S.69 1/2°E., 30.0 ft.

12

Section Corner for Secs. 4, 3, 9 and 10.

The orig. corner and its accessories were destroyed by road construction. Before its destruction, the corner was re-referenced by Weyerhaeuser Company engineers. 1" Iron pipe from which:

- 36" Red Cedar, bears N.78°E., 59.0 ft.
- 36" D. Fir, bears N.39°W., 21.8 ft.

13

1/4 Corner for Secs. 9 and 10.

Restored during Williams River No. 1 survey (Sec. 9, T26S, R9W)

Set 2" Iron pipe from which:

- 14" Maple bears S.73 1/2°W., 11.5 ft.
- 10" Maple, bears S.61 1/2°E., 8.0 ft.

14

Center 1/4, Section 10.
Drove nail in 2 foot by 3 foot rock outcropping. Referenced as follows:
36" D. Fir, bears N.67°W., 15.6 ft., scribed C 1/4 Cor S 10 RP
12" Cedar, bears N.46 1/2°E., 13.4 ft. scribed C 1/4 S 10 RP.

Weyerhaeuser Company
Dellwood Engineering Office
Williams River No. 2 Survey
Robert C. Adamek
March 27, 1975

1176