

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26 T. S. R 9 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 31881

Robert C. Adamek, Dellwood Dist. Engineer  
For: Weyerhaeuser Company  
Feb. 2, 1977  
M 63 - 19 C.S. 58/135

Robert C. Adamek  
For: Weyerhaeuser Co.  
Elk Wallow Survey  
July 13, 1977  
M 66 - 12  
C.S. 58/139

Michael S. McDowell  
Weyerhaeuser Co.  
Sept. 25, 1981  
C.S. 58/8

Gregory Quibell  
John Powell  
Doug. Co. Surveyors  
Office.  
June 2, 1982  
C.S. 61-36

East 1/4 Corner for Sec. 2  
Found no trace of orig. corner or its accessories. Restored this corner by the single proportion method.  
Set - 3/4" I.P. from which a:  
24" Alder bears S.51 3/4°W., 27.96 ft. scribed 1/4 CNR RP.  
24" Hemlock bears N.24°E., 20.25 ft. scribed 1/4 CNR RP.

15

North 1/4 Corner for Sec. 2  
Found no trace of orig. corner or its accessories.  
Set - 3/4" I.P. from which a:  
19" D. Fir bears N.49 1/2°W., 7.5 ft. scribed 1/4 CNR RP.  
14" D. Fir bears S.22°W., 12.6 ft. scribed 1/4 CNR RP.

16

NW Section corner for Sec. 2.  
Found - Orig. 16" Cedar, bears S.23°W., 35 lks. A larger Cedar now stands between this BT and the corner.  
orig. D. Fir, 48", bears N.43°W., 82 lks.  
Set - 3/4" Iron Pipe.

17

West 1/4 Corner for Sec. 2  
Found no trace of the orig. corner or its accessories.  
Set - 3/4" Iron pipe from which a:  
40" Cedar stump bears N.12 3/4°E., 44.3 ft.

18

South 1/4 Corner for Sec. 2  
Found no trace of the orig. corner or its accessories.  
Set - 3/4" Iron pipe from which a:  
42" D. Fir bears N.65°E., 21.5 ft.  
18" Cedar bears S.79°W., 7.9 ft.

19

Center 1/4 Corner for Sec. 2  
Set - 3/4" I. Pipe from which a:  
27" D. Fir bears S.06°W., 21.7 ft. scribed C 1/4 RP  
29" D. Fir bears N.52°E., 27.6 ft. scribed C 1/4 RP.

20

S 1/4 Cor. Sec. 36  
Found - 28" D. Fir, orig. BT, with visible scribing bears N.11°E., 12 links.  
Set - A 1" I.P. from which a:  
20" D. Fir bears S.39°E., 44.8 ft.  
18" D. Fir snag bears S.27°E., 21.1 ft.

21

Section corner for Secs. 2 and 3; and Secs. 34 & 35 of T.25-9  
Found - 1" iron pipe. Ren. #17  
36" fir, OBT, bears N.43°00'W., 55.6 ft.  
28" cedar, OBT, bears S.23°00'W., 24.2 ft.  
Said corner falling on the centerline of a proposed logging spur, and with the possibility of existing accessories being obliterated by the road construction, new accessories were established as follows:  
28" white fir scribed BT bears N.19°30'E, 68.2 ft.  
20" fir scribed BT bears S.42°30'E., 87.3 ft.  
18" cedar scribed BT bears S.36°00'W., 36.6 ft.

22

1/4 Corner for Sections 22 and 27.  
Found - Orig. 15" x 12" x 10" sandstone, now 15" x 10" x 7" with "1/4 S" visible on north face. Stone was firmly set protruding 5" out of ground.  
Orig. 13" now 24" cedar, previously opened showing rotted face with no scribing visible, bears S.64°E., 23.8 ft. (Rec. S.60E.)  
Orig. 26" now 32" cedar previously opened showing rotted face with no scribing visible, bears N.51°W., 58.1 ft. (rec. N.47°W.)

23