

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R 9 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

26

CONT - - - (1/4 Cor. 27 and 34)

Gregory Quibell,
Deputy, Doug. Co.
Surveyors Office
John Powell-Gary L.
Langlitz (guest witness)
May 27, 1982
S. 61/36

I place found I.P. along southerly edge of brass cap.
New accessories:
Spike in top of 48" fir stump bears N.60°W., 21.7 ft.
8" hemlock scribed "1/4 S27 CS BT" in double blaze bears N.4°W.,
49.5 ft.
Spike in top of 36" fir stump bears N.1°W., 46.6 ft.

5/27/82

CONDITION REPORT ONLY -

27

1/4 Corner for Secs. 22 and 23 (possible)

Found - Steel fence post with line crossing sign attached & tag which
indicated that this is the cor. location. This sign is
located approx. 1/2 way up a steep cut bank on the south side
of a rock road. The tag is from Weyerhaeuser Timber Co. (WTC)
From this location both orig. BTs would have been destroyed by
road construction.

Gregory Quibell, Deputy
Doug. Co. Surveyors
Office
John Powell
Guest Witness: Gary L.
Langlitz
May 27, 1982
C.S. 61/36

42" fir stump with "WTC" bearing tag which reads "T26S R9W S23
45.5 ft. N4W to W 1/4"
64" fir stump with "WTC" bearing tag which reads "T26S R9W S22
54 ft. N 70 1/2 E to E 1/4"
32" fir stump with "WTC" bearing tag which reads "T26S R9W S22
71.8 ft. S 34 E to E 1/4".

Since I could find no orig. evidence and since found BT stumps are not of
record, I DO NOT set a monument.

5/27/82

Section Corner for Secs. 2, 3, 10 and 11

28

Found - A 1" O.D. Iron pipe protruding 7" above ground. (Set by
Weyerhaeuser Co.) Ren. #10

8" now 12" dia. 3 ft. high Hemlock stump; with a fully healed
single blaze, bears N.46°W., 6.1 ft. (Rec. N.37°W., 6.1 ft.
Ren. No. 10

24" now 18" dia., 3 ft. high Madrone stump with a previously
opened rotted blaze, bears N.66°E., 5.5 ft. (Rec. N.76°E.,
5.5 ft.) Ren. No. 10

18" now 18" dia. 2 ft. high D.Fir stump, rotted shows old axe
marks and "W" nail laying along stump, bears S.13°E., 26.1 ft.
(Rec. S.13°E., 25.0 ft.)

SW BT from Ren. No. 10 is gone.

New BT - 18" dia. 2 ft. high D.Fir stump with boat spike set through
BT tag near center of stump, BS bears S.50°E., 26.7 ft.

Corner is approx. 40 ft. North of a gravel road and 10 ft. East of a cat
road in a clear cut.

7/30/92

Douglas County
Surveyors Office
July 30, 1992
Randall Smith
Stephen Flause
C.S. 64/31

S 1/4 Cor. Sec. 34

29

Found - 3/4" I.P., 1 foot out of the ground, from which:
10" decayed stump, bears S.26°E., 10.4', (14" Hemlock S.29°E., 15
lks, 9.9' GLO rec)
13" Hemlock, WEYCO tag, bears N.28°W., 19.6'.
18" Hemlock, cruisers marks, bears S.88°E., 20.4'.
43" Fir, WEYCO tag, cruiser marks, bears S.36°W., 25.1'

C 1/4 Sec. 34

30

Set - 5/8"x36" rebar w/plastic cap mkd: "HOSTETTER LS 1975" from which
17" Fir, scribed "C 1/4 S34 BT", bears S.59°E., 29.9'.
15" Fir, scribed "C 1/4 S34 BT", bears S.9 1/2°W., 39.1'.
14" Fir, scribed "C 1/4 S34 BT", bears N.38 1/2°W., 24.4'.
15" Fir, scribed "C 1/4 S34 BT", bears N.30°W., 0.6'.

Cor. Secs. 34, & 35

31

Found - 40" Fir stump, possible face, burned corner tag, GLO rec. N8°W.
31 lks. (20.5') bears N.3°W., 20.5'.

42" Fir stump, face evident, 2 nail & a melted corner tag, GLO rec
S.70 1/2°W., 34 lks. (22.4') bears S.68°W. 22.4'.

Set - 5/8"x36" rebar w/plastic cap mkd: "HOSTETTER LS 1975" from which
45" Fir stump, WEYCO tag & 6" spike, bears S.25°E.,
49.8'.

001

Tony Hostetter
For: Weyerhaeuser & Menasha
March 1996 M 126-61