

Douglas County Surveyor's Record of
Government Corners Renewed

T 26 T. S. R9 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Tony Hostetter
For: Weyerhaeuser &
Menasha Corp.
March 1996
M 126-61

Cor. Secs. 26, 27, 34, & 35

32

Set - 5/8"x36" rebar w/plastic cap mkd: "HOSTETTER LS 1975"
40" Fir snag, no marks, possible face, bears N.27°45'E.,
128.4', (GLO rec. Fir, N.29°E., 190 lks., 125.4') OBT.
39" Fir snag, visible axe marks, face evident, bears
S.39°E., 119.6', (GLO rec. S.38½°E., 182 lks., 120.0') OBT
48" Fir snag, visible axe marks, face evident, bears
S.9°W., 25.1', (GLO rec. S.8°30'W., 38 lks., 25.1') OBT
40" Fir snag, visible axe marks, face evident, bears
N.84°15'W. 44.9', (GLO rec. N.87°15'W., 68 lks. 44.9') OBT
18" Fir, bears N.27°15'E., 99.2', scribed "S 26 T26S R9W BT"
24" Fir, bears S.41°E., 79.8', scribed "S 35 T26S R9W BT"
16" Fir, bears S.39°30'W., 19.8', scribed "S 34 T26S R9W BT"
25" Fir, bears N.14°30'W., 58.2', scribed "S 27 T26S R9W BT"