

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

102

$\frac{1}{4}$ Corner to Sections 29 and 30.
Found - No trace of Corner Stone.
30", now 38" Cedar, S. 55° W. 19.1 ft., opened for scribing, " $\frac{1}{4}$ S".
20", now 34" D. Fir, N. 21° E. 57.4 ft. shows good scar.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: T 27 S R 1 W County Surveyor's #151
Office, 1969
New BT's: 12" Hemlock S. 79° E. 18.6 ft. mkd: " $\frac{1}{4}$ S29 CS BT".
8" Hemlock S. 81° W. 6.2 ft. mkd: " $\frac{1}{4}$ S30 CS BT".
- - - - - 12/16/69

103

$\frac{1}{4}$ Corner to Sections 19 and 30.
Found - No trace of Corner Stone.
14" Cedar, now Snag, S. 5° E. 12.5 ft., opened for scribing.
24", now 38" Cedar, badly burnt, N. 36° W. 15.2 ft.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: T 27 S R 1 W County Surveyor's
 $\frac{1}{4}$ S 19 County
S 30 1969
New BT's: 28" Cedar N. 17° E. 49.0 ft. mkd: " $\frac{1}{4}$ S19 CS BT".
40" D. Fir S. 32° E. 56.0 ft. mkd: " $\frac{1}{4}$ S30 CS BT".
- - - - - 12/16/69

104

$\frac{1}{4}$ Corner to Section 34 only, T27-1W.
Found - 30", now 47" D. Fir, N. 7° E. 23.8 ft., opened for scribe, "BT"
and other marks.
No trace of S. E. Bearing Tree.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office $\frac{1}{4}$ S 34 T28S
1969
New BT: 10" Hemlock N. 77° E. 20.4 ft. mkd: " $\frac{1}{4}$ S34 CS BT".
- - - - - 12/12/69

105

$\frac{1}{4}$ Corner Section 32 only, T27-1W.
Found - 18x12x6 Stone, firmly in ground, mkd: " $\frac{1}{4}$ " on north face.
18", now 34" D. Fir, S. 32° W. 9.9 ft., opened for scribe " $\frac{1}{4}$ ".
16" D. Fir, now snag, N. 45° W. 9.2 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office $\frac{1}{4}$ S 32 T28S
1969
New BT's: 30" D. Fir N. 40° W. 22.5 ft. mkd: " $\frac{1}{4}$ S32 CS BT".
28" D. Fir N. 51° E. 21.7 ft. mkd: " $\frac{1}{4}$ S32 CS BT".
I opened and destroyed scribing of S.W. Bearing Tree as this corner
does not refer to Section 5.
- - - - - 12/12/69

106

Closing Corner to Sections 1 and 2 only, T 28 S - R 1 W.
Found - 15x12x10 Stone, firmly set, mkd: 1 notch East side.
16", now 30" D. Fir, S. 61° W. 44.9 ft., shows good scar.
12" D. Fir, now stob, S. 18° E. 24.4 ft., found scribing "S1 BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S RLW S 36
Office, 1969 T28S CC S 2 | S 1
New BT: 6" Cedar S. 88° E. 15.2 ft. mkd: "T27S RLW S 1 CC CS BT".
This corner lies 25 ft. East of spring branch & 99.0 ft. East of
Sec. Cor. to 35/36. T27-1W., See corner below.
- - - - - 12/15/69

107

Section Corner to Sections 35 and 36 only, T27-1W.
Found - 12x10x6 Stone, no marks found.
10", now 10" Hemlock, N. 2° W. 5.3 ft., scribe visible.
30", now 40" Hemlock N. 46° E. 72.6 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S RLW S 35 | S 36
Office, 1969 T28S RLW S 2
All Bearing Trees O. K. and Tagged.
This corner lies about 60 ft. west and 25 ft. south of spring branch.
Also lies 99.0 ft. west of Sec. Cor. 2/1, T28-1W., see above.
- - - - - 12/15/69

John M. Powell
Frank Jones & W. Penley
December, 1969 C. S. File No. 54/94