

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

108

$\frac{1}{4}$  Corner to Section 31 only, T26-1W.  
Found - No trace of Corner Stone nor N. W. BT.  
12", now 25" Cedar, N.76°E. 48.2 ft., scribe visible.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R1W  $\frac{1}{4}$  S 31  
Office, 1969 T27S  
New BT: 10" Hemlock N.77°W. 29.2 ft. mkd: " $\frac{1}{4}$  S31 CS BT".  
Bear. & Dist. btwn.  $\frac{1}{4}$  Sec. 6 and  $\frac{1}{4}$  Sec. 31 is S.82°W. 117.6 ft.  
(Record West 125.4 ft.) 12/17/69

109

$\frac{1}{4}$  Corner to Section 6 only, T27-1W.  
Found - 20x18x5 Corner Stone, in place & mkd: " $\frac{1}{4}$ " on south side.  
40", now 50" Cedar, S.37°W. 22.4 ft., shows scribing.  
No trace of S.E. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R1W  $\frac{1}{4}$  S 6  
(In place of Cor. Stone) Office, 1969 T27S  
New BT: 6" Hemlock S.36°E. 13.1 ft. mkd: " $\frac{1}{4}$  S 6 CS BT".  
The  $\frac{1}{4}$  Sec. 6 only lies 117.6 ft. S.82°W. from  $\frac{1}{4}$  Sec. 31 only on steep, N.slope  
12/17/69

110

Closing Corner, Sections 30 and 31, T. 27 S. R. 1 W.-E.  
Found - 1927 G.L.O. Brass Cap firmly set at closing corner, properly marked.  
16" Hemlock, now 19", N.78°E. (Rec. N.80°E.) 19.1 ft. scribe marks visible.  
10" Hemlock, now 12", S.40°E (Rec. S.37°E.) 34.3 ft., scribe visible  
"T27S R1E S31 CC BT".  
New BT: 18" Hemlock S.13°E. 20.5 ft., scribed "T27S R1E S31 CC CS BT".  
Old BT S.37°E. is at edge of unit now being logged. May be destroyed by logging  
12/23/69

111

Section Corner to Sections 25 and 36 only.  
Found - 10" Hemlock, now 17", S.45°W. 17.8 ft., scribe visible "S".  
14" Hemlock, now stub, N.68°W. 13.2 ft., also stone at sec. cor., no marks.  
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 27 S R  
Office 1 S 25 S 31 1  
1969 W S 36 E  
New BT: 7" Hemlock N.67 $\frac{1}{2}$ °W. 19.6 ft., scribed "T27S R1W S25 CS BT".  
12/23/69

112

$\frac{1}{4}$  Corner to Sections 9 and 16, T. 27 S. R. 1 W.  
Found - 14" D.Fir, now 34", N.60°E. 30.4 ft., shows good scar.  
10" Maple, now 14", S.22°E. 23.9 ft. (Rec. 25.7), open for scribing  
"4" "S" "B".  
Also 20x15x5 stone firmly set at  $\frac{1}{4}$  cor., could find no mks.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W  
Office  $\frac{1}{4}$  S 9  
1969  $\frac{1}{4}$  S 16  
New BT: 10" D.Fir S.9°E. 17.8 ft., scribed " $\frac{1}{4}$  S16 CS BT".  
12/18/69

113

$\frac{1}{4}$  Corner to Sections 24 and 25, T. 27 S. R. 1 W.  
Found - 10" D.Fir, now 15", S.5°E. 18.5 ft., open for scribing BT.  
No trace of stone.  
NE BT down in windfalls.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W  
Office  $\frac{1}{4}$  S 24  
1969  $\frac{1}{4}$  S 25  
New BT: 22" D.Fir N.81°E. 26.5 ft., scribed " $\frac{1}{4}$  S24 CS BT".  
12/22/69

John M. Powell  
Frank Jones & W. Penley  
C. S. File No. 54/94

5/28/80  
Referenced  
For Road Work  
D.C.S.O. K. Reed  
See C.S. 59/30

RE-RENEWED, SEE CORNER #186