

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21801

Milo E. Godfrey, Deputy County Surveyor
Wm. Stoffel & Mike Stone
December 1963 and January 1964
C. S. File No. 49/28

Vernon "Ray" Tracy
Jack Heritage & E. West
August 7, 1967
C. S. File No. 54/40

Corner to Sections 7 and 18 only. (E. Line of T27-2W) 11
Found - 36" Sugar Pine S.22°E. 30.4 ft., opnd & fd. good scrbing. "18BT".
No trace of any other bearing trees.
Did not find Rock at Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W

S 7	RLW
SL8	

New BT's: 18" D.Fir N.11°E. 35.5 ft. Mkd: T27S RLW S7 CS BT.
16" Red Cedar S.67°E. 29.4 ft. Mkd: T27S RLW SL8 CS BT.
Note - This Corner is approx. 10 chains south of corner to Secs. 12 & 13, only, T27S R2W.

Closing Corner to Sections 12 & 13, T27-2W. 12
(W. Line of T27S RLW)
Found - Rock 15" x 8" x 6" with 2 notches on one side & 4 notches on opposite side lying loose on top of ground near corner.
11" Red Cedar S.30°W. 20.5 ft., has been previously opened, good scribing visible "T27S R2W SL3 BT".
Stump of 50" Fir N.40°W. 23.1 ft., scar visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W

SL2	RLW
SL3	

New BT's: 15" Red Cedar N.14°W. 66.3 ft. Mkd: T27S R2W SL2 CS BT.
12" D.Fir S.60°W. 9.6 ft. Mkd: T27S R2W SL3 CS BT.
Note - Corner lies approx. 200 ft. north of rocked logging road running N.W. & S. E.

Closing Corner to Sections 6 and 7, T27-1W. 13
(E. Line T.27S R2W)
Found - Brass Cap set in 1960. Orig. Rock along side. See Ren. No. 2.
18" D.Fir N.84°E. 100.2 ft. to face, bark scribing visible.
This tree is across road from corner, tree alive & in good cond.
Doug. Fir S.12°E. 29.7 ft., bark scribing visible. This tree is ~~seen~~ alive but in poor condition.
New BT: 20" D.Fir S.30°E. 40.8 ft. Mkd: T27S RLW CC S7 CS BT.
FOUND O.K. 10/68 VRT

Corner to Sections 18 and 19 only, T27S RLW. 14
(E. Line T27S R2W)
Found - 24" Hemlock Snag S.26°E. 8.6 ft., face badly burned, no scrbing. fd.
Uprooted Fir Snag N.21°E. 17.8 ft., cut open & found good scribing.
Could not tell exactly where tree had stood.
Portion of large Cedar Stump with root system still in ground, N.63°W. 23.8 ft., no markings.
Did not find Original S. W. BT.
Set - 2" Iron Rod, Corner position falls under log approx. 40" Diam.
Rescribe Hemlock Snag S.26°E. 8.6 ft. "T27S RLW SL9 CS BT".
New BT: 40" D. Fir Stump N.34°E. 60.0 ft. Mkd: T27S RLW SL8 CS BT.
No live trees available. Corner is in clean cut logged area.
Jan. 2, 1964

Township Corner, T.26 & 27S., R1s. 1 & 2W. 15
Found - No trace of Original Corner Stone or other obliterated BT.
Orig. 40", now 48" down Fir, S.74°W. 16.5 ft., open & shows "S W" scribe.
Orig. 24" Fir, down & almost completely buried, N.3°W. 15.2 ft.
Orig. 6", now 16" Fir, down, S.60°E. 20.5 ft., open & find obliterated blaze as called for.
Set - Brass Cap at Cor. Mkd: County Surveyors T26S

R2W	S 36	RLW
T27S	S 1	

Office, 1967
New BT's: 10" Cedar N. 70° W. 36.5 ft. mkd. T26S R2W S36 CS BT.
18" D.Fir S. 88° W. 41.7 ft. mkd. T27S R2W S1 CS BT.
Note - This corner lies on southerly slope.

Closing Corner of Township. 16
Found - Corner Stone mkd. "CC" & 6 notches on N. & S. edges.
Orig. 28", now 38" Cedar, alive, S.62°E. 21.1 ft., scribe vis. unhealed blaze
(Rescribe "T27S RLW S6 CC CS BT")
Orig. 12", now 22" W. Fir, alive, N.80°E. 25.7 ft., scribe visible on unhealed blaze. (Rescribe: "T26S RLW S31 CC CS BT".
Set

(continued over)