

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21991

L.E. Monrean
P.L. Earle
A.V. Cangie
6/19/75
C.S. 57/30

131

Sec. Corner for sections 29, 28, 32 and 33
Found: 12"x10"x8" Basalt stone on surface of ground. 4 notches on east edge & 1 notch on south edge.
From which: A 63" Dia. Fir stump bears N78°E., 8 1/2 ft. #154
Stump cut below normal notch height. Original notes call for 60" Fir on line between sections 28 and 33 A distance of 3.3 ft. east of corner. No bearing trees found. Orig. call on south line to spring checked, no trace of cabin, area cat logged & burned. Renewal: 3.3 ft. West of Line tree I
Set: Iron pipe 2 1/2 ft. in length 1 1/2" in dia. with 2 1/2" brass cap stamped

COUNTY SURVEYORS OFFICE
1975

T 27S R1W

S29	S28
S32	S33

Bearing Objects: (no trees available)

5/8" Iron rod with aluminum cap 1 1/2" dia. cap center punched & stamped DOUGLAS CO. SURVEYOR

B.O. No.1"

Set in orig. line tree stump

Bears N 75°E., 3.8ft.

5/8 " iron rod with aluminum cap 1 1/2" in diameter set in 48" dia. cedar stump bears S 25 1/2°E., 64.4 ft. Cap center punched & stamped

DOUGLAS CO. SURVEYOR B.O. NO.2

5/8 Iron rod with aluminium cap 1 1/2" in dia. Cap center punched & stamped

DOUGLAS CO. SURVEYOR B.O. NO. 3 Bears S 75°W., 22.2 ft.

12"x.0"x8" stone (Basalt) with 4 notches on east edge & one notch on south edge, lying on ground surface. Bears S59°W., 5.8 ft.

5/8 " Iron rod with aluminium cap 1 1/2" in dia. set in a 30" dia. fir stump. Cap center punched & stamped

DOUGLAS CO. SURVEYOR B.O. NO.4

bears N.58 1/2°, W 70.8 ft.

132

Closing Cor. Common to 19 and 30 only

Found: 16"x10"x8" stone with 4 notches on one edge and 2 notches on the opposite edge, lying on surface of ground.

Rotted stump bears N.65°E., 8.5ft. (Rec.11.9) No scribing

Fir stump bears S 42°W., 37.7 ft. (42" Fir snag stands directly on line and scribed as BT for closing corner to the south) (Rec.36.6ft)

Set: Brass cap stamped " Co. Surveyors Office

T27S R1W

1975

R2W	S19
S24	S30

Set Original stone on easterly edge of cap.

BT's A 14" dia. Hemlock bears N 21°E., 48.5 ft. Scribed "T27S R1W S19 CS BT"

A 16" Dia Hemlock bears S71°E., 28.3 ft. Scribed "T27S R1W S 30 CS BT"

133

1/4 Corner for Secs. 4 and 3.

Found - A 12" x 10" x 6" Basalt stone with "1/4" on West face.

A 18" now 21" Fir snag bears S.85°E., 15.2 ft. with "1/4 S3 BT" in cut open blaze.

A 18" now 24" Fir, bears S.81 1/2°W., 27.2 ft. (call S.81 1/2°W 15.2 ft) Tree is alive with well healed blaze.

Set - A 1" x 36" I.P. with brass cap at true corner point, stamped:

"Douglas Co. Surveyor"

T 27 S R 1 W

1976

1/4 S 4 | S 3

Placed orig. stone on West side of cap.

New BT - A 9" Fir, bears N.45°E., 27.9 ft. scribed "1/4 S3 CS BT" in double blaze.

7/29/76

134

1/4 Corner for Sec. 19. West Boundary.

Found - A 34" Fir (Rec. 36") bears N.10°W., 10.6 ft. Blaze opened, old scribing visible "1/4 S24 BT"

A 14" now 28" Fir bears S.37°E., 24.4 ft. (Rec. S.40°E.) No scribing found, blaze is chopped out.

Set - 1" x 36" I.P. Pipe with brass cap attached at 1/4 corner as determined in found trees. Cap is stamped "Douglas County Surveyor" T27S R1W

1977

1/4 S 19

I reblaze old bearing tree, 28" Fir, bears S.37°E., 24.4 ft. scribed "1/4 S19 CS BT" on single blaze.

Corner lies on N-S cutting line. Timber is on east as the BT to the NW is the only evidence remaining of the 1902 and 1911 surveys I do Not remove the scribing to Sec. 24. altho the 1911 notes indicate this is not 1/4 for 24.

L.E. Monrean
P.L. Earle
A.V. Cangie
6/19/75
C.S. 57/30

M Lenora Ladig
Jim Cook
Doug. Co. Surveyors
July 29, 1976
C.S. 59/18

Larry E. Monrean
Doug. Co. Surveyors
Office
Karen Cheney
Feb. 23, 1977
C.S. 59/29

RENEWED, SEE CORNER NO. #154

RENEWED, SEE CORNER NO. #192

3/77