

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

141

CONT. FROM LAST PAGE:

I buried the corner stone alongside. I built a mound of stones around the brass cap.
New BT's - A 18" D. Fir bears S.7°W., 11.5 ft. scribed "1/4 S31 CS BT" on a double blaze.
A 22" D. Fir bears N.71 1/2°E., 26.2 ft. scribed "1/4 S32 CS BT" on a double blaze.
Place County BT signs on both BT's.

1/12/78

142

1/4 Corner for Sec. 31 only. (South)
Found - Corner stone called for in GLO notes is gone.
A 19" Fir stump bears S.21°W., 5.28 ft. (Rec. S.15°W., 5.28 ft.)
Scribing visible on partly healed blaze, "1/4 S6 BT".
A 40" Fir stump bears N.4°E., 36.3 ft. (Rec. N.10°E., 36.3 ft.)
Has a healed scar.
Set - Using the record BT distances as reference, I chain from BT stumps and set a 2 1/2" Brass cap on a 1" I.P., stamped:
County Surveyor's Office 1978

T 27 S R 1 W
1/4 S 31
S.C.

New BT's and Accessories:
A 15" White Fir bears S.55°W., 86.7 ft. scribed "1/4 S31 CS BT" on a double blaze.
A point of rock 10 ft. x 6 ft. x 4 ft. above ground. On the E.S.E. face I mark "X BR" 1 ft. above ground. "X" mark bears N.24°E., 14.0 ft.
A 13" White Fir bears S.74 1/2°E., 121.0 ft. scribed "1/4 S31 CS BT" on a double blaze.
Placed County BT signs on 2 stumps and 2 new BT's.
Corner located in SW corner of a clearcut unit. This is a standard corner on the 6th standard parallel south.

1/12/78

Jan 78

143

Section corner for 10, 11, 15 and 14.
Found - Orig. corner stone set solidly in place. Stone is soft and no marks remain.
Orig. 30" Fir is now a windthrow. Stump hole bears S.34°W., 44.2 ft. Open & find scribing "T27S".
Orig. 24" Fir is now a windthrow. Stump hole bears N.64°W., 30.4 ft. is lying on face.
Both BTs to the east are gone.
Set - Moving the corner stone aside, I SET in it's place a 2 1/2" brass cap on a 1" Iron pipe stamped County Surveyor's Office T27S R1W S10 S11 S15 S14 1978.
I bury corner stone alongside brass cap
New BT's- A 19" Grand Fir bears S.8°30'W., 51.6 ft. scribed "T27S R1W S15 CS BT" on a double blaze. No suitable trees in Sec. 11.
A 14" Hemlock bears N.14°W., 48.6 ft. scribed "T27S R1W S10 CS BT" on a double blaze.
A 8" Grand Fir bears N.47°30'W., 24.7 ft. scribed "T27S R1W S10 CS BT" on a double blaze.
A 23" D. Fir bears S.27°30'E., 21.3 ft. scribed "T27S R1W S14 CS BT" on a double blaze.

6/14/78

144

Section corner for Secs. 15, 16, 21 and 22.
Found - Doug. Co. Surveyor's Office brass cap extending 18" above ground. Ren. #73
36" Fir, N.18 1/2°E., 31.7 ft. (N.16°E., 48 lks.) (Orig. BT.)
26" Fir, S.40°E., 5.3 ft. (S.40°E., 9 lks.) Orig. BT.
26" Fir, N.61 3/4°W., 71.5 ft. (N.61°W., 73.3 ft.)
New BT - 8" Fir S.63 1/2°W., 25.3 ft. scribed "T27S R1W S21 BT".

Dennis Gaylord, USFS
Deputy, Doug. Co.
Surveyors Office
Randal Lopez
Jan. 12, 1978
C.S. 59/46

Dennis Gaylord
U.S.F.S.
Deputy, Douglas Co.
Surveyors Off.
Witness: William
Pack
June 14, 1978
C.S. 60/11

Jim S. Peterson
For: U.S. Forest
Service
November 1978
M 70 - 41