

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 27                      T. S.                      R 1                      R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE., ZIRRI

Jim S. Peterson  
For: U.S. Forest  
Service  
November 1978  
M 70 - 41

*1-79*

*SEE ren 209*

**145**

East 1/4 Corner for Sec. 21  
Found no trace of original corner or BTs.  
Set - 3" Brass tablet in rock outcropping.  
BT's- 16" Fir, N.74 3/4°E., 65.2 ft. scribed "1/4 S22 BT".  
12" Hemlock, N.54 1/2°W., 6.1 ft. scribed "1/4 S21 BT"

**146**

Center 1/4 Corner for Sec. 21  
Found - 3" x 3" wood post N.49°E., 20.0 ft. of correct position.  
Set - 2" x 30" Iron pipe with 3" brass cap. Built mound of stone  
around corner.  
BT's- 18" Hemlock, N.18 1/2°E., 52.7 ft. scribed "C1/4 S21 BT".  
18" Fir, S.28 1/4°E., 80.0 ft. scribed "C1/4 S21 BT".

**147**

1/4 Corner for Secs. 28 & 29  
Set - 2 1/2" Iron pipe with brass cap.  
BT's- 6" D. Fir bears S.75°E., 14.8 ft. scribed "1/4 S28 BT".  
14" D. Fir bears N.31°W., 65.0 ft. scribed "1/4 S29 BT".  
Note: Set post and sign 3.0 ft. east of corner. Both trees have  
brass washers - RLS 1005 - in B.T. face.

**148**

Center 1/4 Corner Sec. 29  
Set- 2 1/2" Iron pipe with brass cap.  
BT's- 6" D. Fir bears N.49°E., 23.2 ft. scribed "C1/4 S29 BT".  
36" D. Fir stump bears S.42°E., 3.5 ft. with 5/8" Iron  
rod.  
Set fiberglass post and sign 5.0 ft. east and 5.0 ft. south of  
corner.  
B.T.'s have brass washers #1005 in faces.  
Scribed: 6" Fir bears N.22°W., 17.7 ft., scribed "C1/4 S29 BT", (4/11/80 D.H.)

**149**

Section Corner for Sections 19 - 20 - 29 - 30 See Ren. #66  
Fd.- Douglas County Surveyor's office brass cap on iron  
pipe.  
A 24" D. Fir bears S.82°W., 84.3 ft.  
A 33" Cedar bears S.21°E., 110.5 ft. with good scar.  
A 12" Hemlock bears N.43°E., 98.7 ft. (Rec. 100.1 ft.)  
New BT's - 6" D. Fir bears N.20° W., 12.7 ft. and scribed  
"T27S R1W S19 BT".  
Brass washer RLS #1005 in B.T. face. Set post and sign 4.0 ft.  
east of corner.

**150**

*See Ren. #97*

1/4 Corner for Sec. 20 and 29.  
Fd.- Douglas County Surveyor's brass cap on 1" iron pipe.  
8" D. Fir bears N.36°W., 40.1 ft. (Rec. 40.7 ft.)  
with good scar.  
32" Hemlock snag bears N.56°E., 25.1 ft. with visable  
scribe.  
24" Hemlock snag bears S.40°W., 25.1 ft. with burnt  
face.  
New BT's - 6" D. Fir bears S.20°E., 48.6 ft. scribed "1/4  
S29BT"  
Brass washer in B.T. face RLS #1005.  
Note: Found 3/4" Iron Rod 0.2 ft. south of corner.

**151**

1/4 Corner for Sec. 29 and 30.  
Fd- Douglas County Surveyor's brass cap on 1" iron  
pipe. *REN #102*  
40" Cedar bears S.55°W., 19.1 ft. with visable  
scribe.  
36" D. Fir bears N.21°E., 57.4 ft. with good scar.  
14" Hemlock bears S.79°E., 18.6 ft. with visable  
scribe.  
10" Hemlock bears S.81°W., 6.2 ft. with visable  
scribe.  
Note- Set fiberglass post with sign 54-4 4.0 ft. north of  
corner.

Ronald A. Quimby    LS # 1654  
Romano E. Ware    LS # 1005  
For: U.S. Forest Service  
March 1980  
M 79 - 32

*FDOK  
BY K. H. G. Fine  
7/95 4/22-27*