

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 1 R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 21881

Ronald Quimby LS1654
BHW, Eng.
For: U.S. Forest Serv.
April 1980
C.S. 58/229

Ronald A. Quimby
LS#1654
For: U.S. Forest Service
May 1980
M 83 - 78

Romanso E. Ware
Ronald Quimby
For: U.S. Forest
Service
July 1980
M 79 - 48

1/4 Corner for SEcs. 17 and 20
Found - 1969 County Brass cap on iron pipe. Ren. #85
A 16" Fir, S.26.5°W., 38.7 ft. good scar.
New BT - We scribed a 6" Fir, N.59°E., 12.2 ft. scribed 1/4 S17 BT with
brass washer in BT face RLS 1005.

*FD of K. Ho...
7/95
M122-27*

158

1/4 Corner for Sec. 25 only, T.27S. R.2W.
Set - 2 1/2" Iron pipe with brass cap mkd: "T.27S. R2W 1/4 S25 only
RLS #1005 1980".
BT's - 22" Hemlock bears N.8°W., 7.7 ft. scribed "1/4 S25 BT" with
brass washer RLS 1005 in BT face.
6" Yew bears N.44°W., 8.7 ft. scribed "1/4 S25 BT" with brass
washer RLS 1005 set in BT face.
10" Yew bears S.7°W., 35.7 ft. scribed "1/4 S25 BT" with brass
washer RLS 1654 set in BT face.
Note - Set post and sign 4.5 ft. north.

4/80
159

1/4 Corner to Sec. 30 only, T.27S. R.1W.
Set - 2 1/2" Iron pipe with brass cap mkd: T27S R1W 1/4 S30 only RLS
1654 1980".
BT's - 6" Cedar bears S.64°W., 15.8 ft. scribed "1/4 S30 BT".
7" Hemlock bears N.9°W., 17.8 ft. scribed "1/4 S30 BT" #196
16" Hemlock bears S.44°E., 19.9 ft. scribed "1/4 S30 BT".
Note - Brass washers marked RLS #1654 set in BT faces. Also set post
and sign 4.5 ft. north.

RE-RENEWED, SEE CORNER NO.

6/80

160

Witness Corner for Secs. 30 and 31, T.27S. R.1W. See Ren.#7
Fd. - 30" Cedar bears S.36°E., 32.0 ft. to old 10' W.C. with visable
scribes.
36" Cedar bears N.51°E., 11.9 ft. to old 10' W.C. with visable
scribes.
True corner is in White Creek = not found.
Set - 2 1/2" Iron pipe with 3" Brass cap mkd. "WC T27S R2W S25; R1W S30,
S31 W36.5 RLS1654 1980".
New BTs- 30" Cedar bears S.18°W., 30.2 ft. scribed "T27S R1W S31 WC BT".
36" Cedar bears N.66°W., 18.5 ft. scribed "%27S R1W S30 WC BT".
Note - Set fiberglass post 2.0 ft. east. Brass washer RLS 1654 in BT's
face.
True corner lies 36.5 ft. West of Witness Corner.

6/80

161

1/4 Corner for Secs. 5 & 8.
Found - 1 1/2" I.P. with brass cap marked County Surveyors Office
T27S R1W 1/4 S5 S8 1969. Ren. #39
32" Fir, S.8°W., 7.9 ft. vis. scribes
36" Fir, N.9°E., 29.0 ft. vis. scribes
Set - Post & sign 5.0 ft. North

162

1/4 Corner for Secs. 7 and 8.
Found - 2 1/2" I.P. with 1971 BLM brass cap.
Orig. stump, 19" Fir S.1°W., 7.3 ft. no vis marks.
New BT's- 6" Pine, N.7°W., 18.6 ft. "1/4 S7 BT"
6" D. Fir, S.24°E., 14.8 ft. "1/4 S8 BT".
Brass washer marked RLS 1005 set in BT faces.
Set - Post & sign 2.0 ft. East.

163

1/4 Corner for Secs. 8 and 9.
Found - 1971 BLM brass cap properly marked.
17" D. Fir N.4 1/2°E., 19.8 ft.
18" Cedar, S.4°W., 39.6 ft.
Set - Post and sign 4 ft. North

164