

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Romanse E. Ware
Ronald Quimby
For: U.S. Forest Service
July 1980
M 79 - 48

Romanse E. Ware
Ronald Quimby
For: U.S. Forest Service
July 1980
M 79 - 50

165

Witness Corner for Center 1/4 Section corner for Sec. 8.
Set - 2 1/2" Iron pipe with brass cap marked T27S R1W WC C1/4 S8
RLS 1654 1980 156.0 N.
New BT's- 56" Fir, S.40°W., 33.0 ft. "WC C1/4 S8 BT"
22" Fir N.40°E., 14.5 ft. "WC C 1/4 S8 BT"
Brass washer marked RLS 1654 set in BT faces. Trees marked with big red X.
Set - Post and sign 6.0 ft. West.
True corner falls in rock bluff. This corner is at base of rock.

166

Section corner for Secs. 7, 8, 17 and 18.
Found - 1969 County brass cap. Ren. #31
Found metal post and sign.
8" D. Fir west 11.0 ft. Good scar.
18" Hemlock N.16°W., 20.2 ft. good scar.
12" Hemlock, N.2°E., 21.9 ft. Good scar.
48" D. Fir, N.23°E., 31.0 ft. Old face with cut.
8" Cedar, S.50°E., 93.5 ft. vis. scribes.
Set - Post and sign 5.0 ft. West.

RE-RENEWED SECTION CORNER NO. #187

167

1/4 Corner for Secs. 8 and 17.
Found - 1971 BLM brass cap properly marked.
54" Fir, N.4°E., 50.3 ft. vis. scribes
Metal Post and sign 4.0 ft. West.
New BT - 8" Fir, S.25°W., 34.3 ft. "1/4 S17 BT".
Brass washer marked RLS 1005 set in BT face.

168

Sec. Corner for Secs. 8, 9, 17 and 16.
Found - 1971 BLM brass cap properly marked
50" Fir, N.8°E., 7.3 ft. vis. scribes
38" Fir, S.70°E., 17.2 ft.
12" Hemlock S.12°W., 40 ft.
32" Fir, S.76°, 74.6 ft.
26" Hemlock S.16 1/2°E., 29.0 ft. (orig. tree)
Down 40" Fir, S.19 1/2°E., 32.3 ft. (orig. tree)
42" Fir snag, N.45°W., 13.9 ft. (orig. tree)
Set - Post and sign 1.0 ft. South.

RE-RENEWED SECTION CORNER NO. #188

7/80

169

1/4 Corner for Secs. 6 and 7
Found - 1969 County Brass cap. Ren. #32
22" D. Fir, N.55°E., 11.7 ft. Good scar.
42" Cedar, S.25°E., 10.7 ft. Good scar.
Set - Post and sign 5.0 ft. North

170

1/4 Corner for Sec. 7 only. (West)
Found - 1968 County Surveyors Brass cap. Ren. #19
12" Fir, N.52°E., 16.8 ft. Scar.
16" Fir, S.24°E., 12.0 ft. Scar
24" Fir, S.18°E., 42.9 ft. vis. scribes.
Set - Post and sign 5.0 ft. North.

171

Center 1/4 Corner for Section 7.
Set - 2 1/2" I.P. with brass cap marked T27S R1W C 1/4 S7 RLS 1654 1980.
New BT's- 6" D. Fir, S.42°W., 8.2 ft. "C 1/4 S7 BT".
6" D. Fir, N.82°W., 20.0 ft. "C 1/4 S7 BT"
Brass washer marked RLS 1654 set in BT faces.
Set - Post & sign 3.0 ft. North.

172

Witness Corner for 1/4 Corner for Secs. 7 and 18.
Found - 1963 County brass cap marked: T27S LS 418 1/4 S7 S18 R1W
W.C. Cor 18 ft. North. Ren. #10
42" Fir, S.14°W., 9.6 ft. vis scribes
24" Fir N.52°E., 99.8 ft. shows scar.
Set - Post & sign 5.0 ft. South.