

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27

T. S. R 1

R. W. W. M.

FORE-CHAPMAN CO., EUGENE, ORE. 97401

Ronald Quimby
Duane Scroggins
For: U.S. Forest
Service
August 1980
M 79 - 57

181

Section corner for Secs. 14, 13, 23 and 24
Found - 1969 County brass cap on a 1 1/2" I.P. properly marked. Ren. #55
34" D. Fir, N.57°W., 26.4 ft. Good scar.
12" Hemlock, N.18°E., 21.0 ft. vis. scribe.
10" Hemlock, S.2°E., 40.0 ft. vis. scribe/
30" Fir stump, N.45°E., 17.8 ft. Good scar.
New BT - 7" D. Fir, S.16°W., 27.2 ft. "T27S RLW BT"
Brass washer marked RLS 1654 set in BT face. Set post & sign 4 ft. South.

182

1/4 Corner for Sections 13 and 24.
Found - 1969 County brass cap on a 1 1/2" I.P. properly marked. REN.#101
38" D. Fir, S.75°E., 23.1 ft. vis. scar.
New BT - 6" D. Fir, N.7°E., 21.1 ft. "1/4 S13 BT"
Brass washer marked RLS 1654 set in BT face. Set post & sign 3.0 ft. South.

183

1/4 Corner for Secs. 23 and 24.
Found - 1 1/2" I.P. with 1969 County brass cap properly marked. Ren. #114
24" Cedar stump N.14°E., 7.3 ft. vis. axe work.
19" Hemlock stump, N.36°W., 33.7 ft. vis. scribe.
3/4" iron rod, N.43°W., 24.4 ft.
3/4" iron rod, S.59°W., 21.3 ft.
New BT's- 10" Cedar, S.57°E., 52.2 ft. "1/4 S24 BT"
7" Hemlock, S.4°W., 45.4 ft. "1/4 S23 BT"
Brass washer marked RLS #1654 set in BT faces. Set post & sign 4 ft. South.

Ronald Quimby
Donald Bentz
BHW, Eng.
For: U.S. Forest
Service
August 1980
M 79 - 56

184

Center 1/4 corner for Sec. 24.
Set - 2 1/2" Iron pipe with brass cap marked "T27S RLW C 1/4 S24
RLS 839 1980"
New BT's- 7" Fir, S.23°W., 84.4 ft. "C 1/4 S24 BT".
16" Fir, S.14°W., 106.5 ft. "C 1/4 S24 BT".
Brass washer marked RLS #1654 set in BT faces. Set post & sign 4 ft. East.
8/80

**Correction
MADE 9/15/80
By BHW, Eng.*

185

W.C. to 1/4 corner for Sec's. 10 & 11.
Found - Possible orig. stone, 19" x 15" x 5". Stone is triangular
in shape, with highest point up. Stone is surrounded by a
mound of stones. No marks are visible on West face .
BT's - 30" stump (orig. 20" Fir) with visible " 4 S11 " in opened
blaze bears N.85°E., 43.6-ft.
15" stump (orig. 10" Fir) with visible " 4 S10 BT" in opened
blaze, bears S.51°W., 26.3-ft. (Rec. 25.7-ft.).
Set - Due to the ground being solid rock, I do not set another
monument, but leave 19" x 15" x 5" triangular stone in its
place, surrounded by mound of stone.
New BT's- 17" Fir bark scribed "WC 1/4 S11 CS BT" in double blaze, bears
N.11°E., 46.8-ft.
10" Fir bark scribed "WC 1/4 S10 CS BT" in double blaze, bears
N.56°W., 75.4-ft.
Note - Corner is on top of Taft Mtn., approx S.55°E., 300-350-ft.
from triangulation station "TAFT".
9/14/81

Gregory E. Quibell
Deputy Doug. County
Surveyors Office
Debbie Stewart, witness
Sept. 14, 1981
C.S. 61 / 27

186

1/4 Corner for Secs. 9 and 16
(REFERENCED NOTES ONLY)
Found - A 1 1/2" x 36" I.P. protruding 1.1 ft. above ground with brass cap
(1969 County) properly marked. Ren. #112
A 20" x 15" x 5" basalt stone 1.35 ft. south of cap, no marks
found on stone. Cap set at corner position by Powell 1969.
An orig. 14" D. fir, now a 30" diam. with healed single blaze,
bears N.60°E., 30.4 ft. Due to discrepancy in orig. bearing
of other orig. BT, we open scar to find scribe "4".
An orig. 10" maple, now 12" with previously opened blaze, visible
scribe "S1 B" bears S.22°E., 23.2 ft. (Rec. 25.7 ft. S.22°W.)
I believe orig. brg. to be in error due to scribe in other orig.
BT at rec. brg. & dist., also face is directed N.22°W.
A 10" D. fir, now 11" with partially healed double blaze visible
scribe " /4 16" bears S.9°E., 17.3 ft. (rec. 17.8 ft. Ren. #112)

Karen Reed, Deputy
Doug. Co. Surveyors
Office
Stephen Flause
Shawn Means
May 28, 1980
C.S. 59/30

MOVED TO
CS 62/50-12

RE-RENEWED **STEVEN QUIBELL** #194