

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 1 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97501

C O N T - - -

(Reference corner notes for 1/4 cor. for Secs. 9 and 16) 186
 Set - Left cap and stone in position.
 This corner lies on the northerly side of a proposed road, therefore we reference it with the following:
 Set - A PK nail 3.5 ft. above ground in a 21" diam. D. fir, bearing N.5°W., 89.2 ft. blaze and tag tree, no scribe.
 5/8" x 30" I. rod with alum. cap stamped "BO 2" bearing N.5°W., 63.2 ft., 4.50' above ground.
 A PK nail 2.2 ft. above ground in a 12" diam. Chinquapin bearing S.89°30'W., 74.9 ft. blaze and tag tree, no scribe.
 5/8" x 30" I. rod with alum. cap stamped "BO 1" bearing S.89°30'W., 94.8 ft. flush with ground.
 Angle between PK nails 84°48'30"
 See sketch attached to notes in C.S. file.
 Work done with Gurley transit, GN 0993.

Karen Reed, Deputy
 Doug. Co. Surveyors
 Office.
 Stephen Flause
 Shawn Means
 May 28, 1980
 C.S. 59/30
 MOVED TO
 CS 62/50-12

5/80

Section corner for Secs. 7, 8, 17 and 18 187
 Found - 1 1/2" I.P. firmly set projecting 15" above ground with brass cap properly mkd. Ren. #31
 Orig. 54" D. fir, N.23°E., 31.0 ft. with no marks visible on previously opened blaze.
 10" W. fir (Hemlock, Ren. #166) bears N.2°E., 21.9 ft. with healed double blaze. Ren. #31
 8" R. cedar, downed S.50°E., 93.5 ft. with partial healed double blaze face down. Ren. #31
 8" D. fir, West, 11.0 ft. with healed double blaze.
 16" W. fir, (hemlock, Ren. #166) bears N.16°W., 20.2 ft. with healed double blaze. Ren. #31
 Set - Added 3 ft. dia. mound of stone from which brass cap and I.P. now project 6".
 New BT - 10" R. cedar, S.65°E., 107.5 ft. scribed "T27S R1W S17 C.S. BT".
 Corner is about 100 ft. south of Little River on high flat ground.

Leonard Herzstein
 U.S.F.S.
 Jim Landrum
 April 14, 1982
 C.S. 61/32

4/14/82

Section corner for Secs. 8, 9, 16 and 17 188
 Found - 1971 BLM brass cap on 2 1/2" I.P. protruding 4" out of ground on very steep, logged over slope. Cap is a standard BLM cap properly marked. (See Ren. #168)
 49" fir per resurvey, now 50" stump which has been split open with scribed "BT" visible in previously opened face bears N.8°E., 7.3 ft. (as per record)
 38" fir per resurvey, now 38" stump with scribed "R1W" visible in previously opened face bears S.78°E., 17.2 ft. (as per rec.)
 12" hemlock per resurvey, now 12" stump with scribed "T27S R1W S8 BT" visible in unhealed blaze bears N.73°W., 109.8 ft. (Rec. per resurvey N.70°W., 106.9 ft.)
 New Accessories:
 Set spike in top of 26" hemlock stump, stamped "B01" bears S.14°W., 29.9 ft.
 Set spike, stamped "B02" in top of 46" fir stump bears N.81°W., 97.7 ft.
 Sketch in C.S. file.

Gregory Quibell,
 Deputy, Doug. Co.
 Surveyors Office
 John Powell
 June 7, 1982
 C.S. 61/36

6/7/82

1/4 Corner for Secs. 16, & 21. 189
 Found - 1" I.P. w/ properly mkd. B.C., protruding 12" above ground, in a 2-foot diam. mound of stone. Ren. #74.
 BTs - Orig. 40", now 48" diam. fir stump w/ portion of previously opened blaze badly burned, bears N.2-1/4°E., 7.9-ft. per M70-41, and Ren. #74.
 Orig. 30", now 42" diam. fir stump (burned) w/ healed blaze bears S.51°W., 30.1-ft. per M 70-41. Orig. Rec. & Ren. #74 call S.50°W., 31.0-ft.
 U.S. Forest Service witness sign & post bear N.85°E., 5.8-ft.
 New BTs- 10" diam. fir dbl. blazed & scribed "1/4 S16 CSBT" bears N.24-1/2°W., 75.4-ft.
 8" fir, dbl. blazed & scribed "1/4 S16 CSBT" bears N.47-1/2°E., 49.3-ft.
 Note - No other trees suitable for scribing. Set bearing objects as follows:

Larry (Ed) Monrean
 Deputy, Doug. Co. Surveyor
 Doug. Co. Surveyors Office
 Randy Smith
 Steve Flause
 February, 14, 1984
 C.S. 62/16