

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 1 R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 91861

189

(CONTINUED)

Larry (Ed) Monrean
Deputy, Doug. Co.
Surveyors Office
Randy Smith
Steve Flause
February 14, 1984
C.S. 62/16

BOs - Set 1/2" x 8" Bridge Spike in pitch ring of a 50" diam. pine stump.
48" high, stamped "BO 1", set down through a DCSO BT tag, bears:
S.59°E., 64.5-ft.
Set 1/2" x 8" Bridge Spike in pitch ring of a 50" diam. fir stump.
Spike stamped "BO 2" set down through DCSO BT tag & bears
S.71-1/2°W., 37.1-ft.
Note - Corner lies on a steep SSW slope near East edge of a clear cut,
burned & recently replanted. 2/84

190

Romanso E. Ware
L.S. 1005
For: U.S. Forest
Service
May 1977
M 65 - 20

West 1/4 Corner, Section 18 only.
Found - Alum. cap on 3/4" iron rod marked U.S.P.C. Prop. Cor. 1/4 S 18
only R. E. 4287. Ren. #22
60" fir stump, N.69°E., 29.5 ft.
60" fir stump, S.22°E., 37.0 ft.
10" hemlock, S.18°E., 11.2 ft. (orig.)
New BTs - 8" D. fir bears East 131.5 ft.
8" D. fir bears S.02°E., 98.0 ft.
Both BTs scribed W 1/4 S 18 BT.

5/77

Lloyd R. Moffit
L.S. 944
For: U.S. Forest
Service
June, 1986
C.S. 62/30

Closing Corner for Sections 6 and 7 only.
Found - A 2 1/2" brass cap on a 1" iron pipe. Ren. No. 13
A 19" fir bears S.30°E., 40;8 ft., scar visible.
A 23" fir bears S.12°E., 29.7 ft., bark scribe visible.
New BT - I marked a 12" fir BT which bears N.64 1/2°E., 111.0 ft. from
the corner, scribed T27S R1W S6 CC BT. Nailed L.S. 944
brass washer to BT scribe.

191

1/4 Corner for Section 19 only. Ren. No. 134
Found - 2" Douglas County brass cap on a 1" iron pipe in a rock mound
40" fir stump bears S.38°E., 24.4 ft., scribe visible.
38" fir stump bears N.10°W., 10.6 ft., scribe visible.
New BTs- A 4" fir which bears S.64°E., 7.7 ft., scribed "X" BT.
A 6" fir which bears S.23°E., 36.7 ft., scribed 1/4 S19 BT.
I nailed a L.S. 944 brass washer to both BT scribes.

192

1/4 Corner for Secs. 20 and 21 **193**
Found - A 1" iron pipe with 2 1/4" brass cap extending 6" above ground
set by Douglas County Surveyor stamped "T27S R1W 1/4 S20 | S21 1969"
A 30" Hemlock stump, bears N35°E, 30.5 ft. (vis. scar)
42" fir stump, bears N54 1/2°W, 39.7 ft. (vis. scribe) SEE REN#87
14" Hemlock, bears S28 3/4°E, 69.1 ft. (vis. scribe) See M70-41
New BT - A 8" D. fir, bears S01°W, 32.4 ft., scribed "1/4 S20BT" with a 1/2"
brass washer marked "RLS 1035" nailed flush to lower end of
blaze

194

1/4 Corner for Section 9 and 16
Found - 1969 Co. Surveyor 2" dia. brass cap, properly mkd., on a 1 3/8"
O.D. iron pipe protruding approx. 13" above ground. Ren. #112
A possible original corner stone measuring approx. 20x15x5 inches
with no marks visible, is found loosely set on surface of ground
approx. 1 foot south of brass cap monumnet.
(Accessories measured from found brass cap)
Orig. BT, a fir, 14" dia. now a 32" DBH D. fir with a partially
opened blaze revealing the scribing "4" bears N.60°E., 30.4 ft.
(Orig. maple bearing tree removed by road work)
A 10" D. fir now a 13" DBH D. fir with a fully healed double blaze
bears S.11 1/2°E., 17.3 ft. (Ren. #112, S.09°E., 17.8 ft.)
(Bearing objects from Ren. #186 found as follows:)
A PK nail 3.5 ft. above ground in a 21" dia. D. fir now a 26" DBH
D. fir blazed but not scribed bears N.06 3/4°W., 89.2 ft.
(Rec. N.05°W., 89.2 ft.)
A 5/8" x 30" I. rod with alum. cap stamped "BO 2" protruding 2"
sbove ground bears N.06 3/4°W., 63.2 ft. (rec. N.05°W., 63.2')
A PK nail 2.2 ft. above ground in a 12" diam. chinquapin now a 15"
DBH chinquapin blazed but not scribed bears S.89 1/2°W., 74.9 ft.
A 5/8" x 30" I. Rod with alum. cap stamped "BO 1" approx. 3" under
duff surface, bears S.89 1/2°W., 94.8 ft.

Brass cap monument agrees well with accessories. Stone monument is left in
found position as an accessory to B.C.

Douglas County Surveyor Office

Stephen J. Flause-R.W. Smith

March 22, 1988

C.S. 62/50

(Monument leis approx 30 ft. north of
spur logging rd. on moderately steep
NW slope.)

FD OK
BY K. Hoffme
7/95
M122-27