

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 1 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

203

Ken Hoffine,
LS #2291
For: Lone Rock
Timber
July 1995
M 122-27

Center 1/4 corner Sec. 20
Set - 5/8"x40" iron rod with 2" alum. cap mkd: LONE ROCK TIMBER
T27S R1W C $\frac{1}{4}$ S20 1995 PLSS 2291
8" D.Fir, bears S.36°W., 22.7'. We scribe T27S R1W C $\frac{1}{4}$ S20 BT
& tag tree.
8" D.Fir, bears N.76°W., 23.3'. We scribe T27S R1W C $\frac{1}{4}$ S20 BT
& tag tree.
11" Hemlock bears S.61 3/4°E., 25.6'. We scribe T27S R1W C $\frac{1}{4}$
S20 BT & tag tree.
9" Hemlock bears N.32°E., 18.9'. We scribe T27S R1W C $\frac{1}{4}$ S20
BT & tag tree.
Corner lies on gentle north slope.

204

Douglas County
Surveyors Office
Randall Smith &
Stephen Flause
Dec. 3, 1997
C.S. 64/78-33 &
C.S. 64/78-34

Sec. Cor. 21, 22, 27, & 28
Mon. Fd.- 2 1/2" brass cap on a 1 1/2" O.D. iron pipe protrudes 10" above a mound of
stone. Orig. stone not seen.
Bt's Fd.- 14" now 35" dia. D.Fir, with a fully healed single blaze, bears N.67°E.,
42' (ren. rec. N.67°E., 43.6') OBT.
Orig. SE BT nearly gone burnt remains, bears S.48°E., 64' (agrees with
ren. rec.) OBT.
20" now 26" dia. D.Fir, with a fully healed double blaze, bears
S.53 1/2°E., 70.6' (rec. S.52°E., 69.6' 1970 DCSO).
New Accessories -
9" dia. Madrone double blazed and scribed "T27S R1W S22 CS BT",
bears N.44°E., 60.3'.
6" dia. live oak double blazed and scribed "X BT", bears S.8°E., 23.2'.
see previous ren. # 118

205

1/4 cor. secs. 27 & 34
Mon. Fd.- 2 1/2" brass cap on a 1 1/2" O.D. iron pipe protrudes 18" above a mound of
stone. #116.
Bt's Fd.- 12" now 23" dia. dead, burnt Cedar, with a fully healed single blaze,
bears S.43°W., 15.2'. (agrees with rec.) OBT.
8" now 25" dia. dead, burnt Hemlock, with a partially healed burnt
blaze, illegible scribing visible, bears N.71°W., 25.7'. (agrees
with rec.) OBT.
10" now 11" dia. dead, burnt D.Fir, with a fully healed single blaze,
bears S.6°W., 17' (agrees with rec.) #116.
Mon. Set- More stone is added to base of monument, BC/IP now protrudes 6"
above 2 1/2" dia. mound of stone.
New Accessories -
24" dia. D.Fir, double blazed and scribed "1/4 S27 CS BT"; bears
N.79°W., 88.3'.
31" dia. D.Fir, single blazed and scribed "1/4 S34 CS BT", bears
S.24°W., 43.9'.
40" dia. 2' high D.Fir stump, with a PK nail set through BT tag no top
center, bears N.51°E., 4.5'.
Corner lies Approx. 250' south of a creek and 100' north of a NW running ridge on a
steep north slope.
see previous ren. #116