

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 27 S.      T. S.      R. 1 W.      R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

Do. Co. Surveyors  
Randall Smith &  
Stephen Flauser  
C.S. 64/78-35

1/4 cor. sec. 27 & 28

**206**

Mon. Fd.- 2 1/2" dia. brass cap on a 1 1/2" o.d. iron pipe protrudes 14" above ground of stone.  
(1969).  
Bt's Fd.- 18" now 35" dia. D.Fir, with a fully healed double blaze (note: burnt bark tree is a live), bears S.60°E., 31.7' (agrees with rec.) OBT.  
14" now 19" dia. Cedar, with a fully healed single blaze (note: burnt bark, tree is a live), bears S.85°W., 7.9' (agrees with rec.) OBT.  
New Accessories -  
43" dia. D.Fir, barked scribed "1/4 S28 CS BT", bears N.37°W., 8.1'.  
17" dia. L.Cedar, double blazed and scribed "1/4 S27 CS BT", bears S.5°E., 30.7'.  
Corner lies on a steep southerly slope.

see previous ren.#95

1/4 Corner Secs. 1 & 2

**207**

Found - 2 1/2" iron pipe by Quimby & Ware in 1980 (Ren. #176), firmly set, projecting 3" above the ground with brass cap properly stamped.  
A 37" W.Fir with a snag top, bears S.80°45'E., 104.0 ft. with scribe mks: "1/4 S1 BT" visible on a open blaze (Rec. S.78°E., 103.6 ft.) 1980  
A 28" W.Fir, bears S.81°45'W., 156.6 ft. with scribe marks visible on a open blaze. (Rec. S.83°W., 156.5 ft.) 1980  
New BT - A 22" W.Fir bears N.58°15'E., 70.7 ft. scribed "1/4 S1 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed to the lower blaze.  
Note - I paint BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.  
Magnetic Declination: 20°E.

Center 1/4 Corner Sec. 2

**208**

Found - 2 1/2" iron pipe by Quimby & Ware in 1980 per M79-55 (Ren. #175), firmly set, projecting 5" above the ground with brass cap properly stamped.  
A 25" W.Fir, bears S.33°E., 23.2 ft. with scribe marks visible on a nearly healed double blaze. (Rec. Hemlock S.30°E., 33.4 ft.) 1980  
A 36° Hemlock, bears N.13°45'W., 68.8 ft. with scribe marks "C 1/4 S2 BT" visible on a partially healed double blaze. (Rec. N.14°W., 69.0 ft.) 1980  
A 3/4" iron rod, bears S.4°40'W., 20.0 ft.  
Note - I paint BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.  
Magnetic Declination: 20°E.

1/4 cor. Secs. 21 & 22

**209**

Les Fanning  
7/7/2008  
C.S. 65/64-23

Found - A 3" dia. brass tablet set in rock outcropping stamped:  
T27S R1W  
1/4  
S21 S22  
1978 PLS 1084  
from which bearing trees by Peterson in 1978:  
A 25" D. Fir bears N.74 3/4°E., 65.2 ft. with healed double blaze. (Rec. N.74 3/4°E., 65.2 ft.)  
A 22" uprooted Hemlock blown down to the SE over the rock outcropping creating huge root wad with boulders and soil hanging over corner monument, which is still accessible. (Rec.  
New BT - A 17" Hemlock bears S.57°W., 20.8 feet, scribed "1/4 S21 BT" on double face.  
All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum cont.

141

N.54 1/2°W., 6.1 ft.)