

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
October, 1969 C.S. File No. 54/94

1/4 Corner to Sections 12 and 13. 34
Found - 12x12x6" Stone mkd. "1/4" on north face.
30", now 36" D. Fir, S. 20° E. 11.2 ft., shows good scar.
20" Hemlock, now down, N. 65° W. 42.9 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office 1/4 S 12
1969 S 13
New BT: 7" Hemlock N. 15° E. 4.2 ft. scribed "1/4 S12 CS BT.
10/23/69

1/4 Corner to Sections 1 and 12. 35
Found - No trace of Corner Stone.
30" Fir, now stump, south 4.6 ft., rotten face, scribe visible.
30" Fir, now stump, N. 68° W. 37.6 ft. shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 1
1969 S 12
New BT's: 7" D. Fir S. 41° E. 19.7 ft. mkd: "1/4 S12 CS BT.
16" W. Fir N. 45° E. 25.0 ft. mkd: "1/4 S31 CS BT.
10/24/69

Section Corner to Sections 1 - 2 - 11 - 12. 36
Found - 15x8x6 Stone, firmly set, at corner.
12", now 26" D. Fir, N. 24° W. 27.7 ft., tree opened but not to face.
12", now 30" W. Fir, N. 18° E. 9.2 ft., scribe visible through hole.
14", now 35" W. Fir, S. 46° E. 25.7 ft., shows good scar.
14" W. Fir, now stob, S. 14° W. 24.4 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 2 | S 1
1969 S 11 | S 12
New BT: 20" D. Fir S. 40° W. 29.7 ft. mkd: "T27S R1W S11 CS BT.
All other Bearing Trees O.K. and Tagged.
10/24/69

1/4 Corner to Sections 17 and 18. 37
Found - Corner Stone, firmly set at 1/4 corner mkd: "1/4".
24", now 39" D. Fir, S. 71° W. 45.5 ft., shows good scar.
24", now 30" D. Fir, S. 85° E. 17.8 ft., shows good scar. This tree,
broken top most of branches gone due to falling trees.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office, 1969 1/4 S 18 | S 17
New BT: 48" D. Fir N. 61° E. scribed "1/4 S17 CS BT".
10/20/69

Section Corner to Sections 4 - 5 - 8 - 9. 38
Found - 15x12x5" Stone, firmly set, mkd. with notches.
16", now 32" D. Fir, N. 46° E. 37.0 feet, shows good scar.
30" D. Fir, now stob, S. 27° E. 36.3 ft., scribe visible.
16", now 36" Cedar, S. 82° W. 48.2 ft., shows good scar.
14", now 21" Cedar, N. 85 1/2° W. 40.9 ft., burnt face, scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 5 | S 4
1969 S 8 | S 9
New BT's: 30" D. Fir S. 5° E. 28.1 ft. mkd: "T27S R1W S9 CS BT.
Reblzd. & Rescbd: 21" Cedar N. 85 1/2° W. 40.9 ft., mkd: "T27S R1W S5 CS BT.
10/28/69

1/4 Corner to Sections 5 and 8. 39
Found - Stone, out of ground, downhill 3 ft. from corner, mkd. "1/4".
14", now 30" D. Fir, S. 13° E. 7.9 ft., shows good scar. #162
20", now 38" D. Fir, N. 9° E. (Rec. N30W) 29.0 ft. opened for scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 5
1969 S 8
Reblzd. & Rescbd: 38" D. Fir N. 9° E. 29.0 ft. scribed "1/4 S5 CS BT.
30" D. Fir S. 13° E. 7.9 ft. scribed "1/4 S8 CS BT.
10/28/69

RE-RENEWED, SEE CORNER NO.