

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
Nov. 1969 C. S. File No. 54/94

Section Corner to Sections 33 & 34 only, T26-1W. 46
Found - Corner Stone, firmly in ground, mkd. with notches.
36", now 39" D. Fir, N. 64° E. 23.1 ft., shows good scar.
16", now 22" Fir, N. 51° W. 20.5 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S S 33 | S 34
Office, 1969 T 27 S RLW S 3

Bearing Trees O. K. & Tagged.
This corner lies 89.8 ft. East of Sec. Cor. 3 & 4, T27-1W. 11/13/69

Section Corner to Sections 3 and 4 only. 47
Found - Corner Stone, firmly set, mkd. with 3 notches E - W.
18", now 18" D. Fir, S. 6° W. 11.9 ft., shows good scar.
18", now 22" D. Fir, S. 61° E. 21.8 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S S 33
Office, 1969 T 27 S RLW S 4 | S 3

Bearing Trees O. K. & Tagged.
This corner lies 89.8 ft. W. of Sec. Cor. 33 & 34, T26-1W. 11/13/69

1/4 Corner To Section 3 only, T27-1W. 48
Found - Corner Stone, firmly in ground, mkd: "1/4" on south side.
10", now 12" Hemlock, S. 67° E. 9.2 ft., scribe visible.
10"(?), now 38" D. Fir, S. 57° W. 25.7 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S 1/4
Office, 1969 T 27 S RLW S 3

Bearing Trees O. K. and Tagged.
This corner lies 92.4 ft. W. of 1/4 Corner Sec. 34, T26-1W. 11/13/69

1/4 Corner to Section 34 only, T26-1W. 49
Found - No trace of Corner Stone.
36" D. Fir, now stump, N. 32° E. 23.1 ft., shows good scar.
12" Hemlock, now stob, N. 78° W. 15.8 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S S 34
Office, 1969 T 27 S RLW 1/4

New BT's: 7" Hemlock N. 47° E. 32.9 ft. mkd: "1/4 S34 CS BT".
8" Hemlock N. 13° E. 30.0 ft. mkd: "1/4 S34 CS BT".
This corner lies 92.4 ft. E. of 1/4 Cor. Sec. 3, T27-1W. 11/13/69

Section Corner to Sections 32 and 33 only, T26-1W. 50
Found - No trace of Corner Stone.
8", now 13" Fir, N. 72° E. (Rec. N82E) 9.2 ft. Find this tree to
be a Cedar, scribe visible.
10", now 15" Fir, N. 65° W. 17.2 ft., opened for scribe "S3".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S S 32 | S 33
Office, 1969 T 27 S RLW S 4

Bearing Trees O. K. AND Tagged. 11/5/69

Section Corner to Sections 4 and 5 only, T27-1W. 51
Found - No trace of Corner Stone nor S. W. Bearing Tree.
12" Hemlock, now snag, S. 44° E. 51.5 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S S 32
Office, 1969 T 27 S RLW S 5 | S 4

New BT's: 15" Hemlock S. 24° W. 40.1 ft. mkd: "T27S RLW S 5 CS BT".
13" Cedar S. 28° E. 53.2 ft. mkd: "T27S RLW S 4 CS BT". 11/5/69

Section Corner to Sections 34 and 35 only. T26-1W 52
Found - 48" D. Fir Corner Tree, good scars.
5", now 6" Hemlock N. 31° E. 2.6 ft., scribe visible.
40", now 46" B. Fir, N. 26° W. 9.9 ft., shows good scar.
Set - Brass Cap on N. Side of Cor. Tree Mkd: County Surveyor's T26S S 34 | S 35
Office, 1969 T27S S 2

New BT: 7" Hemlock N. 75° E. 25.6 ft. mkd: "T26S RLW S35 CS BT".
This corner lies 85.0 ft. W. of Cor. to Sections 3 & 2, T27-1W. 11/6/69