

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

ROBE-CHAPMAN CO., EUGENE, ORE. 21881

53

Section Corner to Sections 3 and 2 only.

Found - Mound of Stone - Stone mkd. with notches, not found.
28" Hemlock, now snag, S.67°E. 21.1 ft., scribe visible.
28", now 38" Hemlock, S.70°W. 24.4 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S S 34
Office, 1969 T 27 S RLW S 3 | S 2

New BT: 40" Hemlock S.62°E. 41.0 ft. mkd: "T27S RLW S2 CS BT".

This corner lies 85.0 ft. East of Sec. Cor. 34 & 35, T26-1w.

11/6/69

54

Section Corner to Sections 2 - 3 - 10 - 11.

Found - 12", now 25" Fir, N.38°E. 21.8 ft., face rotted.
12", now 27" Fir, S.61°E. 21.1 ft., scribe visible.
16" Fir, now stob, S.69°W. 18.5 ft., stob rotted.
16", now 30" Fir, N.54°W. 35 ft. (Rec.35.6), face rotted out.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 3 | S 2
1969 S 10 | S 11

Reblzd. & Resbd: 25" W. Fir N.38°E. 21.8 ft. scribed T27S RLW S2 CS BT.

27" W. Fir S.61°E. 21.1 ft. scribed T27S RLW S11 CS BT.

30" W. Fir N.54°W. 35.0 ft. scribed T27S RLW S 3 CS BT.

New BT: 18" D. Fir S.37½°W. 6.8 ft. mkd: "T27S RLW S10 CS BT".

11/7/69

55

Section Corner to Sections 13 - 14 - 23 - 24.

Found - 15x12x8" Stone, firmly set mkd: 3 notches S. & 1 East.
30" D. Fir, now stump, N.45°E. 17.8 ft., shows good scar.
18" D. Fir, now snag, S.28°E. 14.5 ft., shows good scar.
18" D. Fir, now snag, S.40°W. 23.1 ft., shows pitched over scribe.
18", now 30" D. Fir, N.57°W. 26.4 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W #181
Office S 14 | S 13
1969 S 23 | S 24

New BT's: 9" Hemlock N.18°E. 21.0 ft. mkd: T27S RLW S13 CS BT.

8" Hemlock S. 2°E. 40.3 ft. mkd: T27S RLW S24 CS BT.

No other trees available.

11/7/69

56

¼ Corner to Sections 34 and 35.

Found - 15x6x6" Stone mkd: "¼".
12", now 36" Fir, S.72°E. 28.4 ft., shows faint scar. (Distances
40", now 50" Fir, S.30°W. 36.3 ft., shows good scar. (for old faces)

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office ¼
1969 S 34 | S 35

Reblzd. & Resbd: 36" D. Fir S.72°E. 28.4 ft. mkd: "¼ S35 CSBT".

11/10/69

57

Section Corner to Sections 26 - 27 - 34 - 35.

Found - 18x12x8" Stone, firmly set, at section corner.
14" Cedar, now stump, N.80°W. 9.5 ft. (Rec.11.9) shows good scar.
8" Cedar, now stump, N.52½°E. 13.2 ft., scribe visible "26" and
and parts of other marks.
16" D. Fir, now stump, S.33½°W. 27.7 ft., shows good scar.

All trees high stumped.

12" Cedar, now stump, S.28°E. 12.9 ft. (Rec.S32E 9.2), parts of
scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 27 | S 26
1969 S 34 | S 35

New BT's: 5" Hemlock S.78°E. 51.5 ft. mkd: "S35 CS BT".

7" Hemlock S.88°W. 55.5 ft. mkd: T27S RLW S34 CS BT.

No other trees available.

This corner on lower side of logging road about 150 ft. west and
125 ft. east and 90 ft. north of said road.

Road

11/10/69

John M. Powell
Frank Jones & W. Penley
November, 1969 C.S. File No. 54/94

RE-RENEWED, SEE CORNER NO. #181