

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell  
Frank Jones & W. Penley  
November, 1969 C. S. File No. 54/94

Section Corner to Sections 25 - 26 - 35 - 36.

58

Found - No trace of Corner Stone.

20", now 27" Hemlock S. 39 $\frac{1}{2}$ ° E. 32.6 ft. (Rec. 27.1) scribe visible.

18" Cedar, now snag, N. 10° E. 25.1 ft., shows scar.

10", now 12" Cedar, S. 78° W. 18.5 ft., rotten face.

16" Fir, Now stump, N. 17° W. 36.3 ft., stump rotted, old face,  
no scribing found.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W  
Office S 26 | S 25  
1969 S 35 | S 36

New BT: " D. Fir N. 57° W. 31.3 ft. mkd: "T27S R1W S26 CS BT.

Reblzd. & Resbd: 12" Cedar S. 78° W. 18.5 ft. mkd: T27S R1W S35 CS BT.

No trees available to the N. E.

11/10/69

$\frac{1}{4}$  Corner to Sections 3 and 10.

59

Found - 12x4x6" Stone, firmly set, mkd: " $\frac{1}{4}$ " on north face.

24", now 29" Fir, S. 30° E. 23.1 ft., shows good scar.

No trace of 10" Fir N. 70° W. 23.1 ft. Find a Hemlock at that  
bearing & distance, but no face.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W  
Office  $\frac{1}{4}$  S 3  
1969 S 10

New BT: 12" Hemlock N. 67° W. 23.9 ft. mkd: " $\frac{1}{4}$  S 3 CS BT".

11/6/69

Section Corner to Sections 20 - 21 - 28 - 29.

60

Found - 15x12x4 Stone, very loose in ground, notches on correct sides.

14" D. Fir, now stob, N. 34° W. 66.0 ft., prev. opened, "T27 R" visible.

36" D. Fir, now down, S. 60° E. 52.8 ft., scribe visible.

24" Fir, now burnt stump, N. 29° E. 70.6 ft.

No trace of S. W. Bearing Tree.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W  
Office S 20 | S 21  
1969 S 29 | S 28

New BT's: 4" D. Fir N. 9° E. 23.0 ft. mkd: "S21 CS BT.

6" D. Fir N. 59 $\frac{1}{2}$ ° E. 9.4 ft. mkd: T27S R1W S21 CS BT.

8" Maple S. 3° E. 15.7 ft. mkd: T27S R1W S28 CS BT.

7" Maple S. 61° W. 20.1 ft. mkd: T27S R1W S29 CS BT.

11/18/69

Section Corner to Sections 31 and 32, T27-1W.

61

Found - 12x8x6 Stone, firmly set, mkd: with grooves E. - W.

12", now 26" Fir, N. 84° W. 37.0 ft., shows good scar.

20", now 30" Fir, N. 40° E. 21.1 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 31 | S 32  
Office, 1969 T28S R1W S 5

Bearing Trees O.K. and Tagged.

Record Distance between corners 13.2, found to be 15.5 ft.

11/17/69

Section Corner to Sections 5 and 6, T28-1W.

62

Found - No trace of Corner Stone.

12", now 26" D. Fir, S. 22° W. 24.4 ft. (Rec. S22E 29.7), opened for scribe.

14", now 29" D. Fir S. 75° E. 29.7 ft. (Rec. S75W 24.4), shows good scar.

Set - Brass Cap at Cl. Cor. Mkd: County Surveyor's T27S R1W CC S 31  
Office, 1969 T28S R1W S 6 | S 5

Bearing Trees O. K. & Tagged.

Record Distance between corner 13.2, I find to be 15.5 ft.

11/16/69

West  $\frac{1}{4}$  Corner Section 7 only, T27-1E.

63

Found - 1927 GLO Brass Cap, properly marked.

26", now 38" D. Fir, S. 62° E. 27.7 ft., shows good scar.

26" D. Fir, now down, N. 45° E. 25.7 ft., tree buried.

New BT: 24" D. Fir S. 22° E. 31.7 ft. mkd: " $\frac{1}{4}$  S 7 CS BT".

Note -  $\frac{1}{4}$  Corner Sec. 12 only, T27-1W, Found Orig. Stone & Bearing Trees,  
O. K. & Tagged, but no trace of 1927 Brass Cap.

11/12/69