

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

64

Section Corner to Sections 17 - 18 - 19 - 20.
Found - Unrecorded 5/8" Iron Rod and BT's., from Ren. #3.
28" Cedar, now 15' Stob, S.89°E. 154.8 ft., scribe visible.
46", now 48" Cedar, N.45°E. 210.1 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 18 | S 17
1969 S 19 | S 20
New BT's: 5" D.Fir S. 81°E. 30.4 ft. mkd: "S20 CS BT".
5" D.Fir N. 32°W. 27.3 ft. mkd: "S18 CS BT".
This corner lies in very brushy, cut unit. No other trees within reason.
11/19/69

FD OK
K. HOFFME
7/95
1122-27

65

1/4 Corner to Sections 19 and 20.
Found - 14x8x8" Stone mkd: "1/4" on north face., See Ren. #6.
36" D.Fir, now stump, N.32°W. 15.2 ft., opened for scribng,
very rotten, but definite scribe marks.
36" D.Fir, now stump, S.48°E. 17.8 ft., shows good scar.
7", now 8" Hemlock, S.39°W. (RecS41W) 55.7 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office, 1969 1/4 S 19 | S 20
New BT: 8" Hemlock S.34°E. 51.5 ft. mks: "1/4 S20 CS BT".
11/19/69

FD OK
J. ARIMAN
C.S. 63/104
5/96

66

Section Corner to Sections 19 - 20 - 29 - 30.
Found - 15x8x8 Stone mkd: 2 notches South, See Ren. #4.
16", now 25" D.Fir, S.82°W. 84.3 ft., shows pitched over
33", now 33" Cedar, S.21°E. 110.3 ft., scribe visible.
Unrecorded 10" Hemlock N.42°E. 98.7 ft. "T27" & other marks
overgrown.
No sign of S.89°E. BT.
Orig.? 40" D.Fir, now burnt stump, S.34°W. 16.5 ft., badly burnt,
no face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 19 | S 20
1969 S 30 | S 29
Reblzd. & Resbd: 10" Hemlock N.42°E. 98.7 ft. scribed "CS BT".
This corner falls in old cut unit. No other trees available.
11/19/69

RE-RENEWED, SEE CHAPTER NO. #149

John M. Powell
Frank Jones & W. Penley
November, 1969 C.S. File No. 54/94

67

Section Corner to Sections 9 - 10 - 15 - 16.
Found - No trace of Corner Stone as this corner lies in logged-off unit.
12", now 14" Fir Stump N.75°E. 23.8 ft., shows good face.
30" Fir, now 32" Stump, S.80°E. 35.6 ft., shows good face.
18" Fir, now 22" Stump, S.45°W. 38.5 ft., opened, found scribe.
12" Fir, now 14" Stump, N.50°E. 40.3 ft., shows good face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office S 9 | S 10
1969 S 16 | S 15
New BT's: 4" Pine N.57 1/2°W. 78.4 ft. scribed "S 9 CS BT".
4" Pine S.82°W. 95.0 ft. scribed "S16 CS BT".
50" D.Fir N.86 1/2°E. 196.8 ft. mkd: "T27S R1W S10 CS BT".
40" D.Fir S.84°E. 213.9 ft. mkd: T27S R1W S15CS BT.
No larger trees available for Secs. 9 & 16. This section corner lies
in cutting unit on steep, south slope.
11/20/69

68

1/4 Corner to Sections 14 and 15.
Found - No trace of Corner Stone.
12" D.Fir, now snag, S.79°E. 43.6 ft., opned for scribe.
14" D.Fir, now down, S.75°W. 9.9 ft., opened for definite
scribe marks.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office, 1969 1/4 S 15 | S 14
New BT's: 14" D.Fir N.20°E. 32.8 ft. mkd: "1/4 S14 CS BT".
11" M aple S.51°W. 44.8 ft. mkd: "1/4 S15 CS BT".
11/21/69