

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

69

Section Corner to Sections 14 - 15 - 22 - 23.

Found - No trace of Corner Stone.

40", now 44" D.Fir, N.72°E. 29.0 ft., shows good scar.

40" D.Fir, now stump, S.64°E. 42.9 ft., opened for scribe.

30" D.Fir, now down, S.28°W. 33.0 ft., shows scar.

10" Yew, now down, N.53½°W. 15.8 ft., laying on face.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office T. 27 S R. 1 W
S 15 | S 14
S 22 | S 23

22" Cedar S.82½°W. 44.8 ft. mkd: "T27S RLW S23 CS BT".

New BT's: 4" Maple S.66°E. 31.0 ft. mkd: "T27S RLW S23 CSBT".

30" D.Fir N.30°W. 52.3 ft. mkd: "T27S RLW S15CS BT".

11/21/69

¼ Corner to Sections 11 and 14.

Found - No Trace of Corner Stone nor S.W. Bearing Tree.

18", now 30" D.Fir N.68½°E. 30.4 ft., opened & found scribing.

We Rescribe: "¼ S11 CS BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 27 S R 1 W
1969 ¼ S 11
S 14

New BT: 40" D.Fir S.75°E. 14.7 ft. scribed "¼ S14 CS BT".

This ¼ corner lies 75 ft. east of logging road.

11/20/69

Section Corner to Sections 3 - 4 - 9 - 10.

Found - Stone, right size but no marks visible.

14" D.Fir(Rec.Hemlock) Down, S.59°W. 40.9 ft., scribe visible.

12", now 10" Hemlock N.45°E.(Rec.NE) 31.0 ft., scribe visible.

18", now 26" Hemlock, S.72°E. 22.4 ft.(Rec.48.8') scribe visible.

24" D.Fir(Rec.Hemlock) N.49°W. 17.8 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 27 S R 1 W
1969 S 4 | S 3
S 9 | S 10

New BT: 14" Hemlock S.38°W. 63.3 ft. mkd: "T27S RLW S 9 CSBT".

All other Bearing Trees O. K. and Tagged.

11/25/69

¼ Corner to Sections 4 and 9.

Found - No trace of Corner Stone nor N.E. Bearing Tree.

18", now 24" D.Fir, S.15°E. 12.5 ft., open for scribe "4 S 9".

(This tree faces badly, however, by scribe & ring count use for S.E.BT)

Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 27 S R 1 W
1969 S 4
S 9

New BT: 24" Cedar N.52°E. 10.0 ft. mkd: "¼ S 4 CS BT".

Reblzd. & Rescbd: 24" D.Fir S.15°E. 12.5 ft. mkd: "¼ S 9 CS BT".

11/25/69

Section Corner to Sections 15 - 16 - 21 - 22.

Found - No trace of Corner Stone nor N.W. - S.W. BT's. due to old skid trail.

28", now 35" D.Fir, N.16°E. 31.7 ft., shows good scar.

14", now 25" D.Fir, S.40°E. 5.9 ft., opened for scribe "S2".

Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 27 S R 1 W
1969 S 16 | S 15
S 21 | S 22

New BT: 26" D.Fir N.61°W. 73.3 ft. mkd: "T27S RLW S16 CS BT". #144

No trees available to S.W.

This corner lies at N.E.Cor. very old clear cut unit about 200' North of flat bench, on the point of a small ridge, running S.E.

11/26/69

¼ Corner to Sections 16 and 21.

Found - No trace of Corner Stone

40", now 48" D.Fir, North 7.9 ft., tree opened at earlier time, "16" vis.

30", now 40" D.Fir, S.50°W. 31.0 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office T 27 S R 1 W
1969 ¼ S 16
S 21

Bearing Trees O. K. and Tagged.

11/26/69

John M. Powell
Frank Jones & W. Penley
November, 1969 C. S. File No. 54/94

RE-RENEWED, SEE CORNER NO. #189