

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Sections 29 - 30 - 31 - 32. 75
 Found - 24x12x8" Stone at corner, no marks.
 30" D.Fir, now Snag, N.15°E. 44.2 ft., shows scar.
 24" Fir, now stump, S.78°E. 61.4 ft., opened for scribe. #152
 8" Fir, now 26", S.40°W. 17.2 ft., shows good scar.
 30" Fir, now stump, N.15°W. 66.0 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
 Office S 30 | S 29
 1969 S 31 | S 32
 New BT's: 26" Hemlock N.89°W. 46.1 ft. mkd: "T27S R1W S30 CS BT".
 14" D.Fir N.58°E. 15.7 ft. mkd: T27S R1W S29 CS BT.
 24" D.Fir S.69°E. 78.5 ft. mkd: T27S R1W S32 CS BT.

11/28/69

$\frac{1}{4}$ Corner to Sections 30 and 31. 76
 Found - 24" D.Fir, now stump, North 7.9 ft., shows good scar.
 24" D.Fir, now stump, S.63°W. 19.1 ft., opened for scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
 Office S 30
 1969 S 31
 New BT's: 17" D.Fir S.21 $\frac{1}{2}$ °W. 34.3 ft. mkd: " $\frac{1}{4}$ " S31 CS BT.
 36" D.Fir N.63 $\frac{1}{2}$ °E. 78.3 ft. mkd: " $\frac{1}{4}$ " S30 CS BT".

11/28/69

$\frac{1}{4}$ Corner to Sections 9 and 10.
 Found - 30" Fir, now stump, N.69°E. 23.1 ft., tree cut below face.
 16" Fir, now stump, N.33°W. 25.7 ft., face badly burnt,
 found "1" above burn area " $\frac{1}{4}$ " very faint on burnt face.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
 Office, 1969 $\frac{1}{4}$ S 10 | S 9
 No trees available to scribe.
 Set - 3/4" I.Rod for bearing objects, as follows



12/1/69

$\frac{1}{4}$ Corner to Sec. ³²35, T27-1W and Sec. ⁵2, T28-1W. 78
 Found - 18x12x6" Corner Stone, in place, mkd: " $\frac{1}{4}$ ".
 18", now 30" D.Fir, S.32°W. 9.9 ft., shows good axe face.
 16" D.Fir N.45°W. 9.2 ft., opened & found scribing.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R.1W $\frac{1}{4}$ S 32
 Office, 1969 T28S S 5
 Stand. Cor.
 New BT: 30" D.Fir N.40°W. 22.5 ft. mkd: "S6 $\frac{1}{4}$ S32 CS BT".
 This corner lies 300.0 ft. East of a logging road.

11/28/69

Section Corner to Sections 33 and 34 only, T27-1W. 79
 Found - 40" S.Pine, now down, N.40°E. 7.3 ft., opened for scribe. #127
 12", now 15" Fir, N.14 $\frac{1}{2}$ °W. 38.3 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 33 | S 34
 Office, 1969 T28S S 4
 New BT: 18" Hemlock N.43°E. 31.3 ft. mkd: T27S R1W S34 CS BT.

11/24/69

Cl.C. Section Corner to Sections 4 and 3 only, T28-1W. 80
 Found - 12x8x8 Stone At Closing Corner mkd: "CC" & 3 notches on E-W sides.
 10", now 15" Fir, S.60°E. 11.9 ft., shows good scar.
 12", now 17" Cedar, S.12°W. 21.1 ft., scribe visible, "4". #128
 Set - Brass Cap at C. Cor. Mkd: County Surveyor's T27S R1W C.C. S 34
 Office, 1969 T28S S 4 | S 3
 Bearing Trees O. K. and Tagged.

11/24/69

$\frac{1}{4}$ Corner to Sec. 33 only, T26-1W. 81
 Found - No trace of Corner Stone. 10", now 13" D.Fir, N.60°E. 16.5 ft.,
 opened for scribe. 24", now 27" D.Fir, N.29°W. (Rec.N21W)
 7.9 ft., shows good scar.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S R1W $\frac{1}{4}$ S 33
 Office, 1969 T27S

12/1/69

John M. Powell
 Frank Jones & W. Penley
 November & December, 1969
 C.S. File No. 54/94