

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 1 W R.W.W.M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21981

1/4 Corner Section 5 only, T27-1W. (North Bdry.) 88  
 Found - 12x8x8 Stone, firmly set, mkd: "1/4".  
 12", now 15" Hemlock S.38°E. 9.9 ft., scribe visible.  
 6", now 8" Hemlock, S.35°W. 16.5 ft., shows good scar.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 26S  
 Office, 1969 T 27S RLW 1/4 S 5

Bearing Trees all O. K. and Tagged. 12/4/69

1/4 Corner to Section 32 only, T26-1W. (South Bdry.) 89  
 Found - 48" D.Fir Corner Tree, now snag, rotted face, scribe visible.  
 No trace of small Bearing Trees. This corner lies at top of  
 60 ft. bluff, BT's. probably went over.  
 On North Side of Corner Tree, directly under tree;  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW 1/4 S 32  
 Office, 1969 T27S

New BT's: 7" Cedar N.89°W. 20.0 ft. mkd: "1/4 S32 CS BT".  
 8" Cedar N.50°W. 20.0 ft. mkd: "1/4 S32 CS BT". 12/4/69

Section Corner to Sections 5 and 6 only, T27-1W. 90  
 Found - Stone, right size, but no marks. #122  
 36", now 40" Cedar, S.28°W. (Rec.S34W) 34.3 ft., scribe visible.  
 26", now 40" D.Fir, S.35°W. 22.4 ft., shows good scar.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S RLW S 31  
 Office, 1969 T27S S 6 | S 5

Bearing Trees All O. K. and Tagged. 12/4/69

Section Corner to Sections 31 and 32 only, T26-1W. #123 91  
 Found - No trace of Corner Stone.  
 24", now 36" Cedar, N.34°E. 7.9 ft., rotten face.  
 12", now 15" Hemlock, N.19°W. 21.8 ft., scribe visible, rotted face.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T26S S 31 | S 32  
 Office, 1969 T27S RLW S 5

Reblzd. & Rescbd: 36" Cedar N.34°E. 7.9 ft. mkd: "T26S RLW S32 CS BT".  
 15" Hemlock N.19°W. 21.8 ft. mkd: "T26S RLW S31 CS BT". 12/4/69

Section Corner to Sections 12 and 13 only, T27-1W. 92  
 Found - 20x10x4 Stone, firmly set, mkd: 2 notches N. and 4 - South.  
 No trace of Brass Cap being set, nor N.W. or N.E. BT's.  
 Orig. 16" Fir S.65°E. 23.1 ft., this tree destroyed.  
 12", now 16" Yew, S.61 1/2°W. 43.4 ft. (Rec.28.4), scribe visible.  
 Reblzd. & Rescbd: "T27S RLW S12 CS BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 27 S R  
 Office 1 S 12 | S18 1  
 1969 W S 13 | E

New BT: 30" D.Fir N.9°W. 25.1 ft. mkd: "T27S RLW S12 CS BT". 12/8/69

Closing Corner to Sections 7 and 18, T27-1E. 93  
 Found - 1927 GLO Brass Cap, properly marked, out of ground.  
 12", now 14" Fir, N.64°E. 7.9 ft., pitched over, scribing visible  
 16", now 26" Fir, S.40°E. 26.1 ft., shows good scar.  
 All Bearing Trees O. K. and Tagged.  
 Reset - Brass Cap in Mound of Stone. 12/8/69

1/4 Corner to Section 13 only, T27-1W. 94  
 Found - 10x8x7 Stone, firmly set, however, mkd: "1/4" on East side.  
 Orig. 14", now 27" D.Fir, S.15°W. orig. 22.4', (1927 25.1') shows good scar.  
 (Orig. Tree destroyed)  
 28" Fir, now stump, S.70°E. 19.8 ft.  
 14", now 19" D.Fir, N.86°W. (Rec.N79W) 29.0 ft., opened for scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 27 S R  
 Office 1 1/4 S13 | 1  
 1969 W E

Reblzd. & Rescbd: 27" D.Fir S.15°W. 22.4 ft. mkd: "1/4 S13 CS BT".  
 This corner lies 119.0 ft. S. of 1/4 Cor. Sec.18, R1E. (Rec.116.2 ft.) 12/8/69

John M. Powell  
 Frank Jones & W. Penley  
 December, 1969 C.S. File No. 54/94