

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 1 W. R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & W. Penley
December, 1969 C. S. File No. 54/94

$\frac{1}{4}$ Corner to Sections 27 and 28. 95
Found - 20x10x8" Stone, mkd: " $\frac{1}{4}$ " on West face, firmly in ground.
18", now 27" Fir, S. 60°E. 31.7 ft., shows good scar.
14", now 18" Cedar, S. 85°W. 7.9 ft., scribe visible. #206
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office, 1969 $\frac{1}{4}$ S 28 | S 27
All Bearing Trees O. K. and Tagged. 12/11/69

$\frac{1}{4}$ Corner to Sections 14 and 23. 96
Found - 15x15x8 Corner Stone, in place, & mkd: " $\frac{1}{4}$ " on North face.
Orig. 30", now 50" D. Fir, N. 12°W. 36.3 ft., shows good axe face.
Orig. 14" D. Fir, now 20" Stump, S. 28°E. 42.2 ft., open & find scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office 1969 $\frac{1}{4}$ S 14
S 23
Resbd: 50" D. Fir N. 12°W. 36.3 ft. mkd: " $\frac{1}{4}$ S14 CS BT".
New BT: 6" Cedar S. 45°E. 53.9 ft. mkd: " $\frac{1}{4}$ S23 CS BT".
This $\frac{1}{4}$ corner lies 70 ft. East about of ridge in a cutting unit. 12/11/69

$\frac{1}{4}$ Corner to Sections 20 and 29. 97
Found - Unrecorded 5/8" I. Rod, but no trace of Corner Stone.
24", now 28" Hemlock, N. 56°E. 25.1 ft., found open face scribe. #150
24" Hemlock, now 25" Snag, S. 40°W. 25.1 ft., found burnt face, no scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office 1969 $\frac{1}{4}$ S 20
S 29
Rescribed BT: 28" Hemlock N. 56°E. 25.1 ft. mkd: " $\frac{1}{4}$ S20 CSBT".
New BT: 5" D. Fir N. 36°W. 40.7 ft. scribed " $\frac{1}{4}$ S20 CSBT".
No BT's. in range to south of line.
This corner lies in a cutting unit. 12/10/69

$\frac{1}{4}$ Corner to Sections 21 and 28. 98
Found - 16" Hemlock, now down & rotten, S. 61°E. 35.6 ft., shows old face.
20" Hemlock, now stump, N. 65 $\frac{1}{2}$ °W. 16.5 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office 1969 $\frac{1}{4}$ S 21
S 28
New BT's: 18" Hemlock S. 80°E. 46.3 ft. mkd: " $\frac{1}{4}$ S28 CS BT".
12" Hemlock N. 5°E. 29.3 ft. mkd: " $\frac{1}{4}$ S21 CS BT". 12/10/69

$\frac{1}{4}$ Corner to Sections 25 and 36. 99
Found - 12x12x8 Stone, firmly set at $\frac{1}{4}$ corner, no marks found.
14", now 24" Fir, North (Rec. South) 15.8 ft., shows good scar.
10", now 12" Cedar, S. 17 $\frac{1}{2}$ °W. (Rec. N17 $\frac{1}{2}$ W) 19.8 ft., scribe visible on rotten face.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office 1969 $\frac{1}{4}$ S 25
S 36
New BT: 16" D. Fir S. 57 $\frac{1}{2}$ °W. 7.5 ft. mkd: " $\frac{1}{4}$ S36 CS BT". 12/5/69

$\frac{1}{4}$ Corner to Sections 16 and 17. 100
Found - No trace of Corner Stone.
No trace of S. E. Bearing Tree (Skid Road)
20", now 31" D. Fir, Snag Top, S. 60°W. 21.8 ft., opened for scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W
Office, 1969 $\frac{1}{4}$ S 17 | S 16
New BT's: 19" D. Fir S. 1° E. 40.0 ft. mkd: " $\frac{1}{4}$ S16 CS BT".
33" D. Fir S. 52°W. 37.4 ft. mkd: " $\frac{1}{4}$ S17 CS BT". 12/5/69

$\frac{1}{4}$ Corner to Sections 13 and 24. 101
Found - No Trace of Corner Stone or N.W. BT., due to old logging.
30", now 40" D. Fir, S. 15°E. 23.1 ft., opened for scribe " $\frac{1}{4}$ ".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W #182
Office 1969 $\frac{1}{4}$ S 13
S 24
New BT: 48" D. Fir N. 89°E. 68.8 ft. mkd: " $\frac{1}{4}$ S13 CS BT".
This corner lies on south side of old skid road. 12/11/69