

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 2 R. W. W. M.

Ben B. Irving
Wit. James Beatty
March 9, 1929

H.L. Eppstein
by B.A. Lane
March 1935

Vol. 7 Re. 17

SECTION CORNER BETWEEN 4, 3, 9, and 10

Identified by an old stone with 5 notches on South and 3 notched on East face. Also original B.T.s as follows
Fir 30" dia. bears S.78°E., 81 ft. which I reblaze and scribe
Fir 30" dia. bears S.63½°W., 79 ft. Which I reblaze and scribe
Fir 24" dia. bears N.64½°W., 59 ft. which I reblazed and scribed
And a new B.T. a 20" Fir N.14½°E., 106.7 ft. which I blazed and scribed.

The two 30" fir B.T.s were cut by forest Service in 1935. New B.T.s were set. Also a 2" x 48" Galvanized Iron Pipe for corner. The new B.T.s are
Sugar Pine 6" dia. N.13½°E., 12.9 ft. marked C.S. S.3 T.27 S. R.2W.
Fir 12" dia. bears N.74°W., 70.6 ft. marked C.S. S.4 T.27S.R.2W.

James W. Byron, Dep. Sur.
M. Godfrey
S. Billow
Sept. 16, 1957
C.S. File No. 49/15
Water Right for W.L. Strain

Section Corner to Sections 8 & 9.

Found - Both original BTs. The 18 inch, Now 26 inch stump open, scribed "S" S.22°E., 24.4 feet.
The 18 inch now 28 inch R. Fir N.66°W., 23.1 feet. I open & find scribing "8S".
Also find 12 X 8 X 7 inch Balsalt stone marked ¼ on W. face.
BTs check bearings & distances to stone at corner.
Set Brass Cap at corner & along side of corner stone. — Marked Cap: County Surveyor's Office, 1957 ¼ S. 8/9 T.27 S., R. 2 W.
New Bearing Trees: Blaze & rescribe original N.W. BT. N.63°W., 22.9 feet, ¼ S 8 CS BT.
Blaze & scribe 8 inch R. Fir, N.21°E., 14.3 feet, ¼ S 9 CS BT.
Note - At West edge 3 foot log.

James W. Byron, Dep. Surv.
M. Godfrey
S. Billow
T. Shrum
C. S. File No. 49/28
Nov. 7, 1957

SECTION CORNER BETWEEN 13, 14, 23, & 24.

Found- Original 10" now 12" Hemlock S. 37° W., 4.6 ft. Tree dead and leaning. I open & find good scribing "S 23".
Original 18" now 24" Cedar now stump. Shows old face . Rotted, no scribing found.
The original S.E. & N.E. BTs. not found.
Set Brass Cap at Corner marked S14 / S13 T27S R2W County Surveyor's Office, 1957.
New BTs.: 20" Cedar bears N. 32½°E. 96.4 ft. scribed T27S R2W S13 CS BT.
Note: BT. at bottom small stream scribed 6 ft. above ground.
Chisled "4" & "B.O." on 6'X6' rock at North edge of stream. Bears N.28°W. 52.2 ft.
Chisled "+ 4" & "B.O." on 6'X3' rock (North Side) bears S.41°E. 77.2 ft.
Note: This area has been burned. No trees available except in N.E.
FOUND O.K. Nov. 1948 V.R.T. Wit. T. Shrum

Renew Corner 11/12 / 13 T. 27 S., R. 2 W.

Found-All original BTs. except 6" Hemlock S.75°E. 36.3 ft.
Original 7" now 16" W. Fir Stump N.23°W., 27.1 ft. Has open face. Good scribing "BT".
Original 24" Hemlock now 38" Hemlock Stump shows old face, no scribing
Original 8" now 14" W. Fir Stump N.28°E., 46.9 ft. Shows good scar, I do not open.
Set Brass Cap at corner marked S11/S12 T.27S., R2W., County Surveyor's Office, 1957. #103
New BTs: 52" R. Fir Stump bears N.57½°W. 38.0 ft. scribed T27S R2W S11 CS BT.
58" R. Fir bears N. 26°E., 113.7 ft. scribed T27S R2W S12 CS BT.