

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 S. T. S. R 2 W. R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

Howard W.
Johnstone
For Rsbrg. Lbr.
Aug. 18, 1962
C.S. File No.
51/163

Section Corner for Sections 1 and 12 only, R. 1 & 2 W.
Found - 5" x 6" x 8" Stone, 5 notches on South Side.
28" W. Fir S. 50°E. 17 lks. (wood scribe visible) # 157
30" Fir N. 73°W. (record N. 80°W.) 20 lks. (faint bark scribe)
34" Fir S. 52°W. (record S. 45°W.) 33 lks. (bark scribe destroyed)
Set - 2" x 30" Iron Pipe.
Scribed - 10" Fir N. 31°W. 22.4 ft.
34" Fir S. 52°W. 23.8 ft.

FOUND O.K.
10/24/68 VRT

10

Closing Corner for Section 25 and 36.
Found - Old Cedar Stake, some scribing still visible "S25".
Hemlock, broken off & dead, S. 76½°W. 33.7 ft. Perfect scribing
still visible on open face "T27S R2W S36 B".
Hemlock, now 12", N. 76°W. 25.1 ft., scribing visible "27S R2W"
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W S25 RLW CC
Set Orig. Post alongside & Office, 1962 S36
Erect Rock Mound.
New BT's: 20" Hemlock S. 22°W. 42.3 ft. Mkd: T27S R2W CC S36 CS BT.
19" R. Cedar N. 64°W. 23.0 ft. Mkd: T27S R2W CC S25 CS BT.
Note - Corner falls in White Creek near East Bank.

11

Witness Corner for Sections 30 and 31, T27-1W.
This corner originally set as corner for sections 25 and 36, T27-2W and
Secs. 30 & 31, T27S RLW. All 4 Orig. trees found, but bearings given
are all wrong, The N.W. tree is actually N.E. The S.E. tree is
actually S.W.; The S.W. tree is actually N.W.; The N.E. S.B. S. E.
Found - Cedar, now 30", S. 46½°E. (not N. 46½°E) 39.6 ft., scribing plainly
visible on open face "T27S RLW S31 BT".
Stump of 12" Hemlock S. 22½°W. (not S. 22½°E.) 25.7 ft. Axe marks on
old face where scribing had been cut off. # 193
20" Hemlock N. 62°W. (not S. 62°W.) 25.1 ft. Broken off & dead.
Axe marks & a few traces of scribing plainly visible on old
face where scribing was cut off.
Cedar, now 36", N. 69°E. (not N. 69°W.) 21.0 ft. (not 25.1 ft.)
Scribing visible on open face "T27S RLW".

Corner falls in White Creek. Could not set Corner in this location.
Set Witness Corner 10 feet East of Corner.

Set - Brass Cap Mkd: County Surveyor's T27S R2W W.C. S30 RLW
Office, 1962 - 10' W. to Corner. S31 FOUND O.K.
10/68 VRT.

Did not find Rock set for Corner.

Blaze & Rescribe the N.E. Tree: 36" Cedar N. 51°E. 11.9 ft. Mkd:
"T27S RLW W.C. S30 CS BT".

Did not rescribe S. E. BT. which bears S. 36°E. 32.0 ft. from Brass Cap.

12

¼ Corner to Sections 24 and 25.
Found - Fir, now 68", N. 22½°E. 23.8 ft. Cut open & fd. good scribing "4 & BT".
W. Fir Stump, now 25", S. 57½°E. 39.6 ft. Has been cut off below
scribing, but lower part of face visible on stump.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W ¼ S24
Office, 1962 S25 97
New BT's: 9" Yew N. 17°W. 24.0 ft. Mkd: ¼ S24 CS BT.
22" Hemlock S. 65°W. 12.0 ft. Mkd: ¼ S25 CS BT.

13

Section Corner to Sections 2 - 3 - 10 - 11
Found - G.L.O. Brass Cap at Corner.
6" Fir N. 60°E. 57.4 ft., alive & standing, scribing still visible. # 256
5" Cedar S. 28½°E. 19.8 ft., alive & standing, scribing still visible.
8" Fir N. 57½°W. 21.8 ft., alive & standing, scribing still visible.
24" Cedar N. 59°W. 49.5 ft., alive & standing, " still vis. (Orig. BT.)
5" Pine S. 27°W. 18.5 ft., standing but dead, scribing visible.
New BT: 9" Hemlock S. 22°W. 29.7 ft. Mkd: T27S R2W S10 CS BT.

14

12/68 FO O.K. VRT.
FO OK BY GEISLER 4/84
M 90-55

Milo E. Godfrey, Deputy County Surveyor
Michael Stone
September 7, 1962
C. S. File No. 49/28