

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

109

1/4 Corner to Sections 30 and 31.

Found - Truck Axle at corner point, properly marked in 1962, See Ren. #29.
Orig. 30", now 34" Hemlock (decaying stump) N. 46° W. 12.5 ft., scribe visible
20" D. Fir Stump N. 52 1/2° E. 36.7 ft. scribed & Alum. Tag #4287.
S.W. BT. Stump, turned out & lying face down.
Set - 6 ft. Steel Fence Post alongside Axle.
New BT: 4" D. Fir N. 57° E. 36.0 ft. mkd: "S30 CS BT".
No other trees available. This corner lies 165 ft. E. of creek,
course N. and approx. 400 ft. E. of Road N. & S.

110

1/4 Corner to Sections 6 and 7.

Found - Orig. 36", now 44" Fir, alive, N. 40° W. 23.1 ft., bark scribe visible.
Orig. 30" Fir, now down & badly decayed, South 3.3 ft., no scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 T 27 S R 2 W
1/4 S 6 / S 7
New BT's: 15" D. Fir N. 81° W. 59.8 ft. mkd: "1/4 S6 CS BT".
9" D. Fir S. 20° W. 53.5 ft. mkd: "1/4 S7 CS BT".
This corner lies on steep southerly slope on N-S cutting line, cut off to E.

111

1/4 Corner to Sections 8 and 9.

Found - 1957 C.S. Brass Cap & BT. as follows, See Ren. #2.
Orig. 18", now 30" Fir, alive, good cond., N. 63° W. 22.9 ft., reblaze healing.
N.E. Ren. BT. gone completely due to clearing & USFS Housing.
No trees suitable to east of line.
New BT: 11" Cedar S. 58° W. 43.8 ft. mkd: "1/4 S8 CS BT".
This corner lies in N - S fence on west side of U.S. Govt. Trailer Park.

112

1/4 Corner to Sections 19 and 30.

Found - Orig. 8", now 25" Fir, alive, S. 0° 30' E. 20.5 ft., Open & find "S30".
Orig. 8", now 30" Fir, N. 31° W. 14.5 ft., alive, shows faint scar.
Rescribe: "1/4 S19 CS BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1968 T 27 S R 2 W
1/4 S 19 / S 30 8/85
New BT: 18" D. Fir S. 37° E. 28.0 ft. mkd: "1/4 S30 CS BT".
This corner lies on top of ridge sloping north.

113

Closing Corner to Sections 5 and 6, T28-2W.

Found - Brass Cap and 2 BT's., See Ren. #19.
42" D. Fir, now 43", S. 45° W. 7.2 ft., shows bark scribing.
48", now 49" D. Fir, S. 34° W. 55.5 ft., shows bark scribing. #211
Remark Brass Cap to Read: County Surveyor's Office, 1968 T27S R2W c.c. S 6 | S 5
Rescribed: 49" D. Fir S. 34° W. 55.5 ft., scribed T28SR2WS5 CC CS BT.
New BT: 6" Madrone S. 1° W. 44.0 ft. mkd: T28S R2WS6 CC CS BT.
This corner lies N. 85° E. 7.0 ft. of A.P. Sec. 31 & 6 which is O.K. and
226.9 ft. of corner of Sections 31 & 32, T27-2W, see below.

114

Section Corner to Sections 31 and 32, T27-2W.

Found - 1/2" I.P. & 2 good BT's., see Ren. #18.
10", now 12" D. Fir, N. 12° W. 14.7 ft., shows scribing.
6", now 7" Madrone, N. 78° E. 21.4 ft., shows scribing. #212
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T27S R2W C.C. S 31 | S 32
Note - This corner lies on top of rocky ridge sloping south and lies
East 226.9 ft. of C.C. Secs. 6 & 5, T28-2W., see above.

Vernon "Ray" Tracy
Frank Jones & V. Perron
November, 1968 C. S. File No. 54/40

RE-RENEWED CORNER NO. #240
RE-RENEWED CORNER NO. #223
RE-RENEWED CORNER NO. #211
RE-RENEWED CORNER NO. #212

FO. OK ROM GEISLER
M 90-71

Rec. 13 S.E. FIELD
FRANCY'S FIELD NOTES READ S.W.