

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

115
#261
1/4 Corner to Sections 7 and 8.
Found - 14x12x10" Basalt Stone mkd: "1/4".
Orig. 24" Fir, now 36" Stump, N.88°E. 63.4 ft., Open & find scribe.
Orig. 18", now 28" Fir, alive, N.20°W. 44.2 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W
(Reset Stone on N. Side) Office, 1968 1/4 S 7 | S 8
New BT's: 9" D. Fir S.75°E. 15.2 ft. mkd: "1/4 S8 CS BT".
14" Pine S.75°W. 16.9 ft. mkd: "1/4 S7 CS BT".
This corner lies on moderate southerly slope.

116
1/4 Corner to Sections 19 and 20.
Found - Orig. 18", now 24" Cedar, alive, S.33 1/2°W. 13.9 ft., previously
opened, no scribe visible. Open higher & find "1/4" scribe.
Orig. 30", now 36" Cedar, alive, S.41 1/2°E. 32.3 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W
Office, 1968 1/4 S 19 | S 20
New BT's: 10" Cedar S.20°E. 25.2 ft. mkd: "1/4 S20 CS BT".
18" Hemlock S.26°W. 28.9 ft. mkd: "1/4 S19 CS BT".
This corner lies on moderate easterly slope about 130 ft. south of
small creek, flowing east.

117
Section Corner to Sections 5 - 6 - 7 - 8.
Found - 3" + on Rock Outcrop 6 ft. long, 2 ft. high and
1905 BT's., as follows:
16", now 24" Fir, alive, N.84°E. 93.1 ft., open & find scribe.
48", now 54" Fir, alive, S.65°E. 90.4 ft., shows good scar.
30", now 38" Fir, alive, S.23 1/2°W. 101.6 ft., scribe visible
on previously opened blaze.
8", now 24" Fir, alive, N.31°W. 70.6 ft., opened, probable
scribe marks visible.
Set Brass Cap 1' west of Corner Point Mkd: T 27 S R 2 W
County Surveyor's S 6 | S 5
Office, 1968 S 7 | S 8
New BT's: 14" D. Fir S.78°W. 9.4 ft. mkd: T27S R2W S7 CS BT.
12" D. Fir N.60°W. 11.3 ft. mkd: T27S R2WS6 CS BT.
10" D. Fir N.50 1/2°E. 7.7 ft. mkd: T27S R2W S5 CS BT.
14" D. Fir S. 2°E. 23.7 ft. mkd: T27S R2W S8 CS BT.
(Bear. & Dist. from True Cor., not Brass Cap. - Lines well blazed E. & S.)

118
Section Corner to Sections 5 and 4.
Found - Found - Orig. 30", now 38" Fir, alive, N.80°W. 13.2 ft., bark
scribe visible, poor condition.
Orig. 20", now 30" Fir, alive, N.45°E. 19.8 ft., remains of
axe bark blaze, no scribe or scar.
Hole where S. E. BT. would have been.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W
Office, 1968 S 5 | S 4
New BT's: 8" D. Fir N.88°E. 13.0 ft. mkd: T27S R2W S4 CS BT.
7" D. Fir N.39°W. 19.5 ft. mkd: T27S R2W S5 CS BT.
This corner lies on steep east slope 69.3 ft. west of C. C. Secs. 8 & 9.

119
Closing Corner to Sections 8 and 9.
Found - Corner Stone, in place. 69.3 ft. E. of Sec. Cor. 4 & 5, see above.
Orig. 14" Alder, now only badly decayed stub, S.60°E. 17.2 ft.,
axe marks, no scribe found.
Orig. 8", now 17" Maple, alive but leaning badly, S.23°W. 46.2 ft.,
we open & find scribe marks.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W #226
(Reset Stone alongside) Office, 1968 C.C. S 8 | S 9
New BT's: 12" Yew S.47°W. 50.0 ft. mkd: T27S R2W S8 CC CS BT.
20" D. Fir S.62°E. 45.4 ft. mkd: T27S R2W S9 CC CS BT.
This corner lies on west edge of small creek, course south.

Vernon "Ray" Tracy
F. Jones & V. Perron
December, 1968 C. S. File No. 54/40

FDOK D. Edwards
3/2001 M136-69 CS 65/34-5

12/5/68