

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T.S. R. 2 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97101

Thomas E. Shrum, Jr.
For: U.S. Plywood
Dec. 1968
Map File M 37 - 17

Angle Point Section 31 and 6, T28-2W. (south of $\frac{1}{4}$ corner) SEE ALSO #99
Set - 2 1/2" diam. Aluminum Cap Mkd: "A.P. T27S R2W S6 S31 T28S".
10" D. Fir, S. 65° E. 11.1 ft., "A.P. S6, BT R.E. 4287".
10" D. Fir, N. 02° W. 33.3 ft., "A.P. S31, BT R.E. 4287". #187

133

Angle Point Section 6 and 31, T27-2W (South of NE cor. Sec. 6)
Set - 2 1/2" Aluminum Cap, "A.P. T27S R2W S6 S31 T28S".
6" Madrone N. 03° W. 27.9 ft. mkd: "A.P. S31 BT R.E. 4287". #210
6" D. Fir S. 43° W. 23.1 ft. mkd: "A.P. S6 BT R.E. 4287".

134

$\frac{1}{4}$ Corner to Sections 6 & 5
Found - O.B.T.S as follows:
Orig. 32" now 38" Fir S. 60°E. 14.5 Ft. Alive frag.
barkscribe visible.
Orig. 30" now 48" Fir S. 80°W. 34.3 Ft. Alive Barkscribe
"1/4 S BT" visible. At Cor. point Set 1" I.P.
Set - Brass Cap Mkd:

135

County Surveyors
Office, 1969
T 27 S R 2 W
1/4 S 6 S 5

And Mkd. new BT's
9" Pine N. 49°E 26.3 Ft. Mkd. 1/4 S 5 CS BT
8" D. Fir N. 47°W. 6.4 Ft. Mkd. 1/4 S 6 CS BT
This Cor. lies on Southerly slope in old growth timber 6-4-69

Cl. Cor. of Sections 19 and 30, T27S. R2W.

Found - O.B.T.s as follows:
Orig. 30" Now 40" Fir N. 65 1/2° E. 22.4 Ft. Alive--shows good
Orig. 36" Fir S. 64°E 48.8 Ft. Now badly decayed remains of
stump. Blze intact. Shows "T 27 S R 2 W S 30 BT Scribe. At point
for closing Cor.
Set - 1" I.P. & Brass cap Mkd:

This is now an amended
closing CORNER - SEE Ren #230
for New positioning - Blze
By Ron Geisler
M 50-11

136

County Surveyors T 27 S
Office, 1969 R 3 W S 19 R 2 W
CC S 30

8" D. Fir N. 76°E. 10.6 ft. mkd: "T27S R2W S19 CC CS BT".
8" D. Fir S. 27°E 15.2 Ft. Mkd. T 27 S R 2 W S30 CC Cs BT
This Cor. lies on S. W. slope & approx. 217.8 Ft. South of the Sec.
Cor. of Sec's 24 & 25 of T 27S R 3 W. 4--22-69

Section Corner to Sections 24 & 25 - T27-3

Found - OETS as follows:
Orig. 20" now 30" Fir S. 78°W 23.1 Ft. now badly decayed
remains of stump bark scribe "R3W S 25 R 1"
Orig. 28" now 48" Fir S. 65°E. 29.0 Ft. Alive axe Mk. on bark.
No scribe or scar. No trace other O.B.T.S
Set - 1" I. P. & Brass Cap Mkd:

137

County Surveyors T 27 S.
Office, 1969 R 3 W S 24 R 2 W
S 25

& Mk. new BT's
6" Hemlock N. 83 E. 33.7 Ft. Mkd. T 27 S R 2 W S 19 CS BT
18" D. Fir S. 10°W 2.0 ft. Mkd. T 27 S R 3 W S 25 CS BT
8" Cedar N. 71°W. 51.5 Ft. Mkd. T 27 S R 3 W S 24 CS BT
This Cor. lies on very steep N. slope of spur & 217.8 Ft. No. of
Closing Cor. of Sec's 19 & 30 of T 27 S R 2 W. 4-22-69

Ed. 8/85
By RONALD GEISLER
M 90-11

Vernon "Ray" Tracy
J. Heritage & V. Perron
April, June 1969 C. S. File No. 54/40