

Douglas County Surveyor's Record of
Government Corners Renewed

27

T. S.

2

R. W. W. M.

ROSE, CHAPMAN CO., EUGENE, ORE. 21881

This Angle Point is Orig. Standard Corner to Secs. 32 & 33, T27-2W.

138

Found - Unrecorded 3/4" I. P. set from OBT's as follows.

Orig. 16" now 28" Fir N. 45°E. 5.9 Ft. Alive - old bark blaze. no scribe fd.

Orig. 16" now 30" Fir N. 25°W. 3.3 Ft. alive - chopped open & burned possible scribe mks.

Orig. 16" now 28" Fir S. 30° W. 64.7 Ft. alive - old bark blaze fragmentary scribe Mk. Fd.

also - Find O.B.T. unrecorded 32" Fir S. 27°E. 12.4 Ft. Alive - shows scar of Approx same age as N.W. B.T.

DO NOT SET BRASS CAP - Mk. new B.T.S.

13" D. Fir N. 12°W 11.2 Ft. Mkd. Ap CS BT

28" D. Fir N. 45°E. 5.9 Ft. Mkd. AP CS BT

The closing Cor. of Sec.'s 4 & 5 of T 28 S R 2W Bears West 96.3 ft.
6-12-69

Closing Corner Sections 5 & 4 T 28 R 2W

139

Found - Unrecorded 3/4" I.P. set from one O.B.T.

Orig. 12" now 20" Laurel S. 68°W. 11.3 Ft. alive - we open & find S R 2 scribe & Reverse. No trace O.B.T. to S. E.

DO NOT SET BRASS CAP - Mark new B.T.S.

* 18" Chinquapin S. 20°W 9.5 Ft. Mkd. T 28 S R 2 W S 5 CC CS BS

20" Laurel S. 68°W. 11.2 Ft. Remark O.B.T. CC S5 CS BT

The A.P. Cor. (old S.C. of 32 & 33 27.2) Bears East 96.3 Ft. 6-12-69

* 30" D.F. See Ren # 64 T28-2 (1-20-98 D.S.O. SC)

Section Corner to Section 32

140

Renew Angle point on S. Lines 32

Found - Unrecorded 3/4" I. P. at Cor. point & O.B.T.s as Follows:

Orig. 12" now 20" cedar S. 62°E. 5.3 ft. Open & found scribe Mks.

Orig. 8" now 12" Hemlock N. 12°W 13.2 Ft. Down & decaying

Previously opened blze rotted away. 3/4" I.P. in good cond.

DO NOT SET BRASS CAP - Mk. new B.T.S.

22" Cedar S. 18°E. 6.3 Ft. Mkd. AP CS BT

18" Cedar N. 35°E. 23.9 Ft. Mkd. AP CS Bt.

This cor. lies on moderate southerly slope in old growth timber. 6-12-69

1/2 Corner Section 18 Only (T. 27-1)

141

Found - Unrecorded U. S. Plywood Alum. Cap Mkd. 1/4" S 18 Only 1962 & O.B.T. as follows:

Orig. 7" now 9" Hemlock S. 18°E. 11.2 Ft. lying face down - we roll over & fd. 1/4" S 18 BT scribe under 40 + years of ever growth - (Old field notes call for Fir) No trace other O.B.T.

Cor. stone called for is broken & small piece is Mkd. 1/4" We mark new B.T.S.

54" D. Fir stump N. 69°E. 29.5 Ft. Mkd. 1/4" S 18 CS Bt

50" D. Fir stump S. 22°E. 37.0 Ft. Mkd. 1/4" S 18 Cs Bt. This

Cor. lies on N. slope in old clear cut area 6-20-69

142

Closing Corner Sections 4 & 3, T28-2W.

Found - O.B.T. as follows:

Orig. 6" Now 10" Yew S. 76°W. 23.1 Ft. Alive - scribe visible on unhealed blaze.

Orig. ??6" now 8" Cedar (record hemlock) East 38.9 Ft. Record S. 77°E. down & decayed - scribe S 3 BT visible. closing Cor.

Set - 1" I. P. & Brass Cap Mkd:

County Surveyor's
Office, 1969

T 27 C. C.
T 28 S4/S3. R 2 W

Mk. new B.T.S.

13" Cedar S. 12°W 10.8 Ft. Mkd. T 28 S R 2 W S 4 CC CS BT

28" W. Fir S. 29°E. 6.4 Ft. Mkd. T 28 S R 2 W S 3 CC CS BT

This Cor. lies on steep East slope. 6-16-69

Vernon "Ray" Tracy
J. G. Heritage & V. Perron
6-12-69 C. S. File No. 54/40

S. FILE