

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

Vernon "Ray"  
Tracy  
& Crew  
C.S. 54/40

Angle Point South Boundary Sec. 33, T27-2W. (See notes for Stan.  $\frac{1}{4}$  Corner) 143  
Found - Orig. 8", now 36" Fir, alive, N.70°E. 38.3 ft., shows good  
scars & fragmentary bark scribe.  
Orig. 7", now 32" Fir, alive, N.30°E. 42.2 ft., shows good scars.  
Set - Brass Cap at Angle Point Mkd: County Surveyor's T27S R2W A.P.  
Office, 1969 T28S  
New BT's: 18" D. Fir S.66°W. 4.0 ft. mkd: "AP CS BT".  
14" D. Fir N.17°W. 8.7 ft. mkd: "AP CS BT".  
Call of 2 $\frac{1}{2}$  chains to ridge top west of corner fits field notes.

M130-47  
Foot  
D. EDWARDS  
9-1998

Section Corner to Sections 7 and 8 only. 144  
Found - 14x10x7 Stone, firmly set, mkd. with notches as noted.  
30", now 42" D. Fir, N.47 $\frac{1}{2}$ °E. 33.0 ft., tree opened & burnt, scribe vis.  
18" D. Fir, now stump, N.14°W. 80.5 ft., found burnt reverse scribe.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W  
Office S 7 | S 8  
1969 S 18  
New BT's: 16" Hemlock N.44°W. 23.9 ft., mkd: "T27S R2W S7 CS BT".  
33" D. Fir S.22°E. 17.0 ft. mkd: "T27S R2W S18 CS BT".  
Reblzd. & Resbd: 42" D. Fir N.47 $\frac{1}{2}$ °E. 33.0 ft. mkd: T27S R2W S8 CS BT.  
10/13/69

John M. Powell  
Frank Jones & W. Penley  
Oct. 1969 C. S. File No. 54/40

Section Corner to Sections 17 and 18, Closing Corner. 145  
Found - 20" D. Fir, now down, S.62°W. 7.9 ft., opened tree for scribe.  
10" D. Fir, now down & rotten, S.19 $\frac{1}{2}$ °E. 27.7 ft.  
Set - Brass Cap at C. Cor. Mkd: County Surveyor's T 27 S R 2 W  
Office C.C. S 8  
1969 S 18 | S 17  
New BT's: 27" Cedar S.2°W. 31.1 ft. mkd: "T27S R2W S18 CC CS BT".  
35" D. Fir S.35°E. 19.2 ft. mkd: "T27S R2W S17 CS BT CC".  
10" Cedar N.28°W. 7.3 ft. mkd: "T27S R2W S 8 CS BT".  
10/13/69

South  $\frac{1}{4}$  Corner Section 8 only. 146  
Found - 24x13x10 Stone, firmly set, mkd. " $\frac{1}{4}$ " on north face.  
18" D. Fir, now 28", N.19 $\frac{1}{2}$ °E. 65.3 ft., tree opened & burnt.  
24", now 31" D. Fir, S.35 $\frac{1}{2}$ °W. 52.1 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W  
Office, 1969  $\frac{1}{4}$  S 8  
New BT's: 6" D. Fir N. 6°W. 42.1 ft. mkd: " $\frac{1}{4}$  S 8 CS BT".  
8" Pine N.44° E. 48.5 ft. mkd: " $\frac{1}{4}$  S 8 CS BT".  
10/13/69

$\frac{1}{2}$  Corner Section 7 only, south side. 147  
Found - 14x8x6" Stone, firmly set mkd: " $\frac{1}{2}$ " on north face.  
12" D. Fir, now snag, N.20 $\frac{1}{2}$ °E. 16. 5 ft., shows good scar.  
15", now 24" D. Fir, S.31°E. 27.7 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 2 W  
Office, 1969  $\frac{1}{2}$  S 7  
New BT's: 15" W. Fir N.9°W. 34.3 ft. mkd: " $\frac{1}{2}$  S 7 CS BT".  
24" D. Fir N.57°W. 33.7 ft. mkd: " $\frac{1}{2}$  S 7 CS BT".  
This corner lies about 85 ft. E. of spring branch, course north.  
10/14/69

MARCH 71

Vernon R.  
Tracy  
C. S. File  
No.  
54/40

North 1/4 Corner to Section 2 only, T28-2W. 148  
Found - All BT's. as recorded in Ren. #85  
No trace of 1923 GLO Brass Cap due to Cat. fire trail  
from bearing trees.  
Set - Brass Cap at Cor. Mkd: County Surveyor's  $\frac{1}{4}$  T27S R2W  
Office, 1972  $\frac{1}{4}$  S 2 T28S  
No New Bearing Trees Marked.  
This corner lies 310 ft. W. of Angle Point on N. side of Cat.  
fire trail and on south side of clearcut unit.  
6/28/72

JAN. 1972