

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 2 R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE., 21881

Center 1/4, Section 12.
Set - 2" iron pipe.
BT's - 12" Cedar, scribed, C₄ S12 BT, S.38° W., 4.4 ft.
8" Hemlock, scribed, C₄ S12 BT, N.23° E., 15.7 ft.

2/74

Baughman Surveying
for Cal Willis
M 52 - 77
February, 1974

1/4 corner for Section 12 only (EAST)
Set - Brass cap
BT's - 12" Fir, scribed, S12 BT, N.4° W., 19.0 ft.
6" Fir, scribed, S12 BT, S.49° W., 44.8 ft.

(SEE C.S. FILE M65-13 FOR NEW BT TAGS SET) 2/77

2/74

1/4 Corn. for Secs. 35 and 34

Found - 1 1/2" I.P. & Steel pipe with U.S. Plywood Alum. cap.
properly mkd., Undrecorded & set from O.B.T.'s as follows:
18" now 18" Fir, S.40° E., 52.1 ft., now decayed stump.
scribe visible on unhealed blaze.

24" now 28" Hemlock S. 54 3/4° W., 41.6 ft. Alive, old scar unopened, rescribed "1/4 S34 BT" & Alum. tag #4287

New BT - 26" Hemlock, S.1° E., 36.3 ft. mkd. "1/4 S35 CS BT"

This cor. lies in marshy area in clearing approx. 11 ft. in diam.

LOOKED FOR - NAT. PD. 474 G. LANGLITZ - MIGHT NOT BE 11/68

CC Cor. for Secs. 32 and 33 only,

Found - Orig. 16" now 24" D.Fir, at the closing cor. with a well healed blaze and four notches on the east side and well healed blazes on the north and west sides. We do not open.

From which:

Orig. 24" now 26" D.Fir bears N.44° E., 23.1 ft. (rec. N.36° 50' E., 23.1 ft.) showing a well-healed blaze.

Orig. 24" now 30" D.Fir bears N.59° W., 25.1 ft. (rec. N.55° 40' W., 24.4 ft.) with scribing "T27S R2W" visible on previously opened blaze. (Note: the orig. distance appears to have been measured to the scribed face of the BT).

We do not monument.

5/29/74

Gary Langlitz
E.D. Hartin
G. E. Quibell
C.S. 56/51
5/29/74

Closing Corner for Sec. 24 & 25 only

Found - 42" Fir snag scribed "T27S.R2W., S24 BT"
Other bearing tree not found, Corner Post not found.

Set - Brass cap at closing corner, stamped County Surveyors Office

		T27S			
R	C	S24		S30	R
2	C	S25			1
W					W
1975					

L.E. Monrean
P.L. Earle
C.S. 57/30
5/21/75

BT's - A 17" Hemlock bears S51° W., 40.2 ft. scribed "CC S25 T27S R2W CS BT"

A 16" Hemlock bears N.63° W., 26.0 ft. scribed "CC S24 T27S R2W CS BT"

A stone 16" 10" X 8" with 4 notches on one edge & 2 notches on the opposite edge, lying on surface of ground bears N. 4° W., 58.9 ft. (rec. N.0° 45' W., 60.7 ft.)

Closing Cor. Common to 19 and 30 only T27 R1

Found: 16" X 10" X 8" stone with 4 notches on one edge and 2 notches on the opposite edge, lying on surface of ground.

A rotted stump bears N.65° E., 8.5 ft. (Rec. 11.9 ft.) No scribing

A fir stump bears S 42° W., 37.7 ft. (42" fir snag stands directly on line and scribed as BT for closing corner to the south) (Rec. 36.6 ft)

Set: Brass cap stamped "Co. Surveyors Office T27S R1W 1975

		R2W			
S24		S19			
		S30			

L.E. Monrean
P.L. Earle
A.V. Cangie
6/19/75
C.S. 57/30

Set Original Stone on easterly edge of cap.

BT's A 14" dia. Hemlock bears N 21° E., 48.5 ft. Scribed " T27S R1W S19 Cs BT"

A 16" Dia. Hemlock Bears S71° E., 28.3 ft. Scribed " T27S R1W S30 CS BT"

477