

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

15

1/4 Corner to Sections 2 and 11.

Found - Fir, now 42", N.10°E. 8.6 ft., bark scribing visible "S",
no "BT" found but bark had been flattened with an axe,
bark charred on lower face.

Stump Hole with clump of Maple shoots around it S.5°E.,
not N.5°E. 8.6 feet.

Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W 1/4 S 2
Office, 1962 S 11

New BT's: 7" Hemlock N.62°W. 22.0 ft. Mkd: 1/4 S2 CS BT.

10" Hemlock S.15°E. 18.5 ft. Mkd: 1/4 S11CS BT.

FD. O.K. Nov. '68 Cor. lies 30' W of N.W. Cor. of CLEARCUT UNIT. V.R.T.

A/84
FD OK
BY GEISLER
M90-55

Section Corner to Sections 1 - 2 - 11 - 12.

Found - Rock set by Roberts in mound of rocks.

Fir, now 30", S.79°E. 30.4 ft., scribing visible in previously
opened, scar "T2". Tree is alive & standing.

Fir, now 24", S.39°W. 35.6 ft., shows good axe scar. Tree is
alive & standing.

Cedar N.20°W. 15.8 ft. & Hemlock N.21°E. 31.7 ft. are both
down, uprooted, The Hemlock is badly decayed; Cedar fairly
well preserved.

Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R2W S 2 | S 1
Office, 1962 S 11 | S 12

Set in Mound of Rock 2 ft. high.

Red Cedar, blazed but not scribed bears South 14.0 ft. from Corner.

A Small Stream running North is approximately 50 feet East of Corner.

16

Closing Corner for Sections 30 and 31.

Found - 30" Fir Stump S.75°E. 19.1 ft., good scribing visible on old face.

36" Fir Stump, uprooted, N.50°E. 18.5 ft., scribing visible "W S30"

Set - Brass Cap at Corner Mkd: County Surveyor's T27S R2W C.C. S30
Office, 1962 S31

a 1 1/2" Iron Pipe bears N.80°E. 1.1 feet.

Scribe 36" Fir Stump S.18°E. 59.4 ft. Mkd: "T27S R2W S31 CS BT".

Note - in clean cut area, No trees available.

Corner lies approximately 50 ft. N. of a timber access road.

FOUND O.K. 10/31/68 V.R.T.

RE-RENEWED CORNER NO. #239

17

Closing Corner for Sections 31 and 32.

Found - 1 1/2" Iron Pipe in Mound of Rock at Corner.

Rotten Fir Snag N.29 1/2°E. 6.6 ft., good scribing on piece of
rotten fir wood lying at base of Snag, "T27S R2W S32 BT".

D. Fir, alive & standing, now 28", N.21°W. 56.1 ft, shows good
axe scar. In small opening previously made for good scribing, "B"

DID NOT SET BRASS CAP AT CORNER.

New BT's: 10" D. Fir N.12°W. 14.7 ft. Mkd: T27S R2W S31 CS BT.

6" Madrone N.78°E. 21.4 ft. Mkd: T27S R2W S32 CS BT.

Corner lies on top of rocky ridge sloping south.

18

114

Closing Corner for Sections 6 and 5, T28-2W. South Boundary of T27-2W.

Found - Fir, now 42", bark scribing visible. (Orig. mist have been 40")
instead of 4") - S.45°W. 6.0 ft. from face.

Fir, now 48", S.34°E. (not S.57°E.) 53.5 ft. (face) bark scribing
visible, (Orig. mist have been 30", instead of 3".)

Set - Brass Cap at Cor. Mkd: County Surveyor's T28S R2W CG S 6 / S 5
Office, 1962

Orig. BT's: 42" D. Fir bears S.45°W. 7.2 ft. to center of tree.

48" D. Fir bears S.34°E. 55.5 ft. to center of tree.

19

113

Township Corner: S36 | S31 T27S
R3W S 1 | S 6 T28S R2W

Found - All Orig. BT's. as are now stumps. N.E. BT. shows good scribing.
Also find Rock Mound at Corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's S36 | S31 T27S
Office, 1962 R3W S 1 | S 6 R2W T28S

New BT's: 16" Cedar bears S.27°W. 72.0 ft. scribed S1 T28S R3W CS BT.

17" Laurel bears S.3°E. 17.0 ft. scribed S6 T28S R2W CS BT.

4" R. Fir bears N.10°W. 19.8 ft. scribed S36 CS BT.

9" R. Fir bears N.87°E. 50.1 ft. scribed S31 CS BT. T27S R2W.

20

RE-RENEWED CORNER NO. #186

BYRON - FOUND O.K.
RENEWED 10/28/68
THIS CORNER V.R.T.

Milo E. Godfrey, Deputy
Ray Tracy and M. Stone
September 1962
C. S. File No. 49/28